Model:	Traditional Reach-In's:
CD-54R	*Reach-In Solid Swing Door Refrigerator*



CD-54R

- **Stainless steel interior and exterior** retains attractive finish longer.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**
  Heavy-duty pull handle
  Each door with two spring hinges, this make the door self-closing with with enduring quality
- **R290 Refrigeration system** holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- **Electronic control system:**
  Adjustable temperature set point and defrost frequency
  Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath

Bottom mounted units feature:

- ”No stoop” lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	HP	Voltage	Amps	NEMA Config.
			L	D	H					
CD-54R	2	6	54 1371	32-1/2 818	82-1/2 2095	49	1/2+	115/60/1	4.56	5-15P

Plug type varies by country.

CONFORMS TO NSF/ANSI STD. 7

Cooler Depot
Add: 14923 Proctor ave, city of industry, CA,91746
Tel: 626-407-1970 E-mail: homedepot@coolerdepotusa.com

CD-54R Plan View



