

0569



RUBBERIZED CRACK & JOINT FILLER Data Sheet

CRACK STOPPER RUBBERIZED BLACKTOP CRACK & JOINT FILLER

- Fills Cracks Up to 1"
- Non-Shrink Formula
- Seals & Waterproofs
- Best Flexible Seal

DESCRIPTION: CRACK STOPPER® RUBBERIZED CRACK & JOINT FILLER is a commercial grade, high performance rubberized compound for use in the repair of blacktop roads, driveways, pavements, expansion joints and walkways. Crack Stopper provides a long term repair on cracks and joints up to 1" wide. Also excellent for foundation walls and other masonry surfaces. Dries to dark black finish.

PREPARATION: Surfaces should be cleaned with Gardner™ Driveway Kleen™, spray on cleaner & degreaser and free any loose materials, grease, oil and dirt, before filling cracks. Do not allow to freeze.

EASY APPLICATION: Apply on a clear sunny day when surface temperature is 65° F and rising. Cut tip to desired opening and puncture seal. Using caulking gun, squeeze material into crack. After material has cured 24 hours, you may apply a premium driveway sealer or leave by itself. Do not apply if rain is expected within 24 hours. DO NOT HEAT.

CLEAN-UP: Soap and water clean-up immediately after use.

COVERAGE: Provides approx. 32 linear feet of 1/4" bead.

Meets:	ASTM C-834
Color:	Black
Odor:	Mild
Consistency:	Smooth Paste
Flash Point:	Not applicable, waterbased
Dry To Touch:	Tack-free in 1 hour
Cure Time:	3-4 days
% Weight Solids:	82 +/- 1% by Weight
Pigments	Calcium Carbonate
Specific Gravity	1.64
Weight / Gallon	13.5 +/- .5 lbs.
Recommended Storage Temperature:	40° F to 100° F.
Recommended Application Range:	45° F to 100° F.
Shelf Life:	1 Year

Approx. Shipping Weights: (Note: All approx. weights include container.)

12 - 10.1 Fl. Oz. Tubes/Case: 15 lbs.

Cases Per Pallet: 140 Cases

DANGER!: HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN.

CAUTION: For exterior use only. Contains petroleum based products. Keep away from heat, sparks, and open flame. Use only with adequate ventilation. Eye and skin irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not use in drinking water or food systems. Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent).

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC/VOS: 10g/L of material

INGREDIENTS

Calcium Carbonate	CAS# 471-34-1
Acrylic Polymer	Not available, mixture
Diisooheptyl Phthalate	CAS# 71888-89-6
Mineral Spirits	CAS# 8052-41-3
Ethylene Glycol	CAS# 107-21-1
Other additives	

©2007 Gardner-Gibson, Inc.
Manufactured by Gardner-Gibson, Inc.
P.O. Box 5449
Tampa, FL 33675

See SDS for more info

WARRANTY AND DISCLAIMER: Gardner-Gibson, Inc. warrants this product to give satisfactory results when our directions are followed in its use and application, for a period of 12 months from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com