

Specifications

Specifications		SB-1200ER / SB-1200RR
Rated voltage		120V-, 60Hz
Rated power consumption		1450W
Length of Power cord		4' 92"
Water supply method		Direct inlet flow type
Requested water pressure range		10.15 - 108.8psi
Water supply control		Static pressure solenoid valve
Warm water cleaning device	Heat exchange method	Instant heating method
	Rear cleaning	0.13 - 0.18 gal/min
	Front cleaning	0.13 - 0.18 gal/min
	Water pressure control	5 levels (Rear / Front)
	Warm water temperture control	4 levels [OFF (1 levels) ~ 4 levels]
	Nozzle position control	5 levels
	Water Heater capacity	1400W
Heated seat device	Safety device	Temperature sensor, Bimetal, Temperature fuse
	Toilet seat temperture control	4 levels [OFF (1 levels) - 4 levels]
	Seat heater capacity	50W
Drying device	Safety device	Temperature sensor, Temperature fuse
	Warm air temperature control	6 levels [OFF (1 levels)~6 levels]
	Dryer heater	290W
Etc	Safety device	Bimetal, Temperature fuse
	Air bubble cleaning	O
	Remote control	RF Type (2 AA type batteries)
	Seat sensor	Capacitive sensor
	Lighting function	High Brightness Blue LED
Requested water temperature range	Water filter	Option / Segment Filter
	Body material	PP
Requested water temperature range		41 - 95°F (Recommend 50 - 86°F)
Product size (W x L x H)	Elongated	16.9" x 21.5" x 6.1"
	Round	16.9" x 19.8" x 6.1"
Product weight (Net)	Elongated	7.28 lbs
	Round	7.05 lbs

※ These specifications are subject to change without prior notice