

WHITE

WHITE

WHITE

WHITE



FLASHING LAP JOINTS GUTTERS DRAIN SPOUTS ROOF VENTS

Contiene: Esters de ftalato y trimetoxivinilsilano. Puede causar irritación a los ojos y la piel. Podría causar sensibilización alérgica en la piel. Evite el contacto con los ojos y la piel. No lo ingiera. Use guantes y gafas de seguridad. Utilice solamente con ventilación adecuada. Evite respirar los vapores. Asegurar la entrada de aire fresco durante la aplicación y el secado del producto. **PRIMEROS AUXILIOS:** PIEL: Lave cuidadosamente. OJOS: Enjuague con grandes cantidades de agua. INHALACIÓN: Trasládese al aire libre. INGESTIÓN: NO INDUZCA EL VÓMITO. Obtenga atención médica inmediatamente si ocurre exposición excesiva. **Para emergencias,** llame al centro de control de envenenamiento al 800-222-1222. Refiérase a la SDS para más información. Para una SDS contacte a su proveedor o visite dap.com. **MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS. NO PERMITA QUE SE INTRODUZCA EN EL CUERPO.**

ADVERTENCIA Cáncer y daños al sistema reproductor
—www.P65warnings.ca.gov

LIFETIME DURABILITY GUARANTEE: DAP warrants the performance of this product for sealant purposes during the lifetime of your home when used as directed within one year of purchase. If not satisfied, return container & receipt to DAP Products Inc. Tech. Service, 2400 Boston St., Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.

Para obtener las instrucciones y garantía en español, llame al 888-327-8477 o visite dap.com.

QUESTIONS? / PREGUNTAS? Llámenos al 888-DAP-TIPS o visite dap.com y pulse en "Ask the Expert."

GUTTER & FLASHING

ADVANCED EXTERIOR WATERPROOF SEALANT



- ADHERES TO WET OR DRY SURFACES
- 30 MINUTE RAIN READY
- EXTREME TEMP USE 20°F TO 120°F
- 100% WEATHERPROOF
- STAYS FLEXIBLE & CRACKPROOF
- STRONG ADHESION
- PAINTABLE & LOW ODOR
- LIFETIME GUARANTEE

WARNING!

Read back panel carefully for cautions.

¡ADVERTENCIA!

Lea atentamente el panel posterior para otras precauciones.

10.1 FL OZ (300 mL)

FOR BEST RESULTS: Application temperature range: 20°F to 120°F. Not for continuous underwater use, high temp. surfaces or for surface defects. If gap is more than 1/2" deep, use foam backer rod. Store product below 80°F & away from moisture.

INSTRUCTIONS: 1. Remove old caulk, dirt, oily residue, frost and loose material from surface. 2. Trim nozzle at 45° angle to desired bead size. 3. Puncture inner foil seal. 4. Load cartridge into caulk gun. 5. Fill crack or gap with sealant. 6. Allow to cure for at least 30 minutes before exposing to rain. Sealant may still be tacky. Sealant reaches full performance in 24 hours. 7. Paintable in 60 minutes with high quality acrylic latex/ waterborne coatings. Use acrylic primer for oil-based paints. 60 min performance achievable with 3/8" max dia. bead, temp at 73°F minimum & 50% RH. 8. Clean up excess uncured sealant with mineral spirits. Cured sealant must be cut or scraped away. DO NOT use mineral spirits to clean skin.

COVERAGE: 55 linear ft at 3/16" diameter bead

Contains: Phthalate esters and trimethoxyvinilsilane. May cause eye and skin irritation. May cause allergic skin sensitization. Avoid contact with eyes & skin. Do not ingest. Wear gloves & safety glasses. Use only with adequate ventilation. Avoid breathing vapors. Ensure fresh air entry during application & drying. **FIRST AID:** SKIN: Wash thoroughly. EYE: Flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention immediately if complications arise from exposure. **For emergencies,** call poison control center at 800-222-1222. See SDS for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.**

WARNING Cancer & Reproductive Harm —www.P65warnings.ca.gov

VOC CCCS Calif. ARB
<3% wt/wt. (4 g/L)

DAP Products Inc.

Baltimore, MD 21224

Made in Canada for DAP Products Inc. with U.S. and globally sourced materials
dap.com

