

Installation & Usage Guide

1. Quick Installation (Tool-Free)

1.1 Prepare a 5-gallon/19-liter bucket (11.91"-12.5" diameter is recommended for optimal fit). Ensure the bucket is clean, dry, and placed on a flat, stable surface.

1.2 Align the round toilet seat with the top edge of the bucket. Position it evenly to cover the bucket opening completely, then press down gently until the seat snaps and latches securely onto the bucket rim. Installation takes only seconds.

1.3 Verify the fit: Confirm the seat is firmly locked and does not wobble. The reinforced supporting beams should align with the bucket edge to ensure stability during use.

2. Usage Instructions

2.1 To use: Lift the 270-degree swivel cover and sit on the cushioned seat. The widened support area enhances comfort, suitable for all seasons—soft enough to avoid extreme cold or heat. The seat supports up to 300 pounds.

2.2 For hygiene: After use, close the swivel cover to keep the seat clean and prevent mess or odor. The cover's 270-degree design ensures easy access while maintaining cleanliness.

2.3 Optional cleanup: For added convenience, line the 5-gallon bucket with a toilet bag before use to simplify waste disposal.

3. Disassembly & Cleaning

3.1 Remove the seat: Grip the seat firmly on both sides and pull upward to release the latches from the bucket rim. It detaches easily for storage or cleaning.

3.2 Clean the seat: Wipe the high-density polypropylene frame with a damp cloth. Remove the PU cushion (removable design) and wash it with mild detergent, then air-dry thoroughly before reassembly.

3.3 Empty the bucket: If not using a toilet bag, empty the bucket promptly and clean it according to hygiene standards before reuse.

4. Storage & Carrying

4.1 Carry: Use the special grooves on the back of the seat for easy gripping and hanging. It's lightweight and portable, ideal for outdoor trips.

4.2 Store: Disassemble the seat from the bucket when not in use. Store the seat in a dry, clean area. The compact design saves space in backpacks, car trunks, or storage cabinets.

5. Important Notes

- Do not exceed the 300 lbs weight limit to avoid damaging the reinforced beams or seat structure.
- Use only with 5-gallon/19-liter buckets (11.91"-12.5" diameter) for a secure fit. Buckets outside this range may cause instability.
- Keep the cushioned seat and swivel cover clean to maintain hygiene. Ensure the PU cushion is fully dry before reuse to prevent mold.
- Suitable for outdoor activities (camping, boating, hiking, fishing) and temporary indoor use. Store in a dry place to prolong durability.

1. Quick Assembly (Tool-Free)

1.1 Unpack all components: main body (detachable into two parts), removable inner bucket, dual-seal lid, and detachable toilet paper holder/phone seat.

1.2 Assemble the main body: Align the two detachable parts along the nested connection points, press firmly until they lock into place. Ensure the structure is stable without wobbling. When fully assembled with the lid closed, dimensions are 18" L x 15.5" W x 15.7" H.

1.3 Install inner bucket & lid: Place the inner bucket into the main body, ensuring it sits flush. Close the dual-seal lid to activate the odor-proof seal.

1.4 Attach the accessory: Mount the detachable holder to the toilet side (per nested design). It functions as both a toilet paper holder and a phone seat.

2. Usage Instructions

2.1 Toilet mode: Open the dual-seal lid. For hassle-free cleanup, line the inner bucket with a toilet bag (smooth to fit evenly). The seat height is optimized for adult comfort, suitable for individuals under 300 lbs. Hold the toilet sides for extra stability when seated.

2.2 Seat mode: Keep the lid tightly closed—the sturdy construction allows it to be used as a temporary seat, supported by anti-slip lines on the bottom.

2.3 Accessory use: Use the side holder for toilet paper or place your phone on it as a convenient rest.

3. Post-Use Cleanup

3.1 With toilet bag: Seal the bag tightly to lock in odors, remove it from the inner bucket, and dispose of it per local waste rules.

3.2 Without toilet bag: Remove the inner bucket, clean it with water and mild detergent, dry thoroughly, then place it back into the main body. The dual-seal lid minimizes residual odors.

4. Disassembly & Storage

4.1 Disassemble: Unlock the nested main body parts, separate them, then remove the inner bucket, lid, and side holder.

4.2 Store: Nest the two main body parts to save space. Store all components in a dry area (vehicle trunk, cabinet, shed) for emergency use. The lightweight design (5.5 lbs) enables easy transportation.

5. Important Notes

- Do not exceed the 300 lbs weight limit to avoid structural damage.
- Use only on flat surfaces—bottom anti-slip lines enhance grip; avoid uneven/slippery areas to prevent tipping.
- Keep the dual-seal lid closed when not in use to reduce odor diffusion. Regular cleaning maintains hygiene.
- Suitable for outdoor (camping, hiking, road trips) and indoor temporary use (healthcare, parties). Refer to the listing video for additional install tips.