

11. Specifications

Model		HLB-3000ER
Rated Voltage		120Vac, 60Hz
Max Consumption Power		1,260W
Water supply Way	Way	direct-coupled water supply system
	Rated water	0.07~0.74 (MPa)
Water Temperature Wash	Wash (ℓ /min)	0.6 ℓ /min
	Bidet (ℓ /min)	0.55 ℓ /min
	Pressure regulation	Hip wash and Down wash, common (1~5 phase)
	Water temperature adjustment	Regulation 4 stages adjust the four-stage (Off, Low, Medium, High)
	Water temperature heating	1,200W
	Backflow protection devices	For vacuum to prevent, Check valve
	Safety devices	Manually place two metal strips
Constant Temperature Toilet seat	Seat Temperature Control	Adjust the four-stage (Off, Low, Medium, High)
	Seat Heating	55W
	Safety devices	Anti-overheating temperature fuse
Drying	Dryer Temperature	Room temperature-131°F, 5 Levels
	Dryer Heat	250W Actual heating power CA(168W)
	Safety Devices	Thermal fuse
Power cord length		3'-10"
Energy Saving Mode		Yes
User water temperature		53.6°F-93.2°F (12°C~34°C)
Environment temperature		34.4°F-104°F (3°C~40°C)

Product weight	About 8.2 lbs
Size (mm)	<p>Appearance size : 19.1"W x 20.9"D x 8.1"H</p>

※ Recommended water supply pressure are 0.1~0.69MPa

※ The minimum available water supply pressure is 0.07MPa, however under 0.1MPa pressure, water spray pressure might not be adequate.