The New Fix-A-Floor Repair Adhesive Squeeze Tube is designed for those who prefer not to use a caulk gun. It's the same Extra Strength Customized Formula Fix-A-Floor created for the specific use of Re-Bonding Loose and Hollow Tile, Marble, Stone, LVP & Wood floors. The Customizable Precision Tip allows for all grout line applications narrow or wide along with wood & LVP flooring.

Directions: One 10.1 oz. Fix-A-Floor Repair Adhesive Squeeze Tube covers Approximately 2ft x 2ft. (4 sq. ft.).

1. Locate loose or hollow problem areas by tapping with wooden dowel or broom handle. Mark the entire perimeter with chalk, tape or similar.

2. For all tile, marble &stone use a masonry drill bit normally 1/8", 3/16" or 1/4" depending on grout width. Drill 1-3 holes on each side of the tile depending on tile size. Drill STRAIGHT down into grout lines inside the problem areas. For Wood floors, use a small standard drill bit.

3. Vacuum over each hole to remove all dust and debris, lightly tapping with a rubber mallet during vacuuming is helpful.

4. Pull off the resealable cap, Insert the precision tip into the drilled hole measuring for a snug fit. Cut tip to fit hole. Squeeze Fix-A-Floor Repair Adhesive into each hole. Squeeze slowly and steadily. Watch for spillage while moving from one hole to the next place finger over tip. Once the adhesive spills up and out of nearby holes this ensures penetration and complete filling of the problem area.

5. Place weights (5-gallon buckets ½ full of water or similar) on area. Be sure to clean up any excess Fix-A-Floor with a sponge and water; allow it to cure for a minimum of 24 hours. Dries Clear!

6. After drying, grout drilled holes with matching grout; for wood floors use a matching wood filler. Wipe clean with damp sponge and your floor is as Fixed!

Please visit us at www.fixafloorworldwide.com for instructional videos and printable step-by-step instructions!

Por favor visítenos en www.fixafloorworldwide.com para videos instructivos e imprimible paso a paso las instrucciones!

Caution: This product is to be used only for its intended purpose. Be sure to use with adequate ventilation, do not put on face or in eyes, do not swallow or ingest. If so, wash with water. If problems occur consult a physician immediately. Keep it from freezing before use.

Warranty: This product is warranted to be free of manufacturing defects. If a manufacturing defect is found within one year from the date of purchase, such defective product shall be replaced. No warranty either expressed or implied is made regarding the performance of this product since the conditions under which these goods are transported, stored, used or applied are beyond our control. This warranty is made in lieu of all other warranties either expressed or implied and the seller shall not be responsible for consequential, incidental, special or other damages no matter what the cause.

Manufactured by Fix-A-Floor Worldwide, Inc. P.O. Box 422 Jensen Beach, FL 34958

PROUDLY MADE U.S.A. IN AMERICA

8 59704 00349 3