

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Issue date: 3/20/2024 Revision date: 3/20/2024 Version: 1.0

## **SECTION 1: Identification**

### 1.1. Identification

Product form : Mixture
Product name : Sievert MAPP
Product code : 221197

### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Welding and Brazing

### 1.3. Supplier

#### Supplier

Rothenberger USA, Inc. 7130 Clinton Road Loves Park, IL 61111 USA

T T 800-545-7698

## 1.4. Emergency telephone number

Emergency number : ChemTel - Domestic: 1-800-255-3924, International: +1-813-248-0582;

Contract number: MIS9223846

## **SECTION 2: Hazard(s) identification**

### 2.1. Classification of the substance or mixture

### **GHS US classification**

Flam. Gas 1 Press. Gas (Liq.) Simple Asphy Extremely flammable gas

Contains gas under pressure; may explode if heated May displace oxygen and cause rapid suffocation

## 2.2. GHS Label elements, including precautionary statements

### **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : Extremely flammable gas

Contains gas under pressure; may explode if heated May displace oxygen and cause rapid suffocation

Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

Store in a well-ventilated place.

Protect from sunlight. Store in a well-ventilated place.

## 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification

: Contact with the liquefied gas may cause frostbite. Material will accumulate static charges during sliding or agitation and may be ignited by an electrostatic discharge.

3/20/2024 (Revision date) EN (English US) 1/8

### Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Name	Product identifier	%
Propene	CAS-No.: 115-07-1	99.5
Propane	CAS-No.: 74-98-6	0 – 0.5

### 3.2. Mixtures

Not applicable

## **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact

: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation

persists. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do

not use hot water.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot

water.

First-aid measures after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use. Do not induce vomiting without medical advice. Never give anything by mouth to an

use. Do not induce vomiting without medical advice. Never give anything by mouth to ar

unconscious person. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Contains refrigerated gas; may cause cryogenic burns or injury.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. Vapors are heavier than air

and can cause suffocation by reducing oxygen available for breathing.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause frostbite on contact the liquefied gas.

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling. May cause frostbite on contact the liquefied gas.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal

use. May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

## 4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. carbon dioxide (CO2). dry chemical powderr.

3/20/2024 (Revision date) EN (English US) 2/8

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Unsuitable extinguishing media : Do not use water jet.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable gas. Products of combustion may include, and are not limited to: oxides of

carbon.. Toxic fumes.

Explosion hazard : May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed

containers, spreading fire and increasing risk of burns and injuries. Ruptured cylinders may

rocket.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Leaking gas fire:

Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do

so. Move containers away from the fire area if this can be done without risk. Cool closed

containers exposed to fire with water spray.

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant

ignition source and flash back.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommend

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges.

Eliminate every possible source of ignition. Isolate from fire, if possible, without unnecessary risk.

#### 6.1.1. For non-emergency personnel

No additional information available

### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Remove all sources of ignition. Do not flush into surface water or

sewer system. Wear recommended personal protective equipment. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

Provide ventilation.

Methods for cleaning up : Isolate the hazard area and deny entry to unnecessary and unprotected personnel . Provide

ventilation.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Hazardous waste

due to potential risk of explosion.

3/20/2024 (Revision date) EN (English US) 3/8

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Precautions for safe handling

: Handle and open container with care. Do not breathe gas, fumes, vapour or spray. Avoid contact with skin and eyes. Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Do not swallow. When using do not eat, drink or smoke. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Wash contaminated clothing before reuse. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Store away from direct sunlight or other heat sources. Do not expose to temperatures exceeding 50 °C/ 122 °F. Protect containers from physical damage. Store in a well-ventilated place.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Sievert MAPP		
No additional information available		
Propene (115-07-1)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	500 ppm	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.

### Eye protection:

Safety glasses or goggles are recommended when using product.

## Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

3/20/2024 (Revision date) EN (English US) 4/8

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Gas

Liquified Gas. Appearance Color Colorless Odor Distinctive Odor threshold : No data available рΗ : No data available Melting point : No data available Freezing point : -185 °C (-301 °F) Boiling point : -48 °C (-54.4 °F) Critical temperature : 92.4 °C (198.32 °F)

Flash point : <-107 °C (-160.6 °F) Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : Extremely flammable gas.

Vapor pressure : No data available

Relative vapor density at 20°C : 1.49

Relative density : No data available Solubility : Water: 200 mg/l

Partition coefficient n-octanol/water : 1.77

Auto-ignition temperature : 455 °C (851 °F)

Decomposition temperature : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosion limits : No data available

Explosive properties : No data available

Oxidizing properties : No data available

## 9.2. Other information

Critical Temprature : 92.4 °C (198.32 °F)

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No dangerous reactions known under normal conditions of use. Not corrosive to metals.

## 10.2. Chemical stability

Stable under normal conditions. Extremely flammable gas. Contains gas under pressure; may explode if heated.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat. Sources of ignition. Direct sunlight. Avoid static electricity discharges. Incompatible materials.

### 10.5. Incompatible materials

Oxidizing agents.

## 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

## **SECTION 11: Toxicological information**

11.1. Information on toxicologica
-----------------------------------

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

### **Propene (115-07-1)**

 LC50 inhalation rat
 > 65000 ppm/4h

 Skin corrosion/irritation
 : Not classified

 Serious eye damage/irritation
 : Not classified

 Respiratory or skin sensitization
 : Not classified

 Germ cell mutagenicity
 : Not classified

 Carcinogenicity
 : Not classified

## **Propene (115-07-1)**

 IARC group
 3 - Not classifiable

 Reproductive toxicity
 : Not classified

 STOT-single exposure
 : Not classified

 STOT-repeated exposure
 : Not classified

Aspiration hazard : Not applicable
Viscosity, kinematic : No data available

Symptoms/effects : Contains refrigerated gas; may cause cryogenic burns or injury.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. Vapors are heavier than air

and can cause suffocation by reducing oxygen available for breathing.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause

frostbite on contact the liquefied gas.

Symptoms/effects after eye contact

: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling. May cause frostbite on contact the liquefied gas.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal

use. May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

### 12.2. Persistence and degradability

Sievert MAPP	
Persistence and degradability	Not established.

# 12.3. Bioaccumulative potential

Sievert MAPP	
Partition coefficient n-octanol/water (Log Kow)	1.77
Bioaccumulative potential	Not established.

3/20/2024 (Revision date) EN (English US) 6/8

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Propene (115-07-1)
--------------------

Partition coefficient n-octanol/water 1.77 (at 20 °C (at pH 7)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

Other information : No other effects known.

## **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with

local, regional, national and/or international regulation.

Additional information : Handle empty containers with care because residual vapors are flammable. Hazardous waste

due to potential risk of explosion.

## **SECTION 14: Transport information**

In accordance with DOT

## 14.1. UN number

DOT NA No : UN1077

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Propylene

## 14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.1 Hazard labels (DOT) : 2.1



# 14.4. Packing group

Packing group (DOT) : Not applicable

## 14.5. Environmental hazards

Other information : No supplementary information available.

## 14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

### 15.2. International regulations

No additional information available

## 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## **SECTION 16: Other information**

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Issue date : 03/20/2024
Revision date : 03/20/2024
Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



Full text of H-phrases	
Flam. Gas 1	Flammable gases Category 1
Press. Gas (Liq.)	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant

Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

3/20/2024 (Revision date) EN (English US) 8/8