OIL-BASED PRE STAIN WOOD CONDITIONER

NO. B1080 CLEAR

PRODUCT INFORMATION

BEHR® OIL-BASED PRE STAIN WOOD CONDITIONER is a clear sealer designed to promote uniform stain application on soft woods, such as pine, fir, birch , maple and hemlock. Generally, softer woods accept stain in varying degrees creating an uneven and blotchy appearance. This product helps to minimize the variation and prepares wood surfaces for staining with oil-based stains.

RECOMMENDED USES:

Ideal for properly prepared interior bare or stripped wood surfaces prior to applying BEHR Oil-Based Wood Stains.

PRODUCT SPECIFICATIONS:

Resin Type: Oil

Weight per Gallon: 6.6 lb

% Solids by Volume: 8% ± 2%

% Solids by Weight: 10% ± 2%

VOC: < 720 g/L

Flash Point: 108°F

Viscosity: 20 – 30 s (#1 Zahn Cup)

Recommended Film Thickness: N/A

Coverage: Up to 400 sq ft/gal, depending on application method and substrate porosity.

APPLICATION:

Stir thoroughly before using. Do not shake or thin. Use a nylon or nylon/polyester brush or a saturated clean cloth and apply liberally to all areas of the wood surface including edges. Allow to penetrate for 5 to 10 minutes, then remove any excess with clean, dry cloth. Apply BEHR Oil-Based Wood Stain or BEHR Oil-Based Stain & Poly In One.

Brush: Nylon/polyester brush

Thinning: DO NOT THIN. Product is formulated for use at package consistency only.

Dry Time: @ 77°F & 50% RH
Longer dry time may be required in cooler temperatures and higher humidity.

To Touch: 10 minutes

To Apply Stain: After 10 minutes

SURFACE PREPARATION:

All surfaces must be clean, free of dust, oil, grease, wax, polish and all other foreign substances.

New Wood: Sand the wood thoroughly with medium grit sandpaper and progress to fine grit sandpaper. Always sand in the direction of the wood grain. Sand smooth and remove all dust.

Previously Finished Wood: Strip the surface completely down to bare wood with a paint or varnish remover such as BEHR PREMIUM Wood Stain & Finish Stripper No. 64, making sure all previous finishes are removed. Surface must be sanded smooth and remove all dust prior to application.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with mineral spirits or paint thinner, where allowed. Otherwise, use acetone.

DANGER! Rags, steel wool and waste soaked with BEHR OILBASED PRE-STAIN WOOD CONDITIONER may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government control agency.

COMPLIES WITH THE BELOW AS OF 5/1/2020			
SCAQMD	YES	OTC*	YES
CARB SCM 2007*	YES	LADCO*	YES
OTC PHASE II*	YES	AIM	YES

*Small Container Exemption compliance.

CAUTIONS/LIMITATIONS:

- Not for use with water-based stains. For water-based stains pre-treat wood with BEHR WATER-BASED PRE STAIN WOOD CONDITIONER.
- Contents are combustible. Keep away from heat and open flame.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:

DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE LIQUID AND VAPOR. CONTAINS: PETROLEUM DISTILLATES and AN OXIDIZING OIL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. NOTICE: Reports have associated repeated prolonged occupational exposure to solvents with permanent brain damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat and flame. Do not smoke. Prevent build-up vapors by opening all windows and doors to achieve cross-ventilation. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a Behr Paint Company representative, call 1-800-854-0133 Ext. 2 (U.S.A. only). ©2020 Behr Process Corporation, Santa Ana, CA 92705 U.S.A.

Revised 6/2020

OIL-BASED PRE STAIN WOOD CONDITIONER

NO. B1080 CLEAR

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Call physician immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a Behr Paint Company representative, call 1-800-854-0133 Ext. 2 (U.S.A. only). ©2020 Behr Process Corporation, Santa Ana, CA 92705 U.S.A.

Revised 6/2020