

CLEAR

CLEAR

CLEAR

CLEAR

CLEAR



# EXTREME STRETCH

**CAUTION!** Contains ethylene glycol. May cause mild skin irritation. Do not get in eyes, on skin or clothing. Use gloves and safety glasses. Use in well-ventilated area. Do not ingest. **In an emergency, call poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit [dap.com](http://dap.com). KEEP OUT OF REACH OF CHILDREN.**

**¡PRECAUCIÓN!** Contiene etilenglicol. Puede causar irritación leve de la piel. Evite el contacto c/los ojos, la piel y la ropa. Use guantes y gafas de seguridad. Use en un área bien ventilada. No lo ingiera. **En caso de emergencia, llame a un centro de control de envenenamiento al 800-222-1222. Para más información, consulte la Hoja de datos de seguridad (SDS). Para obtener una SDS, comuníquese con su proveedor o visite [dap.com](http://dap.com). MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

**⚠ WARNING** Cancer & Reproductive Harm / **ADVERTENCIA** Cáncer y daños al sistema reproductor—  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

NCCS Calif. ARB VOC < 1.5 wt/wt% (VOC 27 g/L)

**QUESTIONS?/¿PREGUNTAS?**  
Call/Llame al **888-DAP-TIPS** or visit/o visite [dap.com](http://dap.com) & click on/ y pulse en "Ask the Expert."

**DAP Products Inc.**  
Baltimore, MD  
Made in the USA with U.S. and globally sourced materials.  
[dap.com](http://dap.com)

**600%**  
TOTAL STRETCH

**SEALS 3" JOINTS UP TO**

# EXTREME STRETCH

**HIGH PERFORMANCE ACRYLIC URETHANE ELASTOMERIC SEALANT**

- Crackproof & Waterproof
- Adheres to Virtually Any Substrate
- Paintable in 2 Hours
- Easy Water Clean-up & Low Odor
- Interior/Exterior
- Lifetime Guarantee

Read back panel carefully for cautions!  
¡Lea cuidadosamente el panel posterior!

10.1 fl oz (300 mL)

# EXTREME STRETCH

**DAP® EXTREME STRETCH** is a high performance acrylic urethane elastomeric sealant ideal for sealing a wide variety of interior & exterior surfaces such as windows, doors, siding, trim, molding, sinks, countertops & more. It stretches over 600% & provides superior adhesion & long-lasting durability. **EXTREME STRETCH** forms a flexible, 100% waterproof & weatherproof seal to withstand environmental conditions. It is easy to apply & tool, paintable, low in odor & cleans up with water. Cured sealant is mold & mildew resistant. VOC compliant.

**FOR BEST RESULTS:** Apply in temperatures above 40°F. Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temps & higher humidity will slow down dry time. Not for continuous underwater use, filling butt joints, surface defects or tuck-pointing. Joint size should not exceed 3" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material. Store away from extreme heat or cold.

**INSTRUCTIONS:** 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Cut nozzle at a 45° angle to desired bead size. 3. Load cartridge into caulk gun. 4. Fill gap with sealant. 5. Smooth/tool bead. 6. Clean excess wet sealant with damp sponge before it skins over. Dried sealant must be cut or scraped away. 7. Paintable after 2 hours (longer in cool/humid conditions) with latex or oil-based paints. 8. Reseal cartridge for storage & reuse.

**COVERAGE:** 55 linear ft at 3/16" diameter bead.

**LIFETIME GUARANTEE:** DAP warrants this product for sealant purposes during the lifetime of your home, when used as directed, within one year of purchase. Call **888-DAP-TIPS**, with your sales receipt and product container available for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.

**Para obtener las instrucciones y garantía en español, llame al 888-DAP-TIPS o visite [dap.com](http://dap.com).**