QO816L100DS LOAD Center QO MLO 240V 100A 1PH 8SP N1





Main

Marketing Trade Name	QO
Product	Load Center
Cover Type	Surface cover with door

Complementary

Complementary		
Tightening Torque	Main lugs 50 lb.in, AWG 8, aluminium/copper Main lugs 50 lb.in, AWG 6AWG 1/0, aluminium/copper	
Load Center Type	Main lugs	
Rated Current	100 A	
Number of Spaces	8	
Max Short Circuit Current Rating	10 kA	
Maximum Number of Single Pole Circuits	16	
Maximum Number of Tandem Breakers	8	
Number of Phases	1 phase	
Voltage Rating	120/240 V AC	
Wire Size	AWG 8AWG 1 aluminium/copper	
Electrical Connection	Lugs	
Grounding Bar	Grounding bar (ordered separately)	
Electrical Connection	Lugs	
Wiring Configuration	3-wire	
Busbar Material	Tin plated aluminium busbar	
Enclosure Material	Welded sheet steel	
Cover Finish	Baked enamel Gray	
Box Number	4	
Height	12.56 in (319 mm)	
Width	8.90 in (226 mm)	

Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R
Discount Schedule	DE3A
GTIN	00785901785743
Nbr. of units in pkg.	1
Package weight(Lbs)	8.25 lb(US) (3.74 kg)

Returnability	Yes
Country of origin	MX
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	4.60 in (11.684 cm)
Package 1 width	10.80 in (27.432 cm)
Package 1 Length	14.40 in (36.576 cm)
Package 2 Weight	686.00 lb(US) (311.164 kg)
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
DEACh Demilation	☑ REACh Declaration
REACh Regulation	- REACT Declaration
REACh free of SVHC	Yes
<u>-</u>	
REACh free of SVHC	Yes
REACh free of SVHC EU RoHS Directive	Yes Compliant EVEU RoHS Declaration
REACh free of SVHC EU RoHS Directive Toxic heavy metal free	Yes Compliant EVEU RoHS Declaration Yes

Contractual warranty

Environmental Disclosure

Warranty	18 months

Product Environmental Profile