

Foldable Four-Wheel Cart Assembly Instructions

Thank you for choosing our foldable four-wheel cart! This product requires no tools for assembly—follow these simple steps to start using it.

1. Unfold the Cart Frame

Take the folded cart out of its packaging or storage space.

Locate the built-in drawstrings on the cart frame. Pull the drawstrings gently to unfold the frame until it locks into a stable, rectangular shape (you may hear a faint "click" when locked).

2. Install the Wheels

The cart comes with 4 detachable wheels (2 front, 2 rear).

Align the wheel axle with the corresponding holes on the cart frame's bottom corners. Push the wheels firmly into the holes until they fit snugly (no tools needed—manual pressure is sufficient).

Confirm all wheels can rotate freely: Test the front wheels for 360° movement to ensure smooth adjustment.

3. Attach the Storage Bag (If Not Pre-Installed)

The 600D tear-resistant Oxford cloth storage bag is either pre-attached or included separately.

If separate: Spread the bag over the cart frame, and fasten the built-in hooks/straps on the bag to the frame's edges (follow the hook-and-loop or buckle markers for proper alignment).

4. Adjust the Handle

Find the auto-rebound handle on the cart's push side.

Push or pull the handle to adjust its angle (supports 90° forward/backward adjustment) until it reaches your preferred height.

Release the handle to test the auto-rebound function—it should stay off the ground to avoid tripping.

5. Post-Assembly Check

Ensure all wheels are securely attached and rotate without obstruction.

Verify the cart frame is fully unfolded and locked (no wobbling).

Check that the storage bag is fixed tightly to the frame (no loose parts).

Notes for Use & Maintenance

Do not exceed the maximum load capacity (100kg/220lbs) to prevent frame damage.

To fold the cart for storage: Pull the built-in drawstrings again, and fold the frame until it reaches the minimum size (fits trunks/garages).

Clean the storage bag by removing it first (detach hooks/straps) and wiping with a damp cloth; avoid harsh detergents.

If wheels need replacement: Pull the old wheels out of the axle holes, and insert new ones following Step 2.