SAFETY DATA SHEET

1. Identification

Product identifier **BEHR® PREMIUM Interior/Exterior Direct-to-Metal Semi-Gloss Paint - Black**

Other means of identification

Product code 3220

Recommended use Architectural Coating

Recommended restrictions Uses other than the recommended use.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process LLC
1801 E. St. Andrew Place
Santa Ana, CA 92705

Telephone 714-545-7101

Emergency telephone +1 760 476 3962
+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Hazards for the product as sold

Physical hazards Not classified.

Hazards for the product as sold
Health hazards Carcinogenicity Category 1B

Hazards for the product as sold
OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) No additional hazards are known to be associated with the expected conditions of use at the time of publication. This document does not address hazards that may arise from uses not reasonably anticipated by the manufacturer.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Kaolin	1332-58-7	3 - 7
Carbon black	1333-86-4	1 - 5
Ammonium hydroxide	1336-21-6	0.1 - 1
Diphenyl ketone	119-61-9	0.1 - 1

Chemical name	CAS number	%
Sodium nitrite	7632-00-0	0.1 - 1
3-Iodo-2-propynyl butylcarbamate	55406-53-6	0 - 0.1

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Absorb spillage with suitable absorbent material. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Persons susceptible to allergic reactions should not handle this product.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Kaolin (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Ammonium hydroxide (CAS 1336-21-6)	IDLH	300 ppm
Carbon black (CAS 1333-86-4)	IDLH	1750 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total

US. OARS. Workplace Environmental Exposure Level (WEEL) Guide

Components	Type	Value
Diphenyl ketone (CAS 119-61-9)	TWA	0.5 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Use of an impervious apron is recommended.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Color	Black.
Odor	Slight.
Melting point/freezing point	Property has not been measured.
Boiling point or initial boiling point and boiling range	> 99 °F (> 37.22 °C)
Flammability	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Flash point	Not applicable.
Auto-ignition temperature	Property has not been measured.
Decomposition temperature	Property has not been measured.
pH	7 - 10
pH concentration	Property has not been measured.
Kinematic viscosity	Property has not been measured.
Solubility	
Solubility (water)	Soluble (10 - 99%)
Partition coefficient (n-octanol/water)	Property has not been measured.
Vapor pressure	Property has not been measured.
Density and/or relative density	
Density	9.07 lb/gal
Relative density	Property has not been measured.
Vapor density	Property has not been measured.
Particle characteristics	Not available.
Other information	
Dynamic viscosity	Property has not been measured.
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Viscosity	50 - 140 ku
VOC	40 g/l (excluding water) (Coating) 13 g/l (including water) (Material)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Product	Species	Test Results
BEHR® PREMIUM Interior/Exterior Direct-to-Metal Semi-Gloss Paint - Black (CAS Mixture)		
Acute		
Dermal		
ATEmix		1942000 mg/kg bw
Oral		
ATEmix		58480000 mg/kg bw

Components	Species	Test Results
3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	1.1 g/kg
Carbon black (CAS 1333-86-4)		
Acute		
Dermal		
LD50	Rabbit	> 3000 mg/kg
Oral		
LD50	Rat	> 8000 mg/kg
Diphenyl ketone (CAS 119-61-9)		
Acute		
Dermal		
LD50	Rabbit	3535 mg/kg
Sodium nitrite (CAS 7632-00-0)		
Acute		
Inhalation		
LC50	Rat	5.5 mg/l, 4 Hours
Oral		
LD50	Rat	214 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Diphenyl ketone (CAS 119-61-9)	2B Possibly carcinogenic to humans.
Sodium nitrite (CAS 7632-00-0)	2A Probably carcinogenic to humans.

NTP Report on Carcinogens

Carbon black (CAS 1333-86-4) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6)			
Aquatic			
Fish	LC50	Oncorhynchus mykiss	67 µg/l, 96 hours
Carbon black (CAS 1333-86-4)			
Aquatic			
Acute			
Fish	LC50	Leuciscus idus	>= 1000 mg/l, 96 Hours
Sodium nitrite (CAS 7632-00-0)			
Aquatic			
Algae	EC50	Desmodesmus subspicatus	> 100 mg/l, 72 hours
Crustacea	LC50	Australian redclaw crayfish (Cherax quadricarinatus)	4.93 mg/l, 96 hours
Fish	LC50	Oncorhynchus mykiss	0.54 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Ammonium hydroxide (CAS 1336-21-6) -2.66

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to IMO instruments Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA) All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

Sodium nitrite (CAS 7632-00-0) 721.4740

CERCLA Hazardous Substance List (40 CFR 302.4)

Ammonium hydroxide (CAS 1336-21-6)
Sodium nitrite (CAS 7632-00-0)

SARA 304 Emergency release notification

Ammonium hydroxide (CAS 1336-21-6) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Ammonium hydroxide	1336-21-6	100	500		

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Carcinogenicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ammonium hydroxide (CAS 1336-21-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Ammonium hydroxide (CAS 1336-21-6)
Carbon black (CAS 1333-86-4)
Kaolin (CAS 1332-58-7)
Sodium nitrite (CAS 7632-00-0)

US. New Jersey Worker and Community Right-to-Know Act

3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6)
Ammonium hydroxide (CAS 1336-21-6)
Carbon black (CAS 1333-86-4)
Kaolin (CAS 1332-58-7)
Sodium nitrite (CAS 7632-00-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Ammonium hydroxide (CAS 1336-21-6)
Carbon black (CAS 1333-86-4)
Kaolin (CAS 1332-58-7)
Sodium nitrite (CAS 7632-00-0)

US. Rhode Island RTK

Ammonium hydroxide (CAS 1336-21-6)
Carbon black (CAS 1333-86-4)
Kaolin (CAS 1332-58-7)

16. Other information, including date of preparation or last revision

Issue date	05-December-2019
Revision date	28-January-2026
Version #	03
HMIS® ratings	Health: 0* Flammability: 0 Physical hazard: 0
List of abbreviations	DOT: Department of Transportation (49 CFR 172.101). IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG Code: International Maritime Dangerous Goods Code. LD50: Lethal Dose 50%. MARPOL: International Convention for the Prevention of Pollution from Ships. PEL: Permissible Exposure Limit. TWA: Time Weighted Average Value.
References	HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens
Disclaimer	Behr Process LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.