



TECHNICAL DATA SHEET
Latex•ite® TROWEL PATCH®
Manufacturer Product#: 1TPC
UPC#: 090932320161



PHYSICAL PROPERTIES & PERFORMANCE

Appearance: Thick Brown Mixture, dries black.	Maximum VOC: Less than 10 g/l
Application Temperature: 55° F and rising.	Specific Gravity: 1.15-1.25
Viscosity: 5,000-10,000 cps	Weight Per Gallon: 14.1-14.8 lbs. per gallon
Color: Brown	Consistency: Thick mixture
Boiling Point: >212° F	Cure Time (50% relative humidity, 70° F): 24-48 hours.
Freeze ability: Do not allow to freeze.	Container Size & Weight: 1 gallon pail, approx. 14 lbs. per pail

FEATURES

Latex•ite® TROWEL PATCH® is a smooth asphalt repair product. It is designed to repair medium to large cracks, smooth out rough spots and fill minor depressions.

- **1 gallon**
- **Patented black, cement-like formula.**
- **For rough spots, depressions, low spots and medium/large cracks.**
- **No-stir formula. Just trowel and smooth over troubled area.**
- **Allow to fully cure prior to sealing.**
- **Low VOC Formula.**
- **Do NOT apply product over gas and oil stained asphalt: it will not adhere**

SURFACE PREPARATION

Prior to using Latex•ite® TROWEL PATCH® it is important to thoroughly clean the area. Sweep out any loose debris and rinse. Once the area is dry, you are ready to apply.

APPLICATION

Latex•ite® TROWEL PATCH® is designed to repair medium-sized cracks and to smooth out rough spots and minor depressions on asphalt driveways. Prior to using Latex•ite® TROWEL PATCH® it is important to thoroughly clean the area. Sweep out any loose debris and rinse. Once the area is dry, you are ready to apply. Just trowel onto troubled area. Latex•ite® TROWEL PATCH® dries from the top down so it is important not to apply it too thick. **We recommend applying no more than two ½" lifts consecutively.** If the depression or crack is deeper than ½", apply the first layer and let that set up and cure thoroughly prior to applying another layer. Once you finish applying, ensure that it is completely dried and cured prior to sealing.

PRECAUTIONS

Avoid applying when rainfall is likely within 24 hours of application time. Avoid applying when temperatures drop below 55° F. Allow all repaired surfaces to cure 24 hours prior to sealing. When transporting this product, ensure that the container is secured and the lid is secure. Do not allow the container to tumble as this may loosen the lid and allow leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Protective clothing and eyewear should be used during application.

CLEAN UP & STORAGE

Fresh Latex•ite® TROWEL PATCH® will clean up with soap and water. If dried, use a cleaner containing citrus to remove.

!!!CAUTION!!!

Latex•ite® TROWEL PATCH® is for exterior use only. Keep out of reach of children. Keep container capped when not in use. Non-flammable. This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

Emergency & First Aid Procedures:

Eyes: Immediately flush with clean water for 15 minutes while holding eyelids open; consult a physician.

Inhalation: If overcome by mist or vapor, remove from exposure immediately; call a physician. If breathing is stopped or irregular, start resuscitation, administer oxygen.

Skin: Remove any contaminated clothing and wash skin with soap and warm water. Vegetable or mineral oil can remove dry material.

Ingestion: DO NOT INDUCE VOMITING even though vomiting may occur. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Get immediate medical attention.

WARRANTY AND DISCLAIMER

There are no express warranties which extend beyond the description on the face hereof. DALTON ENTERPRISES, INC. DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY, OR OF FITNESS FOR ANY PARTICULAR PURPOSE. Since seller cannot control the manner of use of its products after their sale, seller will not be responsible for any consequential or indirect damages. Rather, seller will, at its options, either replace the goods sold or refund the purchase price. No warranties will apply if the goods are in any way altered or modified after delivery by seller. This warranty does not include labor or cost of labor for the application or consequential damages. This warranty gives you specific rights and you may also have other rights which may vary from state to state.