



30°
FULL HEAD NAIL

ROUNDRIVE® FRAMING NAILS











**MAXIMIZE PERFORMANCE
BY USING PASLODE
NAILS AND NAILERS**



ROUNDRIVE® FRAMING NAILS

FEATURES AND BENEFITS

ROUNDRIVE® BRITE & HOT DIPPED GALVANIZED NAIL FEATURES

DESIGN	FEATURE	BENEFIT	NAIL TYPE
	Full Round Head – provides Round Head performance in a 30° collated strip	Code Recognized (IRC, IBC)	BRITE + HDG
	Offset Round Head – provides tighter nail-to-nail collation for higher capacity nail strips	Less Reloading	BRITE + HDG
	Patented fluted shank designed for easy drive and secure holding strength	Drives Flush	BRITE + HDG
	Rigid Paper-Tape – stands up to rough handling + wet conditions	Less Waste + Fewer Jams	BRITE + HDG
	Red + Black Tip Coatings bond with wood fibers for secure placement (Black PowerBoost™ Coating only available on nails in Fuel + Nail Packs)	Increase drive performance + Holds Tight	BRITE + HDG
	Defined Rings (Ring Shank nails only) – for superior withdrawal strength	Consistent Holding Strength	BRITE + HDG
	Hot Dipped Galvanizing provides corrosion resistant protection	Approved for use in treated lumber	HDG
	Green Polymer Head Coating – added corrosion protection barrier	Superior Stain + Streak Protection	HDG



Patented fluted shank designed for easy drive and secure holding strength

AVAILABLE SIZES

ROUNDRIVE® 30° FRAMING NAILS BRITE

Part #	Length	Diam.	Shank	Finish	Qty./Carton
650272	2"	.113	Smooth	Brite	5,500
650273	2"	.113	Ring	Brite	5,500
650237	2 3/8"	.113	Smooth	Brite	5,000
650238	2 3/8"	.113	Ring	Brite	5,000
405253	2 1/2"	.131	Smooth	Brite	3,000
650836	3"	.120	Smooth	Brite	2,500
650830	3"	.131	Smooth	Brite	2,500
650839	3 1/4"	.131	Smooth	Brite	2,500

Building code compliant, approved per ICC ESR-3072 and ICC ESR-1539
Compatible with most clipped head nailers

ROUNDRIVE® 30° FRAMING NAILS HOT DIPPED GALVANIZED (HDG)

Part #	Length	Diam.	Shank	Finish	Qty./Carton
650381	2"	.113	Ring	HDG	2,000
650382	2-3/8"	.113	Smooth	HDG	2,000
650383	2-3/8"	.113	Ring	HDG	2,000
650384	3"	.120	Smooth	HDG	2,000
650385	3"	.120	Ring	HDG	2,000
650386	3"	.131	Smooth	HDG	2,000
650387	3"	.131	Ring	HDG	2,000
650388	3 1/4"	.131	Smooth	HDG	2,000
650474	3 1/4"	.131	Ring	HDG	2,000
650476	3 1/2"	.131	Smooth	HDG	2,000

Meets ASTM A 153 Class D specifications. Building code compliant, approved per ICC ESR-3072 and ICC ESR-1539
Compatible with most clipped head nailers



MANY SIZES AVAILABLE IN FUEL + NAIL PACKS

