

CLEAR

CLEAR

CLEAR

CLEAR



CAUTION! Contains ethylene glycol. Use in well-ventilated area. Do not get in eyes or on skin. Do not ingest. Use gloves and safety glasses. **In an emergency**, call your poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

PRECAUCIÓN! Contiene etilenglicol. Utilícelo en un área bien ventilada. No permita el contacto con los ojos o la piel. No lo ingiere. Use guantes y gafas de seguridad. **En caso de emergencia**, llame a un centro de control de envenenamiento al 800-222-1222. Refiérase a la Ficha de Datos sobre Seguridad (SDS, por sus siglas en inglés) para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ WARNING Cancer and Reproductive Harm / **ADVERTENCIA** Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov

QUESTIONS? ¿PREGUNTAS? Call/Llame al 888-DAP-TIPS or visit/o visite dap.com & click only/ pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al 888-327-8477 o visite dap.com.

© DAP Global Inc., Baltimore, MD 21224

Made in the USA with U.S. and globally sourced materials.

dap.com

KWIK SEAL ULTRA

ADVANCED SILICONIZED SEALANT

- 100% Waterproof & Crackproof
- 4 Hour Water Ready



EASY WATER CLEAN-UP & LOW ODOR

Kitchen, Bath & Plumbing

Read back panel for cautions!
¡Lea las precauciones en el panel posterior!

10.1 FL OZ (300 mL)

DAP® KWIK SEAL ULTRA® ADVANCED SILICONIZED SEALANT is formulated with innovative ultra-hydrophobic technology that repels water, dirt & stains & offers a lifetime mold & mildew resistance guarantee so the sealant stays looking clean, fresh & new. It is 100% waterproof & crackproof. Strong multi-surface adhesion & excellent flexibility for long lasting durability.

ADHERES TO:

Wood: painted & unpainted • Ceramic • Porcelain • Glass • Most metals • Most plastics • Fiberglass • Drywall • Plaster • Granite • Cultured marble • Brick • Stone • Most common building materials

PHYSICAL PROPERTIES

App. Temp Range:	40°F to 100°F
Ideal Bead Size:	3/16" (recommended)
Coverage:	55 linear ft. at a 3/16" bead size
Skin Time:	5 minutes
Tack Free Time:	10 minutes
Full Cure Time:	24 hours
Paint Ready Time:	Not paintable
Water Ready Time:	4 hours
Mold Resistance:	Lifetime mold & mildew resistance guarantee
Odor:	Very mild
Clean-Up:	Water
VOC Content:	NCCS Calif. ARB VOC <1.5% wt/wt% (VOC 28 g/L)
Shelf Life:	12 months (unopened/ cool & dry conditions)

FOR BEST RESULTS: Apply in temperatures above 40°F. Not for continuous underwater use. Joint width should not exceed 3/8". If joint depth exceeds 3/8", use foam backer rod. Sealant applies white & dries clear in 7-14 days (depending on joint depth, temp & humidity). Sealant is not paintable. Paint surfaces before applying. Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Cut nozzle at 45° angle to desired bead size. 3. Puncture inner foil seal. 4. Load cartridge into caulk gun. 5. Fill gap or joint with sealant. 6. Smooth bead. 7. Clean up excess wet sealant with a damp sponge before it skins over. Clean hands & tools with warm water. Excess dried sealant must be cut or scraped away. 8. Wait 4 hours before exposing to water. Sealant reaches full performance in 24 hours. Regular cleaning of surrounding areas is suggested. 9. Reuse cartridge for storage & reuse.

LIFETIME MOLD & MILDEW RESISTANCE GUARANTEE: DAP warrants that this product will not mildew, crack, peel or separate when used as directed within one year of purchase. If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.