



# PORCH & PATIO ANTI-SLIP FLOOR PAINT

## NO. 6250 (TEXTURED LOW-LUSTRE) ULTRA PURE WHITE®

### PRODUCT INFORMATION

BEHR PREMIUM® Porch & Patio Anti-Slip Floor Paint is a 100% acrylic textured low-lustre enamel that is ideal for interior/exterior applications on wood and concrete porches, patios, pool decks and walkways. It provides a mildew resistant paint finish that resists cracking and peeling, as well as withstands scuffing and fading.

### RECOMMENDED USES:

This product is ideal for porches, floors, decks, basements, patios, siding, trim, furniture and trellises. Not for use on garage floors or areas subject to automotive traffic or hydrostatic pressure. Use on properly prepared, uncoated, previously painted or primed interior or exterior surfaces such as:

- Wood
- Concrete
- Composite Wood

### PRODUCT SPECIFICATIONS:

#### Tint Bases/Max Tint Load:

- No. 6250 Ultra Pure White® 128 fl oz / 2 fl oz
- No. 6230 Deep Base 116 fl oz / 14 fl oz

#### PRE-MIXED COLORS:

- No. 6295 Slate Gray
- No. 6294 Silver Gray

**Gloss:** 0 – 5 @ 60°

**Sheen:** 0 – 5 @ 85°

**Resin Type:** 100% Acrylic

**Weight per Gallon:** 12.5 lb

**% Solids by Volume:** 48% ± 2%

**% Solids by Weight:** 64% ± 2%

**VOC:** <50 g/L

**Flash Point:** N/A

**Viscosity:** 115 – 130 KU

#### Recommended Film Thickness:

- Wet: 21.3 Dry: 10.2 mils @ 75 sq ft/gal
- Wet: 10.7 Dry: 5.1 mils @ 150 sq ft/gal

**Coverage:** 75 – 150 sq ft/gal depending on application method and substrate porosity. Does not include the loss of material from spraying.

### APPLICATION:

**Brush:** Nylon/polyester

**Roller:** 1/4" – 3/8" nap roller, depending on surface texture

**Spray:** Texture sprayer capable of 1 gpm with a 3 mm tip. Do not use with airless sprayer.

**Thinning:** Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

**Dry Time:** @77°F & 50% RH

**To Touch:** 2 hours

**To Recoat:** 4 – 6 hours

Dry times are temperature, humidity, and film thickness dependent.

### SURFACE PREPARATION:

**New or Weathered Wood:** Use a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner. Lightly sand to remove remaining wood fibers/fuzz.

**Note:** WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**Painted Surfaces-Wood:** For a painted surface in sound condition, use a product to clean and prepare the surface. If the coating is failing or peeling, use a paint stripper to remove old coating. Scuff sand glossy surfaces. Use stainless steel or galvanized nails to prevent nail staining. Countersink nail heads, repair imperfections and sand smooth. Remove all dust with a damp cloth, allow to dry.

**Uncoated Concrete or Masonry Surfaces:** Allow new surfaces to cure 30 days. Clean and etch surface using a product such as a muriatic acid etcher (read and follow all manufacturer's label directions) to achieve a textured profile similar to 150 grit sandpaper. Wipe your fingers over the clean, dry floor to check for dust or powder. Ensure there is no residue on your fingers that may have been left from the etcher. If residue is found, rinse the surface to remove residue. Allow the surface to dry completely. Sprinkle a few drops of water onto the surface. If water is quickly absorbed and the surface feels like 150 grit sandpaper, the surface is ready. If not, re-etch.

**Painted Surfaces-Concrete:** For a painted surface in sound condition, use a product to clean and prepare the surface. If the coating is failing or peeling, use a paint stripper to remove old coating or scrape/sand down to a sound concrete surface. Scuff sand glossy surfaces. Clean and spot etch any exposed concrete. Remove all dust with a damp cloth, allow to dry.

COMPLIES WITH THE BELOW AS OF 6/1/2022			
SCAQMD	YES	OTC	YES
CARB SCM 2007	YES	LADCO	YES
OTC PHASE II	YES	AIM	YES

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### SYSTEM RECOMMENDATIONS:

#### Wood:

- 1 coat BEHR PREMIUM® No. 75 Kitchen, Bath & Trim Stain Blocking Primer & Sealer
- 2 coats BEHR PREMIUM® No. 436 Multi-Surface Stain Blocking Primer & Sealer

#### Concrete & Masonry:

- 1 coat BEHR PREMIUM Concrete & Masonry Bonding Primer No. 880
- 2 coats BEHR PREMIUM Porch & Patio Anti-Slip Floor Paint

### CLEAN-UP/DISPOSAL:

Clean all tools and equipment with clean water. Properly dispose of all soiled rags. For disposal of empty containers and unused product, contact your household refuse collection service.

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on areas subject to automotive tires or hydrostatic pressure.
- Painted surfaces may become slippery when wet.
- Do not use on roofs.





## PORCH & PATIO ANTI-SLIP FLOOR PAINT

NO. 6250 (TEXTURED LOW-LUSTRE) ULTRA PURE WHITE®

- For best results, apply at temperatures between 50°F – 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Allow 72 hours before subjecting to normal use.
- After 30 days, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.
- Shelf life under normal conditions is two years unopened.

### GENERAL INFORMATION:

**WARNING! IRRITANT.** CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CONTAINS 2-ETHYLHEXYL BENZOATE, CRYSTALLINE SILICA, AND TITANIUM DIOXIDE. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experience, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**