

Trinkiti DOLMAR




Subject	Carburetor Tamper Resistance
For model	All power cuts, chain saws, blowers, grass trimmers, hedge trimmers, brush cutters, edgers
Country	USA
Description	EPA (US Environmental Protection Agency) regulations require tamper proof carburetors to assure engines maintain exhaust emission compliance. Carburetor service and high altitude adjustments can be made by Authorized Service Centers or Factory Service Centers.

<u>Replacing carburetors</u>: Carburetor service requiring full carburetor replacement – confirm H and L needles are set to factory settings.

Consult the appropriate repair manual and/or operator's manuals for the proper carburetor settings for a specific machine.

Reference Makita/Dolmar Technical bulletin 2012-03M and 2012-41

COMPACT CLASS CHAIN SAWS: EA3201S35B, PS-32C (WALBRO TYPE)



COMPACT CLASS CHAIN SAWS: EA3201S35B, PS-32C (ZAMA TYPE)






FARM CLASS CHAIN SAWS: EA3601F40B, PS-352

CEMENTED CARBURETOR	TAMPER RESISTANT CARBURETOR	REQUIRED TOOLS	FACTORY SETTINGS	HIGH ALTITUDE SETTINGS
	PN 168819-4	DN () , which		




FARM CLASS CHAIN SAWS: EA4300F40B, PS-351, PS-421

			<u> </u>	
CEMENTED	TAMPER RESISTANT	DECLUDED TOOLS	FACTORY SETTINGS	HIGH ALTITUDE
CARBURETOR	CARBURETOR	REQUIRED TOOLS	FACTORY SETTINGS	SETTINGS



MID-RANGE FARM & PRO CHAIN SAWS: DCS5121, EA5000P53G, PS-510, PS-5105






ERVICE notes

2014-22

Power Cutters: EA6100P53G, PS-6100

CEMENTED	TAMPER RESISTANT	REQUIRED TOOLS	FACTORY SETTINGS	HIGH ALTITUDE
CARBURETOR	CARBURETOR	REQUIRED TOOLS	FACTORY SETTINGS	SETTINGS



PRO CLASS CHAIN SAW: DCS642120, PS-6400, PS-7310, PS-7910

I NO OLAGO OII	AIN OAN. DOOG	L 1 L 0,1 O O T 00,	. • 1010,1010	. •
CEMENTED CARBURETOR	TAMPER RESISTANT CARBURETOR	REQUIRED TOOLS	FACTORY SETTINGS	HIGH ALTITUDE SETTINGS
	PN 038-153-515 Zama type DM18	PN 957340020		= Φ = 0
	Engine	Air Filter	L=1-1/4 H=1-1/2	
Replace with tamper resistan	ĹĤ	Available only for Makita		

Available only for Makita

Factory and Authorized Service Centers.

POWER CUTTERS: EK6101, PC-6114

type if service is required

CEMENTED CARBURETOR	TAMPER RESISTANT CARBURETOR	REQUIRED TOOLS	FACTORY SETTINGS	HIGH ALTITUDE SETTINGS
Not Applicable	PN Zama type DM21 Air Filter Air H L	PN 957340020 Engine Available only for Makita Factory and Authorized Service Centers.	H =1-1/2 H=2-1/2	=⊕ =0



Power Cutters: DPC7331, EK7301, PC-7414

CEMENTED	TAMPER RESISTANT	REQUIRED TOOLS	FACTORY SETTINGS	HIGH ALTITUDE
CARBURETOR	CARBURETOR	KEQUIKED TOOLS	FACTORY SETTINGS	SETTINGS
	PN 395-151-025 Walbro type WJ-131	PN 957340030	L= H=	= O = O
	Filter	Engine	L=1-3/8 H=1-1/8	
Replace with tamper resistatype if service is required		Available only for Makita Factory and Authorized		

Service Centers.

MM4 Power Cutters: EK7651H

CEMENTED CARBURETOR	TAMPER RESISTANT CARBURETOR	REQUIRED TOOLS	FACTORY SETTINGS	HIGH ALTITUDE SETTINGS
Not Applicable	PN 168815-2 Walbro type WT-1066	PN 957340030		= O = O
	Engine A Fill		L=2-1/4 H=2-3/8	L=2-1/4 H=1-3/4
	L H	Factory and Authorized		

Service Centers.

POWER CUTTERS: EK8100, PC-8216

CEMENTED CARBURETOR	TAMPER RESISTANT CARBURETOR	REQUIRED TOOLS	FACTORY SETTINGS	HIGH ALTITUDE SETTINGS
Replace with tamper resistatype if service is required		PN 957340030 Engine Available only for Makita Factory and Authorized Service Centers.	H= L=1-1/4 H=1	= O = O





BBX7600, BBX7600CA, BBX7600N, PB-7600.4, PB-7601.4, PB-7602.4


CARBURETOR

JET SIZE

PN 597-60010-00 Walbro type WYK-260



Factory Standard jet= #60 Standard High Altitude jet= #59



EB7650WH, EB7650TH


CARBURETOR

JET SIZE

PN 168859-2 Walbro type WYK-427



Factory Standard jet= #60 Standard High Altitude jet= #59



EM2650LH, EM2652LHN, EN5550SH, EN5950SH, EN7350SH, EM2650UH, EN4950H, EE2650H, EY2650H25H, EN4951SH, PE254.4, MS-246.4C, MS-256.4C, CS-246.4C, ME-246.4, MH-246.4DS


CARBURETOR

JET SIZE

PN 168762-7 Walbro type WYL-287A



Factory Standard Jet = #33.5 Long High Altitude Jet = #32 Long






BHX2500, BHX2500CA, PB-250.4, PB-251.4


CARBURETOR

PN 168641-9 Walbro type WYL-213A



Factory Standard jet = #38.5 Standard High Altitude jet = #37

JET SIZE



EM4251, EM4251CA, EM4250, EM4250CA, MS-251.4 CARBURETOR

JET SIZE

PN 168497-0 Walbro type WYL-125



Factory Standard jet = #34.5 Long High Altitude jet =

