



HEAVY DUTY SEMI-RIGID ALUMINUM DUCT

SKU 604 128, 1005 469 156, 604 774



- This duct is ideal for dryer applications where code requires an all aluminum product
- Totally non combustible with a maximum operating temperature of 435°F
- The continuous lock seam permits the duct to be pulled open, compressed, bent and re-bent without developing leakage
- UL2158A listed and marked for dryer venting purposes
- Thicker than the standard version and allows for easy rotation and more durable handling

Product Code	UPC Code 060672	SKU	Size	Packaging	Pack Qty.	Pack Wt. (lbs)	Pack Cube (cu. ft.)
MFX42CULXHD	310265	604 128	4" x 2' w/collars	Bulk / Cut Case	12	4.6	1.5
MFX46C2ULHD12	148967	1005 469 156	4" x 6' w/collars	Retail Bag / Cut Case	12	9.85	3.78
MFX48ULXHD12	310296	604 774	4" x 8'	Retail Bag / Cut Case	12	12.8	3.78

Code Compliance:

We recommend that you check with the local code body, having jurisdiction in your area, to determine applicable codes. UL 181, NFPA 90A & 90B, BOCA, ICBO, SBCC, HUD/FHA MIN. Property STD.

Flame Spread: Zero

Smoke Developed: Zero

Temperature Range: -100°F to 435°F

Maximum Velocity: 5000 FPM

3" to 10" Diameter

Static Pressure - Positive: 12 in. WC

Static Pressure - Negative: 12 in. WC

