

D1500-2 Series Aluminum Multi Section Extension Ladders



The D1500-2 series aluminum extension ladders have a duty rating of 300 lbs and have extra heavy duty I-beam side rails. The base and fly sections separate easily and can be used separately. Guide brackets help to ease operation when raising and lowering the fly section. The exclusive ALFLO® rung joint means TWIST-PROOF® performance every time. TRACTION-TRED® D rungs are slip resistant, and the rugged shoes rest flat or are held in spur position with the SHU-LOK® feature. Rugged spring-loaded locks operate smoothly. Mar-resistant end caps protect the surface ladder is resting against.

Features

- Alflo rung joint for Twist-Proof performance
- External Guide Brackets
- Mar-resistant molded end caps
- Modified I-beam rails
- Removable section for use as a single ladder
- Rope and pulley system
- Rope clamp ties rope to rung
- Slip-resistant shoe with Shu-lok feature and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

Specifications

Model No.	Size	Reach Height	Max Working Length	Max. Open Extended Length	Approx. Closed Length	Approx. Shipping Weight Lbs.
D1516-2 	16 ft	16 ft	13 ft	13 ft	8 ft	30.5
D1520-2	20 ft	20 ft	17 ft	17 ft	10 ft	37
D1524-2	24 ft	23 ft	21 ft	21 ft		45
D1528-2	28 ft	27 ft	25 ft	25 ft		56
D1532-2	32 ft	31 ft	29 ft	29 ft		67
D1536-2	36 ft	34 ft	32 ft	31 ft	18 ft	80
D1540-2	40 ft	37 ft	35 ft	35 ft	20 ft	89.5