

CAUTION: VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSE EYE, SKIN, NOSE, AND THROAT IRRITATION. Can be absorbed through skin. May cause reproductive hazards. Harmful if swallowed. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe vapors. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not get in eyes, on skin, or clothing. Wash thoroughly after handling.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call poison control center, hospital emergency room, or physician immediately; for skin, wash thoroughly with soap and water. If you experienced difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, call poison control center, hospital emergency room, or physician immediately. If swallowed, do not induce vomiting. Call poison control center, hospital emergency room, or physician immediately. KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

DANGER – RAGS, STEEL WOOL, OR WASTE SOAKED WITH PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL, OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

WARNING: Reproductive Harm – www.P65Warnings.ca.gov.



DOES NOT EXCEED MAXIMUM VOC 100 g/L

UNITED GILSONITE LABORATORIES, 1396 Jefferson Ave., Dunmore, PA 18509  
www.UGL.com

Order No. 32712 L119



EXTERIOR WATER BASE



Poly

H I G H P E R F O R M A N C E

LONGER-LASTING

Light Amber Finish with Superior UV Protection



SATIN

1 QT (946 mL)  
SEE CAUTIONS ON BACK PANEL.

WARNING!  
VAPOR HARMFUL.  
HARMFUL IF INHALED.

**ZAR® Poly HIGH PERFORMANCE** is a long-lasting exterior water base polyurethane providing some of the toughest UV protection available. For exterior surfaces exposed to direct sunlight and harsh extremes of weather. Ideal substrates: Exterior doors and trim, outdoor furniture, and wooden marine surfaces (above water line). ZAR® Poly High-Performance full-bodied formula is self-leveling and dries to a rich, amber tone. Use on bare wood or over ZAR® Stain. **Not for use on decks or other areas subject to foot traffic.**

#### PREPARE WOOD FOR FINISHING

**Stained Steel Doors and Fiberglass Doors:** Wood stain must be thoroughly dry. Do not sand uncoated stained surface.

**New Wood:** Sand smooth using fine sandpaper, vacuum sanding dust. **Do not use steel wool.** To fill open-grained woods use ZAR® Wood Patch.

**Old Clear Finishes in Good Condition:** Remove grease, dirt, and wax. Sand lightly in the direction of the grain to remove any gloss. **Do not use steel wool.** Vacuum all sanding dust.

**Old Clear Finishes in Poor Condition, Lacquer, or Shellac:** Remove completely. If the old finish contains wax, regardless of condition, remove completely. Do not use steel wool. Sand and vacuum all sanding dust.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION:** Stir thoroughly before and during use. Do not shake! Apply straight from the can. Thinning not required. Apply only when air and surface temperature is between 60°F (15.5°C) and 90°F (32°C) and the relative humidity is less than 50%. Can be applied with a brush, synthetic applicator, or spray. Do not use a roller. Apply in the direction of the grain at a rate of 125-150 sq. ft. per quart. Do not over brush and let the poly self-level.

**Note:** When staining an exterior surface before top coating use ZAR® Stain. To ensure satisfactory results always test ZAR® Poly High Performance in an inconspicuous area before completing the entire job.

**DRYING:** ZAR® Poly High Performance dries to the touch in 30 minutes, can be recoated after 2 hours. Drying time will be affected by temperature, humidity and film thickness. If while sanding, sandpaper gums or surface feels tacky, extend drying times. On exterior wooden surfaces apply 3 coats. For steel and fiberglass doors apply a minimum of 2 coats.

**CLEAN UP:** Clean brushes and tools immediately after use in warm soapy water.

**COVERAGE:** Covers up to 125-150 sq. ft. (11.6 m<sup>2</sup>-13.9 m<sup>2</sup>) per quart.