



RUST-OLEUM®

MILK PAINT FINISH

DESCRIPTION AND USES

Rust-Oleum® Milk Paint Finish creates a unique washed effect, perfect for furniture and décor pieces. This one-step paint finish is easy to use and has superior adhesion. Multiple coats can be applied to achieve desired effect.

PRODUCTS

SKU	DESCRIPTION (Quarts)
340248	Navy
340249	Eclipse
339974	Classic White
339976	Kingston Gray
339977	Highland Blue

APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Surface must be free of any dust, grease, oil, stains, rust, or any other substances. Sand glossy surfaces before painting, and remove any loose paint.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION (cont.)

APPLICATION

For interior use only. Do not apply paint on surfaces which are exposed to high humidity. Use when temperature is between 50°F (10°C) and 85°F (32°C) and humidity is below 85% to ensure proper drying.

Stir well before use. A high quality synthetic brush is recommended for application. Apply a light coat to your surface, brushing in a "V" pattern to achieve a washed look. Apply multiple coats to achieve desired coverage.

NOTE: Paint finish will have a subtle texture.

DRY AND RECOAT TIMES

Based on 77°F (25°C) 50% relative humidity. Dries to the touch in 30-60 minutes. May be recoated after 1 hour. Allow more time at cooler temperatures or in high humidity.

COVERAGE

One quart will cover 55-125 sq. ft., depending on surface texture, porosity, and application method.

CLEAN UP

Clean brush and other application tools with soap and water. Clean up any drips or spills immediately.

DISPOSAL

To dispose of empty containers and unused product, contact your local environmental regulatory agency.



RUST-OLEUM®
MILK PAINT FINISH

PHYSICAL PROPERTIES

		MILK PAINT FINISH
Resin Type		Acrylic
Pigment Type		Varies depending on color
Solvents		Water, Glycol Ethers
Weight	Per Gallon	10.6-12 lbs.
	Per Liter	1.3-1.4 kg
Solids	By Weight	46.6-56.28%
	By Volume	32.12-37.27%
Volatile Organic Compounds		<110 g/l
Recommended Dry Film Thickness (DFT) per Coat		1-2 mils
Wet Film to Achieve DFT (Unthinned material)		5-6 mils
Practical Coverage at Recommended DFT (assume 15% material loss)		55-125 sq.ft./qt.
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	30-60 minutes
	Recoat	1 hour
	Full Cure	24 hours
Shelf Life		3 years
Flash Point		>200°F
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.