



A Division of Auto Care Products, Inc.

For Questions or Concerns, Please Call

(800) 992-2018

RoughTex® Rollout Flooring

Installation Tips:

- Flooring should only be installed on clean, smooth, flat surfaces.
- Before installing, sweep the area where you are going to be placing the flooring.
- Clean up oil and any other chemical residue.
- Start unrolling the flooring at the entrance to the garage and work your way back.
- If necessary, use a broom to push any air out from underneath the flooring, working from the center outward.
- Depending on the temperature of the garage, it may take a few days for the flooring to lay completely flat.
- The flooring can be cut to size with a utility knife or scissors. Due to the nature of the material, the flooring may expand during the summer and contract during the winter. Depending upon the climate you live in, the flooring may expand and contract up to 3%. If trimming to fit around areas such as polls, cabinets, workbenches or along walls, during cold weather, please keep in mind that additional trimming may be necessary during hot weather due to expansion.

Mounting to the Floor:

If you wish to secure the flooring your garage floor, we recommend using an indoor/outdoor carpet tape.

Making a Water Tight Seal:

To make a water tight seal between the seams, we recommend using a vinyl backing material and PVC adhesive. Both of these items can be purchased from your retailer or directly from Auto Care Products, Inc.

Cleaning:

To clean your flooring, only use mild household soaps. Do Not Use Solvents, Harsh Chemicals, Abrasive Cleaners or Bleach.

For more information, please feel free to call Customer Service at 800-992-2018 or email info@auto-care.com.

Limited Lifetime Warranty

Auto Care Products, Inc. warrants to the original purchaser that your RoughTex® Flooring is free from defects in material and workmanship for life, subject to the following conditions and limitations:

Condition:

This warranty only applies to the original purchaser.

Limitations:

This warranty does not cover the following:

1. Improper installation.
2. Placement on any surface that is not smooth and flat.
3. Improper use.
4. Mold or mildew.
5. Punctures, cuts or abrasions.
6. Indentations or permanent impressions.
7. Use of solvents, chemicals or harsh detergents.
8. Normal wear and tear.
9. Discoloration that may occur over time.
10. Staining from tires or chemicals.
11. Fading or discoloration due to extended exposure to sunlight.

All warranty claims must be reported to Auto Care Products, Inc. within 30 days of occurrence. Auto Care Products, Inc. at its sole discretion may require photographs of claimed defect(s) and in addition, may require the product to be returned to Auto Care Products, Inc., at the purchaser's expense. If the product, after being returned, is deemed not to be defective, the purchaser will be responsible for all freight charges to return the product back to the purchaser. Upon the determination, by Auto Care Products, Inc., that a product is found to be defective, Auto Care Products, Inc. will either repair or replace the defective product as it deems necessary. Auto Care Products, Inc. will not be held liable for any costs incurred, including but not limited to, installation, removal, disposal, loss of use, loss of revenue or loss of time.