

Irrigation Fittings **Blue Twister®**

The self-threading Double Helix® design of Blue Twister® irrigation fittings provides effortless insertion into PE pipe. No longer is there a need to hammer or walk them into the pipe. Just twist the fitting clockwise into the pipe and let the Double Helix® pull the pipe onto the fitting.

Once the pipe has covered all of the barbs you are assured a connection that does not leak and will withstand the water pressure of your installation.

Features:

- Designed for easy installation without tools.
- Patented self-threading Double Helix® design provides effortless insertion into polyethylene (PE) pipe.
- 100% corrosion resistant.
- Not compatible with compressed air or gases.
- Suitable for underground applications.
- No restriction on number of connections that can be made to achieve desired pipe length.
- Most secure connection requires a hose clamp.

Specifications:

- 160 psi @ 73° F
- Made from polypropylene plastic.
- For use with polyethylene pipe (PE).
- For use with cold water applications only.

Approvals:

- ASTM D-2609
- NSF 61 for potable water
- ANSI/NSF 14 & 7

Installation:

Squarely cut PE pipe to desired length. Slide clamp over end of pipe. Twist fitting clockwise into the pipe until all barbs are covered by pipe. Slide clamp 1/8"-1/4" from the end of the pipe and over the fitting barbs closest to the end of the fitting. Fasten clamp. Check connections after installation.

