



RAPIDFUSE™

Fast Curing Wood Adhesive

CURES IN
30
MINUTES!

Ready to

Plane

Sand

Stain



NO ACTIVATOR NEEDED

Works on All Wood Types

Great for other surfaces: Plastic, Metal, Rubber, Ceramics & More

RapidFuse™ Wood Adhesive

The latest advancement in woodworking adhesives creates a professional strength bond and works on all wood types.

Ready in 30 Minutes

- Ready to plane, to sand, and to stain
- Minimizes clamping time
- Achieves handling strength in 30 seconds
- Repositionable for up to 3 minutes



Professional Strength & Performance

- 40% stronger*
- No swelling, shrinking, or cracking
- Goes 2X further than yellow glue
- Keeps joints tight
- No accelerator needed



Product Details

- Interior/Exterior
- 40 Minute Open Time
- Highly Concentrated Formula: 4 oz. of RapidFuse Wood Adhesive = 8 oz. of traditional yellow glue
- Works on: All Wood Types, ABS, Melamine, Particle Board, Rubber, Steel, Aluminum, PVC, Glass, Stone & More
- 18 Month Shelf-life
- Clean up: Wash skin with warm soapy water. Dried glue can be scraped, sanded or removed using acetone.



*40% stronger than cherry, poplar, and pine woods based on ASTM 3163 testing.



RapidFuse
(NEW Hybrid Technology)




Yellow Glue
(Poly Vinyl Acetate)



Gorilla Glue
(Polyurethane)



Super Glue
(Cyanoacrylate)



2P-10
(Cyanoacrylate)

Repositionability

✓ 30 Seconds up to 3 Minutes	✓ 10-15 Minutes	✓ 2 Steps: Must Dampen Surface	Do Not Attempt Brittle Bond	2 Part System 2 - 4 Seconds
------------------------------	-----------------	--------------------------------	-----------------------------	-----------------------------

Return to Service

✓ 30 Minutes	> 3-8 Hours	> 3-8 Hours	✓ < 30 Minutes	✓ < 30 Minutes
--------------	-------------	-------------	----------------	----------------

Bond Strength

✓ PSI 1296 40% Stronger than PVA & PU	✓ PSI 890	✓ PSI 903	Brittle Bond	Brittle Bond
---------------------------------------	-----------	-----------	--------------	--------------

Long-term Durability (Accelerated Aging)

✓ Plasticizers		✓ Flexible		
----------------	--	------------	--	--

No Swelling No Damage

✓	50% Water Swells Wood	Foam Swells 3X	✓	✓
---	-----------------------	----------------	---	---

Indoor/Outdoor

✓ Interior/Exterior	Interior Only (OD Version Available)	✓ Interior/Exterior	Interior Only	Interior Only
---------------------	--------------------------------------	---------------------	---------------	---------------

YELLOW GLUE



- ✗ Long cure time
- ✗ Long clamp time
- ✗ Damage caused by water content swelling joints

GORILLA GLUE



- ✗ Requires dampening the surface
- ✗ Long clamp time
- ✗ Long dry-time
- ✗ Foaming mess

INSTANT GLUE



- ✗ Activator required
- ✗ Will not survive heavy processing
- ✗ Brittle bonds
- ✗ Low durability
- ✗ Non-repositionable

Product Name	Color	Size	Case Pack	Case Code	Package Code	GTIN14	Case Weight	Case Dims. (LxWxH)	Case Vol. (cu. Ft.)
RapidFuse Wood Adhesive	Clear	.85 OZ.	6	00156	0 70798 00156 5	100 70798 00156 2	1 lb.	7" x 4.75" x 7"	0.135
RapidFuse Wood Adhesive	Clear	4 OZ.	6	00157	0 70798 00157 2	100 70798 00157 9	2.75 lbs.	9" x 5.75" x 9.25"	0.277