



***Longest Lasting Wood Sealer & Water Repellent***

**DIRECTIONS FOR USE  
PLEASE READ PRIOR TO APPLICATION**

**RECOMMENDED USES:**

For use on virtually all properly prepared, exterior wood surfaces such as decks, docks, sidings, specialty hardwoods, pressure treated lumber, garden furniture, playhouses and log/timber frame homes. Do not apply over previously painted or stained wood surfaces without proper preparation. Contact an INSECO representative for detailed specifications.

**SURFACE PREPARATION:**

1. Apply a solution of 1part household bleach or bleach alternative, 1part dishwashing soap and 4 parts water.
2. Scrub and/or pressure wash as necessary to remove any surface contaminants.
3. Apply a test sample of **WOOD Rx** to insure proper adhesion and an appealing appearance. If beading or crawling occurs, contact INSECO prior to applying.

**PUMP SPRAY APPLICATION:**

1. Shake container thoroughly before use.
2. The sprayer is supplied with 3 different tip sizes. Red is small, blue is medium and yellow is large. For most applications, we recommend the **BLUE** tip. Substitute the tip accordingly if more (yellow) or less (red) material is desired. It is recommended that
3. Begin spraying and apply in an even, continuous manner. Saturate the entire surface but **AVOID PUDDLING!** If puddling occurs, use a brush or roller to evenly distribute the excess material. **DO NOT ALLOW PUDDLES TO DRY!**
4. Resists lapping but working with wet edge and back brushing is recommended.
5. Apply 1-2 coats as required to saturate the surface and achieve a uniform appearance. Two coats are recommended for maximum performance. Allow 1-2 hours between coats.
6. **WOOD Rx** may be applied to damp or dry wood.
7. Insure that all areas not to receive product are covered and/or protected from overspray.

**Do not apply if the threat of rain exists. Keep from freezing. Do not use if temperature is below 40 degrees F.**

**RECOMMENDED THINNER:**

WOOD Rx *ultra* does not require thinning and should be used as is, directly from the container.

**CLEAN UP:**

Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

**DRY TIME:**

Allow 12 hours before subjecting to light foot traffic.

**COVERAGE:**

WOOD Rx covers approximately 400 square feet per gallon. Coverage will vary depending on texture, porosity and contour of the surface being coated.

**CAUTION: KEEP OUT OF REACH OF CHILDREN!**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

INSECO, Inc.  
5601 Banner Drive  
Ft. Myers, FL 33912  
800-883-5150  
[www.woodrx.com](http://www.woodrx.com)