UL Rated 1-A, 10-B:C









Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PRO 110 is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder with a tough aluminum valve assembly.

Features bilingual nameplate and carton

At a Glance

- Model PRO 110
- Multipurpose Dry Chemical
- Rechargeable
- **UL** listed
- UL rated 1-A,10-B:C
- U.S.C.G, DOT approved Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Features

- **Multipurpose Fire** Extinguisher
- Aluminum cylinder
- Tough aluminum valve assembly
- Pressure gauge allows for immediate pressure status check
- Rechargeable unit.
- Assembled in Mexico from global components
- 6 year warranty
- UL rated 1-A, 10-B:C
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with optional mounting bracket
- Optional metal strap bracket Pt # 466401
- Powder coated cylinder for corrosion protection



Pt # 21005776 - 4 pack UPC: 0-47871-05776-4 I2F - 10047871057761

Product Specification

For use on the following types of fire:

roduct specification				
Net agent weight (Average)	2.6 lb.			
Unit weight (Average)	rage) 4.0 lb.			
Diameter	3.25 inches			
Height	15.0 inches			
Discharge time	8-12 seconds			
Discharge range	10-15 feet			
Operating pressure	100 psi			
Cylinder	Seamless aluminum			
Valve/handle/lever	Aluminum	ı		
Strap Bracket (not supplied)	U.S.C.G approved	I		

Packaging Options



Packaging dimensions (inches)

	Depth	Width	Height
Carton	3.25	4.25	14.1
Master Pack	11.06	15.5	7

