

1. Identification

| | | |
|---|---|--|
| Product identifier | BEHR DYNASTY™ Interior Color Sample Satin Enamel Paint - Deep Base | |
| Other means of identification | | |
| Product code | DY623 | |
| Recommended use | Architectural Coating | |
| Recommended restrictions | None known. | |
| Manufacturer/Importer/Supplier/Distributor information | | |
| Supplier | Behr Process Corp. 1801 E. St. Andrew Place Santa Ana, CA 92705 | |
| Telephone | 714-545-7101 | |
| Emergency telephone | +1 760 476 3962 +1 866 519 4752 | |
| Access code | 335213 | |

2. Hazard(s) identification

| | | |
|-----------------------------|---------------------|-------------|
| Physical hazards | Not classified. | |
| Health hazards | Sensitization, skin | Category 1A |
| OSHA defined hazards | Not classified. | |
| Label elements | | |



| | | |
|--|--|--|
| Signal word | Warning | |
| Hazard statement | May cause an allergic skin reaction. | |
| Precautionary statement | | |
| Prevention | Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. | |
| Response | If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. | |
| Storage | Store away from incompatible materials. | |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. | |
| Hazard(s) not otherwise classified (HNOC) | None known. | |
| Supplemental information | None. | |

3. Composition/information on ingredients

Mixtures

| Chemical name | CAS number | % |
|---|-------------|---------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-65-0 | 1 - 5 |
| Silica gel, precipitated, crystalline-free | 112926-00-8 | 1 - 5 |
| 3-(2-aminoethylamino)propylmethylmethoxysilane | 3069-29-2 | 0.1 - 1 |

| | | |
|---------------------------------------|------------|---------|
| 2-Methyl-2H-isothiazol-3-one | 2682-20-4 | 0 - 0.1 |
| 5-Chloro-2-methyl-2H-isothiazol-3-one | 26172-55-4 | 0 - 0.1 |

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--|------|------------------------|-------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) | PEL | 5 mg/m ³ | Mist. |
| | | 2000 mg/m ³ | |
| | | 500 ppm | |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value |
|--|------|-----------------------|
| Silica gel, precipitated, crystalline-free (CAS 112926-00-8) | TWA | 0.8 mg/m ³ |
| | | 20 mppcf |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|--|------|---------------------|---------------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) | TWA | 5 mg/m ³ | Inhalable fraction. |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|--|---------|------------------------|-------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) | Ceiling | 1800 mg/m ³ | |
| | STEL | 10 mg/m ³ | Mist. |
| Silica gel, precipitated, crystalline-free (CAS 112926-00-8) | TWA | 6 mg/m ³ | |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

| | |
|---|---|
| Color | Opaque. |
| Odor | Slight. |
| Odor threshold | Not available. |
| pH | 7 - 10 |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | > 99 °F (> 37.2 °C) |
| Flash point | Not applicable. |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | 50 - 140 KU |
| Other information | |
| Density | 9.05 lb/gal |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |
| VOC | 20 g/l (including water) (Material) 46 g/l (excluding water) (Coating) |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | May cause an allergic skin reaction. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | May cause discomfort if swallowed. |

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

| Components | Species | Test Results |
|--|--|---|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 5000 mg/kg, 24 Hours |
| Inhalation | | |
| <i>Aerosol</i> | | |
| LC50 | Rat | > 5 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| Silica gel, precipitated, crystalline-free (CAS 112926-00-8) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC50 | Rat | > 2200 mg/m ³ , 4 hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. | |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | May cause an allergic skin reaction. | |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | Not classifiable as to carcinogenicity to humans. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) | 3 | Not classifiable as to carcinogenicity to humans. |
| Silica gel, precipitated, crystalline-free (CAS 112926-00-8) | 3 | Not classifiable as to carcinogenicity to humans. |
| NTP Report on Carcinogens | | |
| Not listed. | | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) | | |
| Not listed. | | |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. | |
| Specific target organ toxicity - single exposure | Not classified. | |
| Specific target organ toxicity - repeated exposure | Not classified. | |
| Aspiration hazard | Not an aspiration hazard. | |
| Chronic effects | Prolonged inhalation may be harmful. | |
| 12. Ecological information | | |
| Ecotoxicity | Toxic to aquatic life. Harmful to aquatic life with long lasting effects. | |
| Persistence and degradability | No data is available on the degradability of any ingredients in the mixture. | |
| Bioaccumulative potential | No data available. | |
| Mobility in soil | No data available. | |
| Other adverse effects | The product contains volatile organic compounds which have a photochemical ozone creation potential. | |

13. Disposal considerations

| | |
|--|--|
| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. |

14. Transport information

| | |
|---|-----------------------------------|
| DOT | Not regulated as dangerous goods. |
| IATA | Not regulated as dangerous goods. |
| IMDG | Not regulated as dangerous goods. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not established. |

15. Regulatory information

| | |
|---|---|
| US federal regulations | This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are listed on or exempt from the U.S. EPA TSCA Inventory List. |
| TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) | |
| 2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) | 1.0 % One-Time Export Notification only. |
| 5-Chloro-2-methyl-2H-isothiazol-3-one (CAS 26172-55-4) | 1.0 % One-Time Export Notification only. |
| CERCLA Hazardous Substance List (40 CFR 302.4) | |
| Not listed. | |
| SARA 304 Emergency release notification | |
| Not regulated. | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) | |
| Not listed. | |
| Toxic Substances Control Act (TSCA) | |
| Superfund Amendments and Reauthorization Act of 1986 (SARA) | |
| SARA 302 Extremely hazardous substance | |
| Not listed. | |
| SARA 311/312 Hazardous chemical | Yes |
| Classified hazard categories | Respiratory or skin sensitization |
| SARA 313 (TRI reporting) | |
| Not regulated. | |
| Other federal regulations | |
| Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List | |
| Not regulated. | |
| Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) | |
| Not regulated. | |
| Safe Drinking Water Act (SDWA) | Contains component(s) regulated under the Safe Drinking Water Act. |

US state regulations

US. Massachusetts RTK - Substance List

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Silica gel, precipitated, crystalline-free (CAS 112926-00-8)

US. New Jersey Worker and Community Right-to-Know Act

Silica gel, precipitated, crystalline-free (CAS 112926-00-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

16. Other information, including date of preparation or last revision

Issue date 05-November-2020

Revision date -

Version # 01

Further information HMIS® is a registered trade and service mark of the ACA.
D - Face Shield, Gloves, Apron

HMIS® ratings Health: 2
Flammability: 0
Physical hazard: 0
Personal protection: D

List of abbreviations DOT: Department of Transportation (49 CFR 172.101).
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG Code: International Maritime Dangerous Goods Code.
LC50: Lethal Concentration, 50%.
LD50: Lethal Dose, 50%.
MARPOL: International Convention for the Prevention of Pollution from Ships.
PEL: Permissible Exposure Limit.
TWA: Time Weighted Average Value.
STEL: Short-Term Exposure Limit.

References HSDB® - Hazardous Substances Data Bank

Disclaimer Behr Process Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.