



FENCE POST BLACK BEAUTY ASPHALT FENCE PAINT Data Sheet

- Weather Proofs
- Prevents Rot & Decay
- Prevents Rust
- Use Above & Below Grade
- Water Clean Up

DESCRIPTION: FENCE-POST Black Beauty Asphalt Fence Paint is a high performance waterbased paint for wood fences. This product penetrates and seals wood to provide a tough, weatherproof finish. Black Beauty helps prevent rot, decay, and reduces insect infestation on wooden surfaces. This easy to apply product is great for above and below grade applications. Black Beauty is also a great anti-corrosive coating for metal pipes, storage tanks and vertical masonry surfaces. (This product is black in color.)

PREPARATION: Clean all areas to be painted. Be sure to remove all dirt, dust, rust and other debris that may hinder adhesion to the substrate. Surfaces must be allowed to dry prior to application. If there is any question regarding compatibility, test a small section first.

FOR BEST RESULTS: Stir contents thoroughly before use. Do not thin. Apply on a clear day when air and surface temperatures are above 60°F and rising. Do not apply if there is a chance of rain within 24 hours.

APPLICATION: For exterior use only. Apply using a paint brush or 3/4" to 1" nap paint roller. Most surfaces will cover in a single coat, however, severely weathered areas may require an additional coat. Product can also be sprayed with a professional airless sprayer.

COVERAGE RATE: Approximately 75-80 sq. ft. per gallon on wood surfaces and 100 sq. ft. per gallon on metal surfaces.

CLEAN-UP: Clean tools with water, or with mineral spirits on dried paint.

PRECAUTIONS: Not designed for plastic or synthetic type of fences. Not for surfaces with foot or vehicle traffic. When transporting this product, ensure that lid is tight and can is secure and upright. Do not allow can to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. Do not reuse empty containers. Do not use in drinking water or food systems. Protect from freezing.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

| | |
|---|--|
| Weight Per Gallon, lbs. | 8.7 lbs. |
| Residue by Evaporation, % | 40 min. |
| Consistency | Squeegee, Brush or Spray |
| Cure Time (50% Relative Humidity, 70°F) | 4-8 hours |
| Full Cure (50% Relative Humidity, 70°F) | 24-48 hours |
| Application Temperatures | 60°-120°F |
| Clean-up Tools | Water or with Mineral Spirits on dried paint |

Approx. Shipping Weights: (Note: All approx. weights include container.)

| | |
|----------------------|----------|
| 4.75 gallons (18 L) | 43 lbs. |
| 55 gallons (208.2 L) | 500 lbs. |

**CAUTION: HARMFUL OR FATAL IF SWALLOWED.
KEEP OUT OF THE REACH OF CHILDREN.
FOR EXTERIOR USE ONLY.
USE WITH ADEQUATE VENTILATION.**

Contains petroleum based products. Eye and skin irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use.

CALIF. PROP. 65 • WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

Warning! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

VOC/VOS - less than 10 g/L (.075 lbs./gal.)

COMPLIANCE: California products meet Los Angeles County A.P.C.D. (Rule #102) and SCAQMD rules.

Asphalt C.A.S.# 8052-42-4
Clay C.A.S.# 1302-78-9
Water C.A.S.# 7732-18-5
This product is asbestos free.
PATENT PENDING

© 2009 Gardner-Gibson, Inc.
Manufactured by:
Gardner-Gibson, Inc., P.O. Box 5449, Tampa, FL 33675

WARRANTY AND DISCLAIMER:

Gardner-Gibson, Inc. warrants this product to give satisfactory results when our directions are followed in its use and application, for a period of 12 months from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

See MSDS for more info

Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com