



## Urethane Alkyd Semi-Gloss Enamel

- Professional Quality Interior/Exterior Semi-Gloss Finish
- Performance of an Oil-based Paint with Easy Soap & Water Clean-up
- Outstanding Flow & Leveling
- Excellent Adhesion
- Less Odor than Oil-based Paint
- Durable Hard Finish
- Easy Stain Removal
- Mildew-Resistant Paint Finish

NO. 3900 White  
NO. 3930 Deep Base



**2 Coats Recommended**  
for Optimal Durability



**Spread Rate:**  
Rough 350-400 Sq. Ft.  
Smooth 500-550 Sq. Ft.



**Dry Time:**  
2-4 Hr. Dry to Touch  
4-8 Hr. Recoat



**Soap & Water**  
Clean-Up

**WHITE:** READY TO USE OR ADD TINTING COLORANTS.  
**DEEP BASE:** DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.  
PROTECT FROM FREEZING.

### WHERE TO USE

Properly prepared and primed wood, hardboard, metal, drywall, plaster, concrete, masonry and other sound above-grade interior/exterior surfaces. Ideal for Doors, Trim, Molding, Cabinetry, Walls, Railings and Wrought Iron. **Do not use on horizontal surfaces subject to foot traffic.**

### PREPARATION† (Proper Surface Preparation is Required)

All surfaces must be clean, sound, dry and free of any dirt, oil and grease stains. Remove mildew stains with a mildew stain removing product. Interior Wood Trim, Door & Cabinetry: Remove all loose and peeling paint; scuff sand glossy surfaces; caulk and repair imperfections. Sand all wood surfaces in the direction of the wood grain to the desired smoothness. Remove all dust from sanded surfaces with a damp, lint-free cloth. Exterior Wood: Use a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner. Thoroughly rinse the treated surfaces with clean water and allow to dry before any paint application. Interior/Exterior Concrete & Masonry: Allow new stucco, plaster and masonry to cure for 30 days. Use a concrete & masonry degreaser & cleaner to clean and prepare the surface. Powerwash to remove chalk on exterior surfaces. Interior/Exterior Metal: Etch galvanized metal. Follow all label instructions.

### PRIME

On Interior/Exterior surfaces with heavy stains, new wood, metal, concrete and masonry surfaces, use a product such as BEHR® Multi-Surface Interior/Exterior Stain-Blocking Primer & Sealer No. 436 prior to topcoating with this product.

### \*LIMITED WARRANTY

For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. To obtain warranty service, call 1-800-854-0133. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).



©2021 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A. • behr.com  
V.O.C. <50 g/L • REV. 05/21

### APPLICATION

DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity. Use adequate ventilation during application and drying process. Certain colors may require 2 or more coats to achieve complete hide and coverage. Use product when air and surface temperatures are 50-90°F (10-32°C). Apply a thin coat using a high quality synthetic brush, 1/4"-3/8" nap roller or an airless sprayer (.013"-.017" spray tip). NOTE: If touch-up is necessary, same application method is recommended.

### DRY TIME

Darker colors may require additional dry time. Longer dry time required in cooler temperatures and higher humidity. Wait at least 7 days before rinsing or cleaning the surface with a mild, non-abrasive detergent

### DISPOSAL

Properly dispose of all soiled rags. For disposal of empty containers and unused product, contact your household refuse collection service.

†**WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING** Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS: DURON, SODIUM LAURETH SULFATE, CRYSTALLINE SILICA AND TITANIUM DIOXIDE. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust.** Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**