



# MSDS

## MATERIAL SAFETY DATA SHEET

### 1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED): Homax Wall Texture Pro Grade- Orange Peel  
PRODUCT CODES: 4555  
SUPPLIER/MANUFACTURER'S NAME: Homax Group, Inc.  
ADDRESS: 1835 Westerly Rd. Suite 101  
Bellingham, WA 98226  
CHEMTREC EMERGENCY NO.: 1-800-424-9300 (United States)  
1-703-527-3887 (International Collect)  
BUSINESS PHONE: 1-800-729-9029  
DATE OF PREPARATION: May 14, 2012

### 2. COMPOSITION and INFORMATION ON INGREDIENTS

<u>CHEMICAL NAME</u>	<u>CAS #</u>	<u>WEIGHT %</u>
Nepheline Syenite	37244-96-5	30-35%
Calcium Carbonate	1317-65-3	30-35%
Ethanol	64-17-5	15-20%
Propane/Isobutane blend	68476-86-5	5-10%
Diacetone Alcohol	123-42-2	1-5%
Isopropanol	67-63-0	1-5%
Silica Quartz	14808-60-7	.01-1%

\*The ingredients in the balance of this product do not contribute significant hazards beyond those described in this document. All pertinent health, safety and environmental information has been presented, per the requirements of the US Federal OSHA Hazard Communication Standard (29CFR 1910.1200).

### 3. HAZARD IDENTIFICATION

INHALATION: Causes respiratory tract irritation. Symptoms of exposure can include coughing, sneezing, shortness of breath, and nasal discomfort. Can cause central nervous system depression. Symptoms of exposure include headache, dizziness, drowsiness, intellectual impairment, pale skin, ringing in the ears, nausea, vomiting, and loss of coordination. Respiratory symptoms may be delayed in onset. High concentrations of exposure can lead to unconsciousness.

EYE CONTACT: Causes irritation, possibly severe. Prolonged exposure can cause pain, drying of the conjunctiva and possible permanent damage to the conjunctiva and cornea. Symptoms of eye exposure may include redness, pain, and tearing.

SKIN CONTACT: Causes irritation. Prolonged skin contact may result in redness, irritation, and dermatitis. Components of this product may be harmful if absorbed through skin.

INGESTION: Ingestion is not anticipated to be a significant route of occupational exposure. If the material is swallowed, irritation of the mouth, throat, and other tissues of the gastro-intestinal system may occur. Ingestion of large amounts may cause central nervous depression.

**CHRONIC:** Long-term skin contact may result in dermatitis. Prolonged or repeated exposure may cause liver, kidney and blood effects. Can cause nerve damage to arms and legs, effects may be permanent.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Pre-existing conditions of conjunctivitis and dermatitis. Pre-existing respiratory, liver, kidney or blood conditions.

---

#### 4. FIRST-AID MEASURES

SKIN CONTACT: If on skin, wash thoroughly with soap and water. If any product remains, gently rub with vegetable oil, baby oil or petroleum jelly to remove.

EYE CONTACT: Flush immediately with large amounts of water for at least 15 minutes. Have victim "roll" eyes to rinse under eyelids. Seek medical attention if irritation persists.

INHALATION: If vapors, mists, or sprays of this product are inhaled, remove victim to fresh air. Victim must seek immediate medical attention if any adverse exposure symptoms develop. If necessary, use artificial respiration to support vital functions.

INGESTION: If this product is swallowed, do not induce vomiting. Have victim drink 2-3 glasses of water and obtain medical treatment immediately. Do not give anything by mouth to an unconscious person.

---

#### 5. FIRE-FIGHTING MEASURES

FLASH POINT: - 137.93 F (Propellant)

FIRE EXTINGUISHING MATERIALS: Use extinguishing material suitable to the surrounding fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: When involved in a fire, this material may decompose and generate toxic fumes.

SPECIAL FIRE-FIGHTING PROCEDURES: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored. Cool fire exposed containers with water. Protect against bursting cans.

---

#### 6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: In case of a spill, clear the affected area. Remove all sources of ignition if safe to do so and ventilate area.

RESPONSE TO SMALL RELEASES: Proper protective equipment should be used. Stop the source of the spill if safe to do so. Contain the spill and collect liquid with an absorbent material. Clean spill area with soap and water. Place collected material in an appropriate container for disposal.

RESPONSE TO LARGE RELEASES: Clean up should only be done by qualified personnel. Responders should wear proper protective equipment. Absorb spilled liquid with polypads or other suitable absorbent materials. Decontaminate the area thoroughly. Place all spill residues in a suitable container and seal.

DISPOSAL: Dispose of all materials in accordance with federal, state and local requirements.

---

#### 7. STORAGE and HANDLING

STORAGE AND HANDLING PRACTICES: Store containers upright in a cool, dry location, away from direct sunlight, and sources of heat. Use in an upright position and with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor or spray mists. Wash thoroughly after use. Do not eat or drink while using this material.

NFPA 30b AEROSOL STORAGE LEVEL: 1

---

#### 8. EXPOSURE CONTROLS - PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to prevent build-up of flammable vapors and inhalation of vapors and spray mists.

RESPIRATORY PROTECTION: If adequate ventilation cannot be guaranteed, use NIOSH approved respirators to control dusts, mists, fumes or vapors, following manufacturer's instructions. Maintain airborne contaminate concentrations below guidelines listed in Section 2 (Composition and Information on Ingredients). Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres use of a full-face-piece pressure/demand SCBA or a full face-piece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (29 CFR 1910.134).

EYE PROTECTION: Use approved safety goggles or safety glasses, as described in OSHA 29 CFR 1910.133. If necessary, refer to U.S. OSHA 29 CFR 1910.133.

HAND PROTECTION: Chemical impervious gloves (e.g., Neoprene or Nitrile) may be used. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or the appropriate standards of Canada.

---

## 9. PHYSICAL and CHEMICAL PROPERTIES

APPEARANCE and ODOR: White slurry with a mild odor in an aerosol can.

RELATIVE VAPOR DENSITY (air = 1): Not determined.

SPECIFIC GRAVITY: Not determined.

SOLUBILITY IN WATER: Partial

VAPOR PRESSURE: Not determined.

pH: N/A

---

## 10. STABILITY and REACTIVITY

STABILITY: Stable under normal circumstances of use and handling.

DECOMPOSITION PRODUCTS: Oxides of carbon.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: This product is not compatible with strong oxidizers, acids and bases.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid contact with incompatible chemicals, heat, and all sources of ignition.

---

## 11. TOXICOLOGICAL INFORMATION

SUSPECTED CANCER AGENT: The following table summarizes the carcinogenicity listing for the components of this product that are considered to be, or suspected to be, a carcinogen by the listed agency.

CHEMICAL	IARC	NTP
Silica Quartz (< .1%)	1	Y

CHEMICAL	Prop 65 (Reproductive, Cancer)
Silica Quartz (< .1%)	Cancer (Respirable Form)

**This product was not tested as a whole. Component data follows:**

**Ethanol**: Acute Oral - Rat: LD<sub>50</sub>: 7060 mg/kg

**Diacetone Alcohol**: Acute Oral-Rat:LD<sub>50</sub>: 4000 mg/kg

**Isopropanol**: Acute Oral-Rat:LD<sub>50</sub>: 5045 mg/kg

---

## 12. ECOLOGICAL INFORMATION No data available

---

## 13. DISPOSAL CONSIDERATIONS


Dispose in accordance with appropriate U.S. Federal, State, and local regulations.

---

#### 14. TRANSPORTATION INFORMATION

GROUND TRANSPORT (US DOT): LIMITED QUANTITY

LABEL:



AIR TRANSPORT (IATA): NOT EVALUATED

MARINE/WATER TRANSPORT (IMDG): NOT EVALUATED

---

#### 15. REGULATORY INFORMATION

##### ADDITIONAL U.S. REGULATIONS:

EPA REPORTING REQUIREMENTS: The following reporting requirements are applicable to components of this product:

CHEMICAL	SECTION 313 (40 CFR 372.65)
Isopropanol	YES
Propane	YES
Isobutane	YES

U.S. SARA SECTION 311/312 FOR PRODUCT: Acute health effects; chronic health effects, flammable.

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

“WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.”

##### ADDITIONAL CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: The components of this product are listed on the DSL Inventory.

---

#### 16. OTHER INFORMATION

Disclaimer: As the handling and use of products under user's conditions are beyond our control, no warranty, expressed or implied, including, but not limited to merchantability or fitness for a particular use, is made concerning this product. The user assumes all risk of use or handling whether or not in accordance with any directions or suggestions of the supplier. Seller shall not be liable to purchaser or any other person for loss or damages directly or indirectly arising from the use of our products, from breach of any warranty or from any other cause, the exclusive remedy against the seller being to require replacement or repair of defective goods.