



UNION UNITED COATINGS

# ROOF MATE FABRIC

**POLYESTER REINFORCEMENT  
FOR PENETRATIONS  
& SEAMS**

**DESCRIPTION:** United Coatings™ Roof Mate™ Fabric is stitch-bonded, 100% polyester material and is part of the Roof Mate™ Coating System. It is used in conjunction with United Coatings™ Roof Mate™ Butter Grade Flashing to repair or reinforce penetrations and seams. Roof Mate™ Fabric offers a combination of high-strength properties and good elongation for excellent thermal stress resistance. The fabric is very pliable and is designed to conform to irregular and dissimilar surfaces.

**INSTALLATION:** United Coatings™ Roof Mate™ Fabric should be installed as required after application of any primers or caulk, and prior to application of the coating on the roof. Cut the fabric to the desired length. Slit the bottom half of fabric used around vent pipes and other circular protrusions so that it lies flat. Utilizing a roller or brush, apply a 8" inch (203 mm) wide strip-coat of Roof Mate™ Butter Grade Flashing at 15 – 20 mils (0.381 – 0.508 mm) thick over areas to be treated. Immediately embed fabric into wet coating and work it with a brush so that it is saturated with coating.

Apply an additional 15 – 20 wet mils (0.381 – 0.508 mm) over the top to completely encapsulate the fabric. All reinforcement fabric must be 100% adhered to the substrate, with no tenting or air pockets.

See [gaf.com](http://gaf.com) for more information.

**STORAGE & HANDLING:** Store in a clean, dry location and out of direct sunlight.

**IMPORTANT:** Repair leaks promptly to avoid adverse effects, including mold growth.