

# B Dieline Standard Metal Quart 13.75 x 4.562

**DRY TIME:** At normal temperatures, 70°F (21°C), Cabinet Transformations Basics dries to the touch in 30 minutes and to recoat in 2 hours. Wait at least 12 hours before reinstalling the cabinet doors and 24 hours before normal usage. Full adhesion and hardness develop in 7 days.

**CLEAN UP:** Soap and water

**COVERAGE:** Up to 200 sq. ft., or 80 linear ft., with 2 coats depending on surface texture, porosity and application.

Max VOC 50 g/L

**PRECAUTIONS:** Do not take internally. Use only with adequate ventilation. Do not breathe dust, vapors, or spray mist. Ensure fresh air entry during application and drying. Close container after each use. Avoid contact with skin and eyes. Wash thoroughly after handling. First Aid: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of contact, immediately flush skin with soap and water and eyes with plenty of water. If swallowed, get medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN.**

For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)481-4785.

**WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

**SATISFACTION GUARANTEED:** If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-901-0411 for a product replacement or full refund of the purchase price. Refer to product number and batch code.

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®**

## Cabinet Transformations® BASICS

### CABINET & TRIM PAINT

LINEN



OUTSTANDING FLOW & LEVELING

SMOOTH DURABLE FINISH

QUICK DRY FORMULA

SOAP & WATER CLEANUP

SEMI-GLOSS

ONE QUART (32 FL OZ) 946 mL



Cabinet Transformations® Basics is an easy-to-use paint that will transform outdated cabinets and trim. Formulated to provide a beautiful and durable finish, Basics provides an easy-to-clean surface that resists dirt, grime, and mildew. Product can also withstand household chemicals, making it ideal for kitchens, bathrooms, laundry rooms, and more.

**READ ALL INSTRUCTIONS BEFORE BEGINNING PROJECT**

**INTERIOR USE ONLY, NOT RECOMMENDED FOR EXTERIOR**

**PAINTING CONDITIONS:** Apply when temperature is 50-90°F (10-32°C) and relative humidity is below 80% to ensure proper drying.

**PREPARATION:** Surface must be free of any dust, grease, oil, stains, rust, wax, or any other substances. To ensure proper adhesion thoroughly scrub cabinet and trim surfaces with a degreaser and prime the surfaces prior to application of the cabinet and trim paint.

**DEGLOSSING:** Thoroughly scrub cabinet and trim surfaces with a degreaser to remove dirt and grease from existing finishes. Thorough preparation of the existing surface with a degreaser will produce optimal results and maximum adhesion.

**PRIMING:** Use Zinsser Bulls Eye 1-2-3® Primer or B-I-N® Primer-Sealer to improve adhesion and help hide stains or tannin bleed that may occur. Priming is especially important on bare wood cabinet surfaces or when painting over dark colors.

**APPLICATION:** Shake or stir well before use. May be applied with a synthetic (nylon, polyester or blend) bristle brush, roller, pad applicator, or airless sprayer. For an airless sprayer, follow manufacturer's instructions when using spray equipment. Use a 0.017" tip at 2000 to 2600 psi. Wear NIOSH approved respirator and provide adequate ventilation. First apply an even, light coat of cabinet and trim paint to cabinet frames, rails and cabinet door backs. Allow to dry 2 hours. Then repeat with a second coat. Allow second coat to dry 2 hours. After door backs are dry, flip over and repeat the two coat process on the door fronts, allowing 2 hours dry time between coats. If applying over a contrasting color, additional coats may be required. Dry times may vary depending on temperature and humidity levels.

000000

**RUST-OLEUM CORPORATION**

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-901-0411 rustoleum.com

Made in USA

©2021 Rust-Oleum Corporation XXXXXX 0721

XXXXXX LINEN WHITE



Left Copy Margin 7/8"

Overlap to 13/16"

Background should extend to the 1/2" glue lap

Copy Margins all 4 sides

7/22/21	SA	Woodcare
WDC_0004_0121		
Principal Display Panel: 25.09 sq in		Signal Word: N/A Statement of Hazard: N/A
Other Cautionary Material: N/A		Other Cautionary Material (Back label): .078"
Other Cautionary Material (Address): .078"		Net Wt: .125"

All dimensions are based on the measurements within the label at 100% actual size.