

DRY TIME
Tiempo
de Secado



1
HOUR

RECOAT
Tiempo
de Secado
Entre Capas



HOURS

WHERE TO USE: Properly prepared and primed, new or previously painted, horizontal wood, incidental metal, concrete basement floors, patios, breezeways, decks, steps, and porches. Some surfaces coated with this product may become slippery when wet. **Please use caution.** Do not use on surfaces that are frequently damp. Not recommended for use on garage floors or carports that are subject to tire traffic. **COVERAGE:** Approximately 300 to 400 sq. ft. (28 to 37 sq. meters) per U.S. gallon (3.78 L) on primed, smooth, nonporous surfaces. Coverage figures do not include material loss due to application. Some colors, drastic color changes, or porous surfaces may require more than one coat to achieve a uniform finish. **SURFACE PREPARATION:** Surface must be clean and dry. Remove all loose, peeling paint, dirt, mildew, grease, oil, chalk, rust, and any other surface contaminants. Blistering and peeling issues are commonly caused by moisture behind the paint film. Problems leading to excessive moisture in the substrate must be repaired prior to painting. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. New concrete should age a minimum of 30 days. Etching with acid is usually not required, but is recommended for optimum performance over smoothly troweled or new concrete. If acid etching, follow manufacturer's recommendations. This product is self-priming in most applications. When applied to an uncoated substrate or to bare wood, two coats are required with the first coat acting as the primer. Prime incidental metal surfaces with a metal primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

APPLICATION: Stir thoroughly. Apply with a high-quality brush, roller, paint pad, or by spray equipment. If spray applied, back rolling or back brushing is recommended. When using more than one container of the same color, intermix to ensure color uniformity. Thinning is not required. However, for the first coat over a new or porous substrate, 1/4 pint (118 mL) of water per U.S. gallon (3.78 L) may be added. Apply when air, product, and surface temperatures are above 50°F (10°C) and surface temperature is at least 5°F (3°C) above the dew point. Air and surface temperatures must remain above 50°F (10°C) for the next 24 hours. Avoid exterior application late in the day when dew and condensation is likely to form or if rain is expected. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat. Do not overbuild. For best final appearance, work from unpainted into painted areas. Avoid excessive brushing and reworking of painted areas. Keep standing water off of painted surface for a minimum of one week. **DRYING:** Normally dries to touch in one hour at 77°F (25°C) and 50% relative humidity. Allow four hours before recoating and 24 hours before normal use. Drying times listed may vary depending on temperature, humidity, color, film build, and air movement. Wait at least 30 days after painting before cleaning the surface with a non-abrasive, mild cleanser. **CLEANUP:** Clean tools with warm, soapy water. **DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer. **PROTECT FROM FREEZING.** U-1507-01

PRECAUTIONS AND FIRST AID: Do not breathe vapor or mist. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. **CONTAINS:** water (7732-18-5), proprietary acrylic resin (Not available), titanium dioxide (13463-67-7), Nepheline syenite (37244-96-5), Limestone (1317-65-3). Contains isothiazolinones. May cause allergic reaction. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION:** (412) 434-4515 (U.S.).