

# RedGard® Seam Tape

## 1 Product Name

RedGard® Seam Tape

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

RedGard® Seam Tape is a fast and easy way to cover seams and changes of plane when installing the RedGard® Uncoupling Mat to provide waterproofing and vapor barrier protection.

### Key Features

- Required for a waterproof installation of RedGard® Uncoupling Mat
- For seams and changes of plane
- Part of a waterproof/vapor barrier control system for floors

### Suitable Tile Types

Suitable for all tile types

### Suitable Substrates

Use on the seams of the RedGard® Uncoupling Mat only

### Sizes

- 4.7" x 4.7" x 16.25' (120 mm x 120 mm x 5 m) Roll
- 4.7" x 4.7" x 98.5' (120 mm x 120 mm x 30 m) Roll

### Benefits of Product in the Installation

- 100% waterproof protection for substrates
- Easy to cut and adjust
- Suitable for all tile types
- Use with polymer modified thin-set mortars

### Limitations to the Product

RedGard® Seam Tape is not intended for use without a suitable substrate that can support the finished floor installation.

## 4 Technical Data

### Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product may contribute to LEED® certification.



## 5 Instructions

### Application of Product

Install RedGard® Uncoupling Mat according to product instructions. To minimize installation duration, measure and cut the seam tape to size with a utility knife ahead of mixing thin-set for installation. Once the mat is installed, apply thin-set mortar into the top of the uncoupling mat where the seam tape will be applied. Using the flat side of a trowel or a taping knife, embed the RedGard® Seam Tape into the still wet thin-set. With firm pressure, work the trowel or taping knife at angles out and away from the center taking care to work out any air that may have been trapped when the seam tape was placed.

### Protection

If tile or stone will not be set immediately after curing, protect the application from heavy traffic damage. Protect from rain and inclement weather for 72 hours after application. If delays longer than 72 hours are expected, cover the area with felt paper. Care should be taken to prevent the application from becoming soiled or punctured during and after application.

### Cleaning of equipment

Clean tools and hands with water before material dries.

### Health Precautions

Wear impervious gloves and eye protection while using this product. Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, rinse cautiously with water for several minutes, remove contact lenses if easy to do: continue rinsing. Immediately seek medical advice if symptoms are significant or persist. Do not take internally. KEEP OUT OF REACH OF CHILDREN.

### Conformance to Building Codes

Installation must comply with the requirements of all applicable local, state and federal code jurisdictions.

## 6 Availability & Cost

Location	Item Code	Size	Package
USA	RGST5	5" x 16.5'	6 rolls per case
USA	RGST30-EA	5" x 98.5'	1 roll per case



# RedGard® Seam Tape

---

## 7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. CUSTOM's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with CUSTOM's printed instructions. CUSTOM makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. This warranty is not transferrable.

## 8 Product Maintenance

Properly installed product requires no special maintenance. Do not use as a wear surface.

## 9 Technical Services Information

For technical assistance, contact Custom technical services at 800-272-8786 or visit [custombuildingproducts.com](http://custombuildingproducts.com).

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### Related Products

RedGard® Uncoupling Mat

