



## BEHR PREMIUM Advanced DECKOVER® – Smooth

No. 5000 Deep Base

- Resurfaces Properly Prepared Weathered Wood and Concrete
- Covers up to 75 Sq. Ft. in 2 Coats
- Smooth Finish
- Conceals Splinters & Cracks up to 1/4"
- Resists Cracking & Peeling
- Durable, Mildew Resistant Finish
- Slip Resistant, Waterproof Coating
- 100% Acrylic



**Prep: Mandatory**  
Before Use



**Conceal: Pre-fill Cracks**  
Less than 1/4" With  
**DECKOVER**  
2 Coats Required



**Covers up to**  
75 Sq. Ft.  
in 2 Coats



**Clean-Up:**  
Soap & Water

### WHERE TO USE

Recommended for properly prepared interior and exterior weathered or cracked horizontal and vertical wood and composite surfaces such as Decks, Railings, Porches and Boat Docks. Can also be used on concrete surfaces such as Pool Decks, Patios and Sidewalks. Do not use on drivable surfaces such as garage floors and driveways. **DO NOT USE ON** wood surfaces that are in direct contact with the ground or exposed to excessive ground moisture.

### SURFACE PREPARATION (Proper Surface Preparation is Required)

All surfaces must be clean, sound, dry and free of any dirt, oil, and grease before application. **Wood Surfaces:** Replace rotting or unstable boards and remove loose splinters. Remove mildew stains, dirt, oil and grease with a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner prior to application. Use a product such as BEHR PREMIUM No. 64 Wood Stain & Finish Stripper (must be followed by No. 63) to remove all loose wood fibers, peeling paint/stain or deteriorated coatings prior to application of DECKOVER®. On new wood, use No. 63 to remove mill glaze and open the pores of the wood. Rinse thoroughly and allow to dry before coating.

**Concrete Surfaces:** Avoid areas that are structurally weak or subject to hydrostatic pressure above 8 psi. Allow new surfaces to cure for 30 days. Use a product such as BEHR PREMIUM No. 992 Concrete & Masonry Paint Stripper to strip peeling coating. Use a product such as BEHR PREMIUM No. 991 Concrete & Masonry Cleaner & Etcher to clean.

### APPLICATION

Use product when air and surface temperatures are between 50-90° F.

- Avoid applying in direct sunlight or to hot surfaces.
- Do not use if rain is expected within 24 hours.
- The surface must be completely dry before application.
- Avoid painting if humidity is expected to be greater than 80%.
- Intermix multiple containers to ensure color uniformity.
- Stir product occasionally throughout application. **DO NOT THIN PRODUCT.**

### LIMITED WARRANTY

For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. In the event this product proves to be defective within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. Note to residents of the State of New Jersey: The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. To obtain warranty service, call 1-800-854-0133. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2018 Behr Process Corporation  
Santa Ana, CA 92704 U.S.A. • behr.com  
V.O.C. <50 g/L • REV. 12/18

- For nail holes and cracks up to 1/4", completely fill in with Smooth DECKOVER® coating using a nylon/polyester brush and allow to dry prior to rolling.
- Deep nail holes and cracks may require additional filling.
- For edges, corners and in between wood boards, apply using a nylon/polyester brush.
- Use pressure while rolling and apply a generous, even coat using a 1/2" nap roller. For a smoother texture, use a brush or thinner nap roller (i.e. 1/4").
- For vertical surfaces such as railings, use a nylon/polyester brush or roller and apply two thin coats at a spread rate of 400 sq. ft. per gallon.
- Airless spray is recommended for experienced applicators only; use a .027" - .035" tip with no filter at 2400-3200 psi. When spraying vertical surfaces, apply a very thin coat (one pass only) and do not back brush/roll. When spraying horizontal surfaces, follow the standard spread rate of 75 sq. ft. per gallon.
- For optimum performance, film uniformity, leveling, to cover cracks and proper adhesion, a second coat **MUST** be applied. Maintain a wet edge when applying.
- For best results, coat all accessible board ends.

### DRY TIME

4-6 hours before recoat. Dries to touch in 4 hours. Wait 24-48 hours before light foot traffic. 72 hours to full cure. Additional dry time may be needed in cooler temperatures and higher humidity. Premature heavy traffic will cause coating failure.

### DISPOSAL

For disposal of empty containers and unused product contact your household refuse collection service.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping vapor treated lumber may be hazardous; wear appropriate protection.

### **WARNING** Cancer and Reproductive Harm [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ACRYLIC RESIN. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**