

## Section 1 - Product and Company Identification

Material Name Product Code Product Description	* <b>DYC361 EPOXY-TITE 1 PART EPOXY ACRYLIC – GULF GRAY</b> * DYC361, DYC 364 * Gray Liquid.
Product Use	* Concrete Coating and Sealer
Synonyms	* Protective Concrete Coating
Manufacturer	* Dyco Paints, Inc. 5850 Ulmerton Rd. Clearwater, FL 33760 United States www.suncoatings.com Please use "Contact Us" form on the website
Telephone	
Technical	* 813-248-2101
<u>Emergency</u>	* 800-424-9300
<u>Emergency</u>	* 703-527-3887
<b>Preparation Date</b>	* 10/30/2017
Last Revision Date	* 10/30/2017

## Section 2 - Hazards Identification

## **Emergency Overview**

Causes mild skin irritation. Harmful if swallowed.

- PreventionDo not handle until all safety precautions have been read and understood. Use personal<br/>protective equipment as required. Wash thoroughly after handling.
- **Response** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

**Storage/Disposal** Store in a closed container. Do not allow product to freeze. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.



Color	* Gray Liquid.
Odor	* Acrylic Paint-Like Odor.
Flash Point	* > 247 F(> 119.4444 C)
OSHA	* Irritant, Carcinogen
WHMIS	* Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B
GHS	* Skin Corrosion/Irritation - Category 3, Serious Eye Damage, Eye Irritation - Category 2A, Carcinogenicity - Category 1A
NFPA:	cts
Inhalation	
Acute (Immediate)	* Inhalation of vapors or mists may cause central nervous system depression, light- headedness, headache, nausea and loss of coordination.
Chronic (Delayed)	* Under normal conditions of use, no health effects are expected.
Skin	
Acute (Immediate)	* May cause irritation.
Chronic (Delayed)	* Repeated and prolonged exposure to the skin may cause dermatitis.
Eye	
Acute (Immediate)	* Likely to cause eye irritation, burning, tearing, etc. on contact with the eyes. If swelling and irritation persist, seek medical attention.
Chronic (Delayed)	* Direct contact may cause slight to moderate irritation.
Ingestion	
Acute (Immediate)	* May cause irritation. May affect the nervous system. May be harmful or fatal if swallowed.
Chronic (Delayed)	<ul> <li>Repeated and prolonged exposure may cause gastrointestinal disturbances including diarrhea, nausea, and vomiting.</li> </ul>

Carcinogenic Effects				
	CAS	IARC	NTP	
Titanium Dioxide	13463-67-7	Group 2B-Possible Carcinogen	Evidence of Carcinogenicity	

## Section 3 - Composition/Information on Ingredients

Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Acrylic Polymer Solution	CAS # - 25212-88-8	37%	Ingestion/Oral-Rat LD50 · 5000 mg/kg		
Nephylene Syenite	CAS # - 37244-96-5	8%			
Titanium Dioxide	CAS # - 13463-67-7	17%	Oral-rat TDLo:60 gm/kg		
Texanol Ester	<b>CAS #</b> - 25265-77-4	4%	Ingestion/Oral-Rat LD50 · 3200 mg/kg		

			Non-Haz	zardous Components	
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Water	7732-18-5	34%			

# This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Section 4 - First	Aid Measures			
Inhalation '	F IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If signs/symptoms continue, get medical attention.			
Skin '	* Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.			
Eye ,	* If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
Ingestion *	* If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.			
Section 5 - Fire F	Fighting Measures			
Extinguishing Media	<ul> <li>* LARGE FIRE: Water spray, fog or regular foam.</li> <li>SMALL FIRES: Dry chemical, CO2, water spray or regular foam.</li> </ul>			
Unsuitable Extinguishing Media	* No data available.			
Firefighting Procedu	<ul> <li>* Fire fighters should wear complete protective clothing including self-contained breathing apparatus.</li> <li>Keep unauthorized personnel away.</li> </ul>			
Unusual Fire and Explosion Hazards	<ul> <li>* Product containers may rupture when exposed to extreme heat. Precaustions should be taken to prevent release of materials.</li> </ul>			
Hazardous Combust Products	ion * Non-combustible, substance itself does not burn but may decompose upon heating to produce toxic fumes.			
Protection of Firefighters	<ul> <li>* Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.</li> </ul>			
Flash Point	* > 247 F(> 119.4444 C) CC (Closed Cup)			
Section 6 - Accid	Iental Release Measures			
Personal Precaution	<ul> <li>* Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.</li> </ul>			
Emergency Procedu	res * Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up.			

- Environmental \* Avoid run off to waterways and sewers. Precautions \* About or equations
- Precautions\* Absorb or cover with dry earth, sand or other non-combustible material and transfer to<br/>containers.Measures\* Absorb or cover with dry earth, sand or other non-combustible material and transfer to<br/>containers.Use appropriate Personal Protective Equipment (PPE)

Section 7 - Handling and Storage			
Handling	<ul> <li>* KEEP OUT OF THE REACH OF CHILDREN! Keep containers tightly closed when not in use.</li> </ul>		
Storage	<ul> <li>* Avoid extreme temperatures and freezing. Keep container/package tightly closed and in a well-ventilated place.</li> </ul>		
Special Packaging Materials	* Not Applicable.		
Incompatible Materials or Ignition Sources	* Avoid contact with strong oxidizing agents and acids.		

## Section 8 - Exposure Controls/Personal Protection

#### Personal Protective Equipment

Pictograms



**Respiratory** \* When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

## **Eye/Face** \* Wear ANSI approved safety glasses with side shields or safety goggles.

- Hands \* Wear chemical resistant gloves with repeated or prolonged exposure.
- Engineering<br/>Measures/Controls\* Adequate ventilation systems as needed to control concentrations of airborne<br/>contaminants below applicable threshold limit values. Use precaution to protect building<br/>intake from fumes and vapors created outdoors.

Exposure Limits/Guidelines						
	Result	Canada Ontario	Mexico	NIOSH	OSHA	
Nephylene Syenite (37244-96-5)	TWAs	0.10 mg/m3 TWAEV (designated substance regulation)	Not Established	Not Established	15 mg/m3 (total dust)	
Titanium Dioxide (13463-67-7)	TWAs	10 mg/m3 TWAEV (total dust)	10 mg/m3 TWA (as Ti)	Not established	15 mg/m3 TWA (total dust)	
Ammonia (7664-41-7)	TWAs	35 ppm	35 ppm	25 ppm	50 ppm	
Texanol Ester (25265-77-4)	TWAs	Not established	Not established	100 mg/m3 TWA (total dust); 5 mg/m3 TWA	100 mg/m3 TWA (total dust); 5 mg/m3 TWA	

## Section 9 - Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	White liquid with the consistency of paint.
Color	Gray Liquid.	Odor	Acrylic Paint-Like Odor.
Taste	No data available.	Particulate Type	Not relevant
Particulate Size	Not relevant	Aerosol Type	Not relevant
Odor Threshold	No data available		
General Properties			
Boiling Point	275 to 324 F	Melting Point	No data available

Decomposition Temperature	No data available	Heat of Decomposition	Not relevant
рН	8 @ 25 C(77 F)	Specific Gravity/Relative Density	1.22 Water=1
Density	10.22 lbs/gal @ 25 C(77 F)	Bulk Density	No data available
Water Solubility	Soluble 100 % @ 25 C(77 F)	Solvent Solubility	Not relevant
Viscosity	iscosity 80 - 90 Krebs-Stormer (KU) @ 25 C(77 F)		
Volatility			
Vapor Pressure	0.1 mmHg (torr) @ 20 C(68 F)	Vapor Density	> 1 Air=1
Evaporation Rate	< 1 Ether = 1	VOC (Wt.)	No data available
VOC (Vol.)	< 30 g/L	Volatiles (Wt.)	No data available
Volatiles (Vol.)	73.0%		
Flammability			
Flash Point	> 247 F(> 119.4444 C)	Flash Point Test Type	CC (Closed Cup)
UEL	No data available	LEL	No data available
Autoignition	No data available	Self-Accelerating Decomposition Temperature (SADT)	Not relevant
Heat of Combustion (ΔHc)	Not relevant	Burning Time	Not relevant
Flame Duration	Not relevant	Flame Height	Not relevant
Flame Extension	Not relevant	Ignition Distance	Not relevant
<b>–</b> · · · ·	•	•	
Environmental			
Environmental Half-Life	Not relevant	Octanol/Water Partition coefficient	Not relevant
	Not relevant Not relevant	Octanol/Water Partition coefficient Bioaccumulation Factor	Not relevant Not relevant
Half-Life			
Half-Life Coefficient of Water	Not relevant	Bioaccumulation Factor Biochemical Oxygen Demand	Not relevant

## Section 10 - Stability and Reactivity

Stability	* Stable under normal temperatures and pressures.
Hazardous Polymerization	* Hazardous polymerization not indicated.
Conditions to Avoid	* Excessive heat and freezing.
Incompatible Materials	* Strong oxidizers and acids.
Hazardous Decomposition Products	* No known issues under normal usage conditions.

## Section 11 - Toxicological Information

Component Name	CAS	Data	
Titanium Dioxide		Acute Toxicity: orl-rat TDLo:60 gm/kg; Irritation: skn-hmn 300 ug/3D-I MLD	
Acrylic Polymer Solution	25212-88-8	Acute Toxicity: Ingestion/Oral-Rat LD50	
Texanol Ester	25265-77-4	Acute Toxicity: orl-rat LD50:3200 mg/kg; ihl-rat LC :>3500 mg/m3/6H	

Other Component Information \* IARC has concluded that the following chemicals in this product are carcinogenic to humans(Group 1): silica, quartz. ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

## Section 12 - Ecological Information

Ecological Fate	* No data available.
Persistence/Degradability	* No data available.
<b>Bioaccumulation Potential</b>	* No data available.
Mobility in Soil	* No data available.
Other Information	* Do not allow product exposure to the ground or into any waterway. Do not allow entry into muncipal sewer systems.

#### Section 13 - Disposal Considerations

Product

\* Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transportation Information

DOT - United States - Department of Transportation - Shipping Name: Not Regulated.

TDG - Canada - Transportation of Dangerous Goods - Shipping Name: Not Regulated.

IMO/IMDG - International Maritime Transport Shipping Name: Not Regulated.

IATA - International Air Transportation Association - Not Regulated.

## Section 15 - Regulatory Information

#### SARA Hazard Classifications \* Acute, Chronic

State Right To Know							
Component	CAS	MA	MN	NJ	PA		
Water	7732-18-5	No	No	No	No		
Acrylic Polymer Solution	25265-77-4	No	No	No	No		
Nephylene Syenite	37244-96-5	No	No	No	No		
Titanium Dioxide	13463-67-7	Yes	Yes	Yes	Yes		
Texanol Ester	25265-77-4	No	No	No	No		

Inventory							
Component	CAS	EU EINECS	TSCA				
Water	7732-18-5	Yes	Yes				
Acrylic Polymer Solution	25265-77-4	No	No				
Nephylene Syenite	37244-96-5	Yes	Yes				
Titanium Dioxide	13463-67-7	Yes	Yes				
Texanol Ester	25265-77-4	Yes	Yes				

#### Canada

Labor

#### Canada - WHMIS - Classifications of Substances

D2A (In certain cases, this classification does not apply. For more information, consult the section

•Titanium Dioxide

13463-67-7 5% TO 15% Substance Specific Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS website.)

#### **United States**

#### Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

#### **United States - California**

#### Environment

U.S. - California - Proposition 65 - Carcinogens List • Ester Alcohol 25265-77-4

#### **United States - Rhode Island**

#### Labor

U.S. - Rhode Island - Hazardous Substance List

•Titanium Dioxide 13463-67-7 17% Toxic

•Ester Alcohol 125265-77- 1% Combustible

**Other Information** 

\* WARNING: This product contains a chemical known to the State of California to cause cancer.

### Section 16 - Other Information

Preparation Date \* 10/30/2017

Last Revision Date \* 10/30/2017

#### **Disclaimer/Statement of Liability**

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the users responsibility to verify the suitability and completeness of such information for particular use. Dyco Paints Inc. does not accept liability for any loss or damage that may occur from the use of this information.