






SCORING WHEEL CHARACTERISTICS

●●● Ideal Use ●● Second best Use ● Alternative Use

 The norm UNE-EN 14411 applies to ceramic & tile classification and fit is of international application. It is indicated on all tile boxes.

	 6 mm 1/4 inch	 8 mm 5/16 inch	 10 mm 13/32 inch	 18 mm 3/4 inch	 22 mm 7/8 inch
--	--	---	---	---	---

 RUSTIC TILES AI, AIIa, AIIb, AIII	●●●	●●●	●●●	●●●	●●●
 PORCELAIN BIa	●	●●●	●●●	●●●	●●●
 FLOOR TILES BIIb, BIIIa	●●●	●●●	●●●	●●●	●●●
 WALL TILES BIII	●●●	●●●	●●●	●●●	●●●
 GLASS TILES GL	●●●	●●●	●●●	●●●	●●●

	 6 mm 1/4 inch	 8 mm 5/16 inch	 10 mm 13/32 inch	 18 mm 3/4 inch	 22 mm 7/8 inch
--	--	---	---	--	---

TS-MAX TR-MAGNET SPEED MAGNET TF-MAX	TS / TS-PLUS TR / TR-S SPEED PLUS TF-MEISTER	SILVER	01945	01902	01946	01950	
	GOLD				01949		01964
	INDURE			01906			
	X-TRIAS						01907
SPEED-N SPEED-FAST STAR-MAX / STAR	SPEED-POCKET RAPID PRACTIC	SILVER	01945	01902	01946		
	GOLD				01949		
	INDURE			01906			
	X-TRIAS						
TZ TX-N / TX-MAX	SILVER			01959	01904	01905	
	GOLD				01993		01965
	INDURE			01903			
	X-TRIAS						01900
TQ TP / TP-S	SILVER						18914
	X-TRIAS						01901
TI / TI-T	SILVER				01975	01976	01977
	GOLD				01978	01974	01979
SLIM SYSTEM CUTTER	SILVER						18914
	X-TRIAS						01901
BASIC KIT TEN-BRIC	SILVER						01960

Ø 14 mm
Ø 9/16 inch



01945 SILVER 01902 SILVER 01906 INDURE 01946 SILVER 01950 SILVER ~~01907 X-TRIAS~~ 01903 INDURE 01904 SILVER 01905 SILVER ~~01900 X-TRIAS~~ 18914 SILVER ~~01901 X-TRIAS~~



01995 Ø1/4" (6mm)
Ø3/8" (10mm)



01969 Ø1/4" (6mm)
Ø5/16" (8mm)
Ø3/8" (10mm)
Ø3/4" (18mm)
Ø7/8" (22mm)