

WOOD PRODUCTS

 **McFarland Cascade.com** the best outdoor projects start with the best materials

Outdoor® Select


Size	Specie	Pcs/Unit	6'	8'	10'	12'	14'	16'	18'	20'
5/4 x 4	hem-fir/SYP	108		✓	✓	✓	✓	✓		
5/4 x 6	SYP/hem-fir	72		✓	✓	✓	✓	✓		
2 x 4	hem-fir	156		✓	✓	✓	✓	✓	✓	✓
2 x 6	hem-fir	96		✓	✓	✓	✓	✓	✓	✓
2 x 8	hem-fir	36		✓	✓	✓	✓	✓	✓	✓
2 x 10	hem-fir	20		✓	✓	✓	✓	✓	✓	✓
2 x 12	hem-fir	16		✓	✓	✓	✓	✓	✓	✓

LUMBER DESCRIPTION


- Initial minimum grade of #1 kiln dried lumber is purchased and then sorted at our plant to eliminate unsuitable characteristics. Specifically:



Centerline Knots – each knot limited to a maximum of 40% of the face, but generally much smaller



Edge Knots – limited in size to 28% of the face width or less



- Holes limited as black knots well spaced and no larger than a dime
- No wane on good face
- Splits limited to maximum of width of face

SAFETY AND HANDLING

- See EPA-approved Consumer Information Sheet prior to use
- The minimal corrosivity of EXTRAGREEN™ wood is similar to that of traditional wood. Hot-dipped galvanized fasteners (meeting ASTM A 153) and connectors (ASTM A 653 Class G185 sheet), or better, are recommended for protection against the effects of moisture often present where treated wood is used. For Permanent Wood Foundations, use 304 or 316 stainless steel. Aluminum should not be used in direct contact with this wood.

TREATMENT

- Unincised
- Treated .06 p.c.f. CA for above-ground use
- Soft cedartone color

intended Use

- Customarily used for decking surfaces or any above-ground application requiring high quality appearance such as fencing cross-members, deck railing, trellis work, exposed gazebo rafters, etc.

Feature	Benefit
• All lumber sorted at our plant to eliminate unsuitable pieces	Every piece is usable for intended use thus eliminating waste
• All lumber kiln dried prior to treatment	Assures greatest CA penetration and retention, along with maximum long term dimensional stability
• Soft cedar color	No need to stain new project. Can be easily restained if color change desired
• CA copper azole	CA protects against rot and attack by termites. ASTM A 153 (fasteners) and ASTM AA 653 Class G (connectors) recommended
• Lifetime limited warranty	Guarantees replacement of wood to original purchaser in the event of termite attack or decay
• Bar coded with warranty label on every piece	Immediate description of product in terms of size, grade of lumber, intended application, and identity code

McFarland Cascade
P.O. Box 1496, Tacoma, WA 98401
(253) 572-3033 • (800)426-8430 • FAX: (253)272-1398