

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

## 1 Identification

- **Product identifier**
- **Trade name:** MONTANA GOLD Spray Paint all colors, fluo and shock
- **Article number:**  
283604 - 285844, 285899, 285905, 285929, 364945, 492747, 492754, 492761, 492778, 492785, 492792, 492808, 419331, 419348, 419355, 419362, 419379, 419386, 419393, 419409, 419416, 419423, 419430, 419447, 419454, 419461, 419478, 430060, 439537
- **Application of the substance / the mixture** *Lacquer*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MONTANA CANS  
Häusserstr. 36  
D-69115 Heidelberg  
Tel. +49-6221-36333-30  
Fax +49-6221-36333-33  
info@montana-cans.de  
www.montana-cans.com
- **Information department:** *Abteilung Produktsicherheit*
- **Emergency telephone number:**  
Tel.: +49 6266-75-310  
Fax +49 6266-75-362  
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 1)

· **Hazard pictograms**



GHS02   GHS04   GHS07   GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*ethyl acetate  
titanium dioxide  
acetone  
Solvent naphtha (petroleum), light arom.*

· **Hazard statements**

*H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H336 May cause drowsiness or dizziness.*

· **Precautionary statements**

*P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P280 Wear protective gloves / eye protection.  
P285 In case of inadequate ventilation wear respiratory protection.  
P302+P352 If on skin: Wash with plenty of water.  
P312 Call a poison center/doctor if you feel unwell.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 4  
Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**



Health = 2  
Fire = 4  
Reactivity = 3

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.  
· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6	dimethyl ether	12.5-<20%
EINECS: 204-065-8	Flam. Gas 1, H220	
Index number: 603-019-00-8	Press. Gas, H280	

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

Trade name: **MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 2)

CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	12.5-<20%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane ⚠ Flam. Gas 1, H220 ⚠ Press. Gas, H280	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane (containing ≥0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1, H220 ⚠ Press. Gas, H280	5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ STOT SE 3, H335-H336	2.5-<5%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide ⚠ Carc. 2, H351	2.5-<5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-<5%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-<5%
CAS: 9004-70-0	cellulose nitrate ⚠ Flam. Sol. 1, H228	2.5-<5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0	isobutane ⚠ Flam. Gas 1, H220 ⚠ Press. Gas, H280	<2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	≤0.5%

· **Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex IA 1272/2008 EU), so the classification as carcinogen need not to apply.

## 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

USA

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 3)

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

115-10-6	dimethyl ether	3,000 ppm
141-78-6	ethyl acetate	1,200 ppm
67-64-1	acetone	200 ppm
74-98-6	propane	5500* ppm
106-97-8	butane (containing $\geq 0,1$ % butadiene (203-450-8))	5500* ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7	xylene, mixture of isomers	130 ppm
75-28-5	isobutane	5500* ppm
103-23-1	Di-(2-ethylhexyl) adipate	17 mg/m <sup>3</sup>
67-63-0	propan-2-ol	400 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>
9002-88-4	Polyethylene low density	16 mg/m <sup>3</sup>
100-41-4	ethylbenzene	33 ppm
123-86-4	n-butyl acetate	5 ppm
85-44-9	phthalic anhydride	18 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	50 ppm
100-42-5	styrene	20 ppm
111-66-0	oct-1-ene	40 ppm

### · PAC-2:

115-10-6	dimethyl ether	3800* ppm
141-78-6	ethyl acetate	1,700 ppm
67-64-1	acetone	3200* ppm

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

		(Contd. of page 4)
74-98-6	propane	17000** ppm
106-97-8	butane (containing $\geq 0,1$ % butadiene (203-450-8))	17000** ppm
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	xylene, mixture of isomers	920* ppm
75-28-5	isobutane	17000** ppm
103-23-1	Di-(2-ethylhexyl) adipate	180 mg/m <sup>3</sup>
67-63-0	propan-2-ol	2000* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
9002-88-4	Polyethylene low density	170 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1100* ppm
123-86-4	n-butyl acetate	200 ppm
85-44-9	phthalic anhydride	56 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	1,000 ppm
100-42-5	styrene	130 ppm
111-66-0	oct-1-ene	800* ppm

**· PAC-3:**

115-10-6	dimethyl ether	7200* ppm
141-78-6	ethyl acetate	10000** ppm
67-64-1	acetone	5700* ppm
74-98-6	propane	33000*** ppm
106-97-8	butane (containing $\geq 0,1$ % butadiene (203-450-8))	53000*** ppm
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene, mixture of isomers	2500* ppm
75-28-5	isobutane	53000*** ppm
103-23-1	Di-(2-ethylhexyl) adipate	1,100 mg/m <sup>3</sup>
67-63-0	propan-2-ol	12000** ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>
9002-88-4	Polyethylene low density	1,000 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1800* ppm
123-86-4	n-butyl acetate	3000* ppm
85-44-9	phthalic anhydride	10,000 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	5,000 ppm
100-42-5	styrene	1100* ppm
111-66-0	oct-1-ene	2000* ppm

## 7 Handling and storage

**· Handling:**

**· Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

**· Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.

(Contd. on page 6)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 5)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 2 B
- **Specific end use(s)** No further relevant information available.

## \* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.  
At this time, the other constituents have no known exposure limits.

### 115-10-6 dimethyl ether

WEEL Long-term value: 1000 ppm

### 141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm

REL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm

TLV Long-term value: 1440 mg/m<sup>3</sup>, 400 ppm

### 67-64-1 acetone

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm

Long-term value: 594 mg/m<sup>3</sup>, 250 ppm

BEI

### 74-98-6 propane

PEL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV refer to Appendix F in TLVs&BEIs book; D, EX

### 106-97-8 butane (containing ≥0,1 % butadiene (203-450-8))

REL Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

TLV Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm  
(EX)

### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

### 1330-20-7 xylene, mixture of isomers

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm

Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm

Long-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 6)

**75-28-5 isobutane**

TLV Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm  
(EX)

**67-63-0 propan-2-ol**

PEL Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
REL Short-term value: 1225 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
TLV Short-term value: 984 mg/m<sup>3</sup>, 400 ppm  
Long-term value: 492 mg/m<sup>3</sup>, 200 ppm  
BEI

**100-41-4 ethylbenzene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
REL Short-term value: 545 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm  
BEI

**· Ingredients with biological limit values:****67-64-1 acetone**

BEI 50 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Acetone (nonspecific)

**1330-20-7 xylene, mixture of isomers**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

**67-63-0 propan-2-ol**

BEI 40 mg/L  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: Acetone (background, nonspecific)

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
Medium: end-exhaled air  
Time: not critical  
Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.  
Avoid contact with the eyes.

(Contd. on page 8)

USA



**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 7)

· **Breathing equipment:**

Filter AX

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g.

KCL Camatril, article no. 898 or similar products

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Aerosol

**Color:** According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 8)

· <b>Ignition temperature:</b>	240 °C (464 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Not determined.
· <b>Explosion limits:</b>	
<b>Lower:</b>	2.1 Vol %
<b>Upper:</b>	26.2 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	8 hPa (6 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.96 g/cm <sup>3</sup> (8.01 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	75.3 %
<b>Water:</b>	0.2 %
<b>VOC content:</b>	719.2 g/l / 6.00 lb/gal
<b>Solids content:</b>	36.2 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

### · LD/LC50 values that are relevant for classification:

#### 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	>15,800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	3,160 mg/kg (rabbit)

(Contd. on page 10)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 9)

### 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,530 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10,000 mg/m3 (rat)

### 1330-20-7 xylene, mixture of isomers

Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29,000 mg/m3 (rat)

### 67-63-0 propan-2-ol

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50	>25 mg/l (rat) LC 50: 6h

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
Vapors have narcotic effect.  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	xylene, mixture of isomers	3
103-23-1	Di-(2-ethylhexyl) adipate	3
67-63-0	propan-2-ol	3
7631-86-9	silicon dioxide, chemically prepared	3
9002-88-4	Polyethylene low density	3
100-41-4	ethylbenzene	2B
14808-60-7	Quartz (SiO <sub>2</sub> )	1
100-42-5	styrene	2B

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
100-42-5	styrene	R

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

### 115-10-6 dimethyl ether

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4,000 mg/l (daphnia magna)
LC50 / 96 h	>4,000 mg/l (fish)

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 10)

**67-64-1 acetone**

LC50/96h	8,300 mg/l (fish)
EC50/96h	7,200 mg/l (algae)
LC50 / 48 h	8,450 mg/l (crustacean (water flea))

**64742-95-6 Solvent naphtha (petroleum), light arom.**

EC50 / 48 h	3.2 mg/l (Daphnia magna)
EC50 / 72 h	2.75 mg/l (Pseudokirchneriella Subcapitata)
EC50 / 96 h	9.2 mg/l (Regenbogenforelle)

**108-65-6 2-methoxy-1-methylethyl acetate**

EC50 / 48 h	>500 mg/l (daphnia magna)
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)

**1330-20-7 xylene, mixture of isomers**

EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

**67-63-0 propan-2-ol**

LC50/96h	9,640 mg/l (pimephales promelas; 96h)
LC50 / 24 h	9,714 mg/l (daphnia magna)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Non contaminated packagings can be used for recycling.

## 14 Transport information

- |                                  |                     |
|----------------------------------|---------------------|
| · <b>UN-Number</b>               |                     |
| · <b>DOT, IMDG, IATA</b>         | UN1950              |
| · <b>UN proper shipping name</b> |                     |
| · <b>DOT</b>                     | Aerosols, flammable |
| · <b>IMDG</b>                    | AEROSOLS            |
| · <b>IATA</b>                    | AEROSOLS, flammable |

(Contd. on page 12)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 11)

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1  
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1  
 · **Label** 2.1

· **Packing group**

· **DOT, IMDG, IATA** not regulated

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Gases

· **Danger code (Kemler):** -

· **EMS Number:** F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:

Category A. For AEROSOLS with a capacity above 1 litre:

Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except

for division 1.4. For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2. For

WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

USA

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 12)

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene, mixture of isomers

103-23-1 Di-(2-ethylhexyl) adipate

67-63-0 propan-2-ol

100-41-4 ethylbenzene

85-44-9 phthalic anhydride

100-42-5 styrene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

100-41-4 ethylbenzene

14808-60-7 Quartz (SiO<sub>2</sub>)

100-42-5 styrene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1 acetone

I

1330-20-7 xylene, mixture of isomers

I

103-23-1 Di-(2-ethylhexyl) adipate

C

100-41-4 ethylbenzene

D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1 acetone

A4

13463-67-7 titanium dioxide

A4

1330-20-7 xylene, mixture of isomers

A4

67-63-0 propan-2-ol

A4

100-41-4 ethylbenzene

A3

85-44-9 phthalic anhydride

A4

14808-60-7 Quartz (SiO<sub>2</sub>)

A2

100-42-5 styrene

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

14808-60-7 Quartz (SiO<sub>2</sub>)

(Contd. on page 14)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/21/2018

Reviewed on 06/21/2018

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 13)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Date of preparation / last revision** 06/21/2018 / 4

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- BEI: Biological Exposure Limit
- Flam. Gas 1: Flammable gases – Category 1
- Flam. Aerosol 1: Aerosols – Category 1
- Press. Gas: Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Flam. Sol. 1: Flammable solids – Category 1
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
- Carc. 2: Carcinogenicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**