

LED BACKLIT PANEL CCT AND WATTAGE-SELECT

PRODUCT DESCRIPTION

The LED Backlit Panel provides soft, even illumination for recessed t-grid ceiling applications. The latest in panel design, backlit panels provide more diffused illumination on the lens and are more efficient in lighting a space. CCT-select and wattage-select ensure the right product is available for any application.

FEATURES

Available in 2x2 and 2x4 sizes 3500K, 4000K, and 5000K CCT-select 3 wattage/lumen selections: 2x2: 20W (2100lm)/30W (3150lm)/40W (4200lm) 2x4: 30W (3150lm)/40W (4200lm)/50W (5250lm) 0-10V dimmable 120-277V driver

FIGURE A



LISTINGS

UL-listed to US and Canadian safety standards DLC Listed FCC RoHS Damp location listed

FIGURE B



WARRANTY

5 Years

SPECIFICATIONS


KPN	Family Name	Size (FT)	Voltage (V)	Wattage (W)	Lumens (Lm)	CCT (K)	CRI (Ra)	Lifetime (Hrs)	Pallet QTY	US Stock
K0000019488	LED Backlit Panel	2x2	120-277	20/30/40	2100/3150/4200	35/40/50	80	50000	96	Yes
K0000019489	LED Backlit Panel	2x4	120-277	30/40/50	3150/4200/5250	35/40/50	80	50000	48	Yes




LED BACKLIT PANEL CCT AND WATTAGE-SELECT

DIMENSIONS

2x2 FT




2x4 FT



OPTICS

2x2 FT



2x4 FT

