

**OLYMPIC WATERGUARD® Tinted Waterproofing Sealant for Wood****GENERAL DESCRIPTION**

OLYMPIC WATERGUARD Tinted Waterproofing Sealant for Wood has been specially developed to provide four-way protection with a slight hint of color to maintain or restore the natural beauty of wood.

RECOMMENDED USES

Recommended for use on exterior bare wood, pressure-treated wood, or wood with a weathered solvent-based clear or semi-transparent stain.

Decks	Railings
Fences	Siding
Outdoor furniture	

FEATURES / BENEFITS

- Repels Water
- Provides Sun Block® U.V. Protection
- Provides a Mildew Resistant Coating
- Protects with Linseed Oil
- Easy Water Cleanup

APPLICATION INFORMATION

FOR EXTERIOR USE ONLY. Stir thoroughly and often during use. When using more than one container of the same color, intermix to ensure color uniformity.

Pretest: Apply to a small area and allow to dry to ensure acceptable appearance and penetration.

Application Equipment: Apply with a high quality polyester brush, paint/stain pad, or by spray equipment.

Application Method: Apply one thin coat. When spraying, always back-brush for best results. To help avoid lap marks, apply to only a few boards at a time and maintain a wet edge.

Thinning: DO NOT THIN.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	35 to 90°F	2 to 32°C
Substrate:	35 to 90°F	2 to 32°C

PRODUCT INFORMATION

55162, 55162C Honey Gold

DO NOT TINT.

PRODUCT DATA

PRODUCT TYPE:	Modified Linseed Oil Resin
VOLUME SOLIDS:	8% +/- 2%
WEIGHT SOLIDS:	9.8% +/- 2%
VOC:	<100 g/L (0.8 lbs./gal.)

WEIGHT/GALLON: 8.4 lbs. (3.8 kg) +/- 0.2 lbs. (91 g)

COVERAGE: Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 L) depending on application, wood texture and porosity.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries in 24 hours when applied in temperatures of 50°F (10°C) to 85°F (29°C). High humidity or low temperature application may prolong drying time.

Drying times listed may vary depending on temperature, humidity and air movement.

CLEANUP: Clean brushes and tools with warm, soapy water.

DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. Refer to www.pittsburghpaints.com, Spontaneous Combustion Advisory for additional information.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

OLYMPIC WATERGUARD Tinted Waterproofing Sealant for Wood

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *OLYMPIC* limited warranty to apply. All surfaces must be clean and free of dirt, dust, oil, mildew, and loose material. Previous coatings must be completely removed. Prior to sealant application, clean weathered, dirty or mildewed surfaces with *OLYMPIC* Deck Cleaner. After rinsing, ensure surface is free of standing water. Remove grade stamps or pencil marks by sanding.

PRETEST: Apply on a small area before treating the entire surface. If the product is not absorbed into the surface and is still tacky after 12 hours, the surface is not suitable for a waterproofing sealant. Tacky areas may be wiped clean with mineral spirits or MEK (Methyl Ethyl Ketone).

EXTRACTIVE BLEEDING: Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to “bleed” or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

MILDEW: Remove mildew stains by using *OLYMPIC* Deck Cleaner.

LIMITATIONS OF USE

Apply product only when air, product and surface temperatures are between 35°F (2°C) and 90°F (32°C) and will remain above 35°F (2°C) for the next 24 hours. Avoid sealing in direct sunlight or on hot surfaces. Do not apply if rain is expected within 24 hours of application.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

FOR EXTERIOR USE ONLY. Not recommended for recently painted or sealed surfaces. Do not use on plastic, rubber, asphalt, tile, vinyl, concrete, or any non-porous surface.

PROTECT FROM FREEZING.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

Do not reuse empty container.

PACKAGING

55162 1-Gallon (3.78L), 5-Gallon (18.9L)
55162C 1-Gallon (3.78L)

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *OLYMPIC*, *OLYMPIC* design, *SunBlock* and *WATERGUARD* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.olympic.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
4 Kenview Boulevard
Brampton, ON L6T 5E4

T.D. 55162, 55162C
9/2013
(Supersedes 12/2012)