



# Herculiner Truck Bed Liner Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/21/2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Herculiner Truck Bed Liner Black

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Roll-on Truck Bed Liner

#### 1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC  
4065 Commercial Ave.  
Northbrook, IL 60062 - USA  
T (847) 559-2000  
[www.oldworldind.com](http://www.oldworldind.com)

#### 1.4. Emergency telephone number

Emergency number : (800) 424-9300; (703) 527 3887 (International)  
Chemtrec

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 3 H226  
Acute Tox. 4 (Inhalation:dust,mist) H332  
Skin Irrit. 2 H315  
Resp. Sens. 1 H334  
Skin Sens. 1 H317  
Carc. 2 H351  
STOT RE 2 H373

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H332 - Harmful if inhaled  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H351 - Suspected of causing cancer  
H373 - May cause damage to organs (Respiratory tract) through prolonged or repeated exposure (Inhalation, oral)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P260 - Do not breathe mist, spray, vapors  
P264 - Wash affected areas thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear personal protective equipment as required  
P302+P352 - If on skin: Wash with plenty of water  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P314 - Get medical advice/attention if you feel unwell  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

# Herculiner Truck Bed Liner Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P342+P311 - If experiencing respiratory symptoms: Call a doctor/physician or poison center  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use foam, dry extinguishing powder, carbon dioxide (CO<sub>2</sub>) to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	% by wt	GHS-US classification
xylene, mixture of isomers	(CAS No) 1330-20-7	<= 29.4	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
4,4'-methylenediphenyl diisocyanate	(CAS No) 101-68-8	< 5.3	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Symptoms of poisoning may not appear for several hours. supervision of a doctor is necessary during at least 48h after an accident happened.
- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Get immediate medical advice/attention. If not breathing, give artificial respiration.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. If eye irritation persists: Get immediate medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Obtain emergency medical attention. A person vomiting while laying on their back should be turned onto their side.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged exposure to small concentrations may result in pulmonary edema. Vapor inhalation and/or skin absorption can cause central nervous system effects, including dizziness, light-headedness, headache, nausea and loss of coordination.
- Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : Nausea. Gastrointestinal complaints. Dizziness.

### 4.3. Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs. Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible. In cases of irritation to the lungs, initial treatment with cortical steroid inhalants. If necessary oxygen respiration treatment. Treat skin and mucous membrane with antihistamine and corticoid preparations. Contains diphenylmethanediisocyanate, isomers and homologues. May produce an allergic reaction.

# Herculiner Truck Bed Liner Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.  
Explosion hazard : May form flammable/explosive vapor-air mixture.  
Reactivity : Cures with exposure to water vapor.

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear suitable respiratory equipment in case of insufficient ventilation.  
Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Refer to section 8.2.  
Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Leave the product to solidify. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Ensure adequate ventilation, especially in confined areas. Do not flush with water.  
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.  
Hygiene measures : Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Do not store near food, foodstuffs, drugs or potable water supplies. Store in a well-ventilated place. Keep container tightly closed. Do not allow water (or moist air) contact with this material.  
Incompatible products : Keep away from strong acids, strong bases and oxidizing agents.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

#### 7.3. Specific end use(s)

No additional information available

# Herculiner Truck Bed Liner Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

xylene, mixture of isomers (1330-20-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	434 mg/m <sup>3</sup>
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	651 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	Upper Respiratory Tract & eye irritant; Central Nervous System impairment
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (STEL) (mg/m <sup>3</sup> )	655 mg/m <sup>3</sup>
OSHA	OSHA PEL (STEL) (ppm)	150 ppm

4,4'-methylenediphenyl diisocyanate (101-68-8)		
ACGIH	ACGIH TWA (ppm)	0.01 ppm
ACGIH	Remark (ACGIH)	Resp sens
OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
OSHA	OSHA PEL (Ceiling) (ppm)	0.02 ppm

#### 8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Safety glasses. High gas/vapor concentration: gas mask.



Hand protection : Wear protective gloves.  
Eye protection : Chemical goggles or safety glasses.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : In case of inadequate ventilation wear respiratory protection. Combined gas/dust mask with filter type A/P2.  
Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Pigment.  
Color : Black  
Odor : Petroleum-like odour  
Odor threshold : No data available  
pH : 8  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point : < -46 °C (< -50 °F)  
Freezing point : No data available  
Boiling point : 140 °C (284 °F)  
Flash point : 27 °C (81 °F) [Method Used: ASTM D56]  
Auto-ignition temperature : > 200 °C (> 392 °F)  
Decomposition temperature : 200 °C (392 °F)  
Flammability (solid, gas) : Flammable  
Vapor pressure : 14.2 hPa @ 20 °C (68 °F)  
Relative vapor density at 20 °C : No data available  
Specific Gravity : 1.03

# Herculiner Truck Bed Liner Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Density	: 1.03 g/cm <sup>3</sup>
Percent Solids	: > 70 % by mass (65% by volume)
Solubility	: Water: Not miscible, reacts with water
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: Not determined
Viscosity, dynamic	: 790 - 2250 cP (80 - 110 Krebs Units)
Explosive properties	: Container can be pressurised by carbon dioxide due to reaction with humid air and/or water. Pressurised container: May burst if heated. In use, may form flammable / explosive vapor air mixture.
Oxidizing properties	: No data available
Explosive limits	: 2.1 - 11.5 vol %

### 9.2. Other information

VOC content : <= 29.00 % <= 250 g/L

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Cures with exposure to water vapor.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents. water.

### 10.6. Hazardous decomposition products

May release flammable gases. Carbon monoxide. Carbon dioxide. Fume. Hydrogen cyanide. (prussic acid). Isocyanates. Nitrogen oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

<b>Herculiner Truck Bed Liner Black</b>	
ATE US (dust,mist)	4.32 mg/l/4h
<b>xylene, mixture of isomers (1330-20-7)</b>	
LD50 oral rat	3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4,200.00 mg/kg bodyweight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	29.00 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
ATE US (oral)	3,523.00 mg/kg bodyweight
ATE US (dermal)	1,100.00 mg/kg bodyweight
ATE US (gases)	4,500.00 ppmv/4h
ATE US (vapors)	11.00 mg/l/4h
ATE US (dust,mist)	1.50 mg/l/4h
<b>4,4'-methylenediphenyl diisocyanate (101-68-8)</b>	
LD50 oral rat	> 7,616.00 mg/kg (Rat; Equivalent or similar to OECD 401; Read-across)
LD50 dermal rabbit	> 9,400.00 mg/kg bodyweight (Rabbit; Read-across; Equivalent or similar to OECD 402)
ATE US (gases)	4,500.00 ppmv/4h
ATE US (vapors)	11.00 mg/l/4h
ATE US (dust,mist)	1.50 mg/l/4h

# Herculiner Truck Bed Liner Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Causes skin irritation. pH: 8.00
Serious eye damage/irritation	: Not classified pH: 8.00
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

### **xylene, mixture of isomers (1330-20-7)**

IARC group	3 - Not classifiable
------------	----------------------

### **4,4'-methylenediphenyl diisocyanate (101-68-8)**

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: May cause damage to organs (Respiratory tract) through prolonged or repeated exposure (Inhalation, oral). May cause damage to organs through prolonged or repeated exposure
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged exposure to small concentrations may result in pulmonary edema. Vapor inhalation and/or skin absorption can cause central nervous system effects, including dizziness, light-headedness, headache, nausea and loss of coordination.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Nausea. Gastrointestinal complaints. Dizziness.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### **4,4'-methylenediphenyl diisocyanate (101-68-8)**

EC50 Daphnia 1	129.70 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 24 h; Daphnia magna; Static system; Fresh water; Read-across)
LC50 fish 2	> 1,000.00 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Danio rerio; Static system; Fresh water; Read-across)
Threshold limit algae 1	> 1640 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Read-across)

### 12.2. Persistence and degradability

#### **xylene, mixture of isomers (1330-20-7)**

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air.
-------------------------------	---

#### **4,4'-methylenediphenyl diisocyanate (101-68-8)**

Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available.
-------------------------------	---

### 12.3. Bioaccumulative potential

#### **xylene, mixture of isomers (1330-20-7)**

BCF fish 1	15.00 8 weeks; Salmo gairdneri (Oncorhynchus mykiss)
BCF fish 2	7 - 26 (8 weeks; Oncorhynchus mykiss)
Log Pow	3.20 (Conclusion by analogy; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# Herculiner Truck Bed Liner Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>4,4'-methylenediphenyl diisocyanate (101-68-8)</b>	
BCF fish 2	92 - 200 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 4 weeks; Cyprinus carpio; Flow-through system; Fresh water; Experimental value; GLP)
Log Pow	5.22 (Estimated value; 4.51; Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 22 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

<b>xylene, mixture of isomers (1330-20-7)</b>	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

### 12.5. Other adverse effects

Effect on ozone layer	: No additional information available
Effect on global warming	: No known ecological damage caused by this product. No additional information available
Other information	: Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Other information	: DOT Consumer Commodity Exemption (Part 172,150) Outer Packaging: "Consumer Commodity - ORM-D" and ISO orientation arrows. Pallets: If "Consumer Commodity" on outer packaging is visible labeling not required. Otherwise label as "Consumer Commodity." Container/Trailer: None required.
-------------------	---

### TDG

Refer to current TDG Canada for further Canadian regulations

### Transport by sea

Limited quantities (IMDG)	: IMDG Exemption for Limited Quantities (IMDG 18.3, 3.26) Outer Packaging: (No requirements) Pallets: Dangerous Goods in Limited Quantities (Class 3 Flammable) Container: "Limited Quantities"
---------------------------	--

### Air transport

Instruction "passenger" - Limited quantities (ICAO)	: IATA Limited Quantities Exemption (Part 2.8) For Shipping of product 10 Liters and Under in one Package: Packing Instruction Y309 (No UN Packaging Required). Labels Required:Paint, Flammable Liquid, 3, ISO orientation arrows, shipper and consignee information, and the statement "LTD. QTY". For Shipping of product over 10 Liters in one Package:Packing Instruction 309 or 310 dependent aircraft type (UN Packaging Required).Labels Required: Paint, Flammable Liquid, 3, ISO orientation arrows (cargo only aircraft label if applicable), shipper and consignee information.
---	---

## SECTION 15: Regulatory information

# Herculiner Truck Bed Liner Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.1. US Federal regulations

Herculiner Truck Bed Liner Black	
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed 9016-87-9 diphenylmethanediisocyanate, isomers and homologues CBD
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
xylene, mixture of isomers (1330-20-7)	
EPA TSCA Regulatory Flag	EPA: I
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
SARA Section 313 - Emission Reporting	1 % Subject to Form R - Reporting requirements; Subject to Supplier notification

### 15.2. International regulations

#### CANADA

#### WHMIS Classification



Class B Division 3 -  
Combustible Liquid

xylene, mixture of isomers (1330-20-7)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

#### EU-Regulations

No additional information available

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

#### National regulations

xylene, mixture of isomers (1330-20-7)
Listed on RCRA Hazardous Substances Xylenes (1330-20-7) RCRA Code: U239 Listed on CERCLA Hazardous Substances List (RQ 1000 lb) Listed on the SC Toxic Air Pollutants List Listed on Title V Clean Water Act (CWA) 311

### 15.3. US State regulations

xylene, mixture of isomers (1330-20-7)
U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List

## SECTION 16: Other information



# Herculiner Truck Bed Liner Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-statements:

H226	Flammable liquid and vapor
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

### NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

### NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

### NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

#### Health

: 2 Moderate Hazard - Temporary or minor injury may occur

#### Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 °F (22 °C) and boiling points above 100 °F (37 °C), as well as liquids with flash points between 73 °F (22 °C) and 100 °F (37 °C). (Classes IB & IC)

#### Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

### SDS GHS US (GHS HazCom 2012) OWI

*Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.*