



TECHNICAL DATA SHEET

Latex•ite® PLI-STIX®

Manufacturer Product#: 35099 (30 ft. 1/2")

UPC#: 090932350991

Manufacturer Product#: 36099 (60 ft. 1/4")

UPC#: 090932360990



PHYSICAL PROPERTIES & PERFORMANCE

Appearance: Black Solid	Maximum VOC: 0 g/L
Application Temperature: 32° F and rising.	Specific Gravity: N/A
Viscosity: N/A	Weight Per Gallon: Approximately 5 lbs. per gallon
Color: Black	Consistency: Solid
Boiling Point: 225° F	Cure Time (50% relative humidity, 70° F): 20 minutes
Freeze ability: N/A	Container Size & Weight: Approximately 2.25 lbs.

FEATURES

Latex•ite® PLI-STIX® **Permanent Asphalt / Concrete Crack Filler** is the only **PERMANENT** solution to cracks on the marketplace. It is the same product seen on highways and roads but the only difference is **YOU CAN APPLY IT** and don't need a 200 gallon melter to do it! Latex•ite® PLI-STIX® is permanent because it is applied with heat (a simple hand held torch) and it bonds to the sidewalls of the crack. Cracks open up because they expand and contract with freeze/thaw cycles - but Latex•ite® PLI-STIX® will expand and contract right along with Mother Nature! (Note: Pli-Stix® and Crack-Stix® is the same product. Pli-Stix® comes in 30 ft (1/2" diameter) and 60 ft (1/4" diameter) rolls, while Crack-Stix® comes in either 125 ft. or 250 ft. roll.)

- **Only permanent crack filler on the marketplace**
- **30 ft Med Pli-stix® fills cracks up to 1" wide while 60 ft Small Pli-Stix® fills cracks up to 1/2" wide**
- **Hot applied "rope-like" filler bonds to sidewalls**
- **Packaging is Type #1 PET plastic and IS recyclable**
- **Ready to use immediately, melt-away wrapper!**
- **Prevent slip, trip and fall accidents**
- **No VOC's**

SURFACE PREPARATION

Latex•ite® PLI-STIX® is a simple and clean process. Before applying the product, it is important to thoroughly clean out the crack and remove any loose debris. Use a screwdriver and whisk broom. Rinsing the crack and allowing it to dry will give you the best results.

Dalton Enterprises, Inc., 131 Willow Street, Cheshire, CT 06410

Phone 800-851-5606 • Fax (203) 271-3396 • www.latexite.com

Revised 09/28/2016

APPLICATION

Now you are ready to install the Latex•ite®PLI-STIX®. Simply place the Latex•ite®PLI-STIX® into the crack (do not remove the plastic wrap from the Latex•ite®PLI-STIX®). The Latex•ite®PLI-STIX® must be inside the crack so we recommend pushing the Latex•ite®PLI-STIX® into the crack using a screwdriver. (*Note: If the crack is not as wide as the Latex•ite®PLI-STIX®, we recommend stretching the Latex•ite®PLI-STIX® out...you can leave it in the sun for a while to make it easier to stretch. You can also splice it with a razor blade). Once it's in simply light your torch (we recommend a Bernzomatic hand-held torch) and apply direct flame to the Latex•ite®PLI-STIX® until it liquefies - this should take about 20 - 30 seconds. Allow the Latex•ite®PLI-STIX® to set up for 20 minutes.

PRECAUTIONS

Avoid applying when temperatures drop below 32° F. When transporting this product, ensure that the container is secured and the lid is secure. Protective clothing and eyewear should be used during application.

CLEAN UP & STORAGE

To remove Latex•ite®PLI-STIX® heat and scrape off excess material. Do not store in areas above 110°F. Product is non-hazardous.

!!!CAUTION!!!

Latex•ite®PLI-STIX® is for exterior use only. Keep out of reach of children. Keep container capped when not in use. Non-flammable. This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

Emergency & First Aid Procedures:

Eyes: Immediately flush with clean water for 15 minutes while holding eyelids open; consult a physician.

Inhalation: If overcome by mist or vapor, remove from exposure immediately; call a physician. If breathing is stopped or irregular, start resuscitation, administer oxygen.

Skin: Remove any contaminated clothing and wash skin with soap and warm water. Vegetable or mineral oil can remove dry material.

Ingestion: DO NOT INDUCE VOMITING even though vomiting may occur. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Get immediate medical attention.

WARRANTY AND DISCLAIMER

There are no express warranties which extend beyond the description on the face hereof. DALTON ENTERPRISES, INC. DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY, OR OF FITNESS FOR ANY PARTICULAR PURPOSE. Since seller cannot control the manner of use of its products after their sale, seller will not be responsible for any consequential or indirect damages. Rather, seller will, at its options, either replace the goods sold or refund the purchase price. No warranties will apply if the goods are in any way altered or modified after delivery by seller. This warranty does not include labor or cost of labor for the application or consequential damages. This warranty gives you specific rights and you may also have other rights which may vary from state to state.