

# SPT-2 Lamp Wire



**Rated 300 Volts  
Rated 60°C**

**Stranded Copper  
Conductors**

## APPLICATIONS

SPT-2 Lamp Wire is intended for use in small household appliances including clocks, lamps, radios and fans that are not subjected to hard usage.

## CONDUCTORS

Two-stranded copper conductors.

## ASSEMBLY

SPT-2: (Premium Grade) Two conductors laid parallel.

## INSULATION JACKET

Polyvinyl chloride insulation available with black, brown, white, clear, or silver jacket.

## INDUSTRY STANDARDS

UL® Spec. No. 62  
UL E88265  
CSA Spec. C22.2  
CSA Spec. No. 49  
CSA LL081924  
NFPA 70: National Electrical Code

## SURFACE PRINT

Sample: Lamp Wire 16-2: (UL) E88265 SPT-2 60°C 2X16AWG(1.31mm<sup>2</sup>) 300V VW-1 C(UL) TYPE SPT-2 60°C 2X1.31mm<sup>2</sup>(16AWG) 300V VW-1 CERROWIRE

Lamp Wire 18-2: (UL) E88265 SPT-2 60°C 2X18AWG(0.824mm<sup>2</sup>) 300V VW-1 C(UL) TYPE SPT-2 60°C 2X0.824mm<sup>2</sup>(18AWG) 300V VW-1 CERROWIRE

©2010, Cerro Wire LLC  
All Rights Reserved



**cerrowire**

Electrical Division: 800.523.3869 | FAX 877.877.9563  
Consumer Markets Division: 866.572.3776 | FAX 812.793.2626  
www.cerrowire.com

A Marmon Wire & Cable/  
Berkshire Hathaway Company

# SPT-2 Lamp Cord

25' to 250' Lengths

PRODUCT CODE NUMBER	NO. OF COND.	AWG SIZE	COND. STRANDS	NOMINAL INSULATION THICKNESS		NOMINAL OVERALL DIAMETER		CURRENT AMPS <sup>(1)</sup>	APPROX. NET WEIGHT LBS/M <sup>(5)</sup>	JACKET COLOR	UPC CODE
				INCHES	MM	INCHES	MM				
252-1202G3	2	16	0.102/64C	0.045	1.14	0.155 X 0.295	3.7 x 7.2 ± 0.15 mm	13	37	WHITE	048243437306
252-1202A	2	16	0.102/64C	0.045	1.14	0.155 X 0.295	3.7 x 7.2 ± 0.15 mm	13	37	WHITE	048243436866
252-1202B	2	16	0.102/64C	0.045	1.14	0.155 X 0.295	3.7 x 7.2 ± 0.15 mm	13	37	WHITE	048243436897
252-1201B	2	16	0.102/64C	0.045	1.14	0.155 X 0.295	3.7 x 7.2 ± 0.15 mm	13	37	BLACK	048243436835
252-1201A	2	16	0.102/64C	0.045	1.14	0.155 X 0.295	3.7 x 7.2 ± 0.15 mm	13	37	BLACK	048243436804
252-1201G3	2	16	0.102/64C	0.045	1.14	0.155 X 0.295	3.7 x 7.2 ± 0.15 mm	13	37	BLACK	048243437252
252-1208B	2	16	0.102/64C	0.045	1.14	0.155 X 0.295	3.7 x 7.2 ± 0.15 mm	13	37	BROWN	048243436958
252-1208A	2	16	0.102/64C	0.045	1.14	0.155 X 0.295	3.7 x 7.2 ± 0.15 mm	13	37	BROWN	048243436927
252-1208G3	2	16	0.102/64C	0.045	1.14	0.155 X 0.295	3.7 x 7.2 ± 0.15 mm	13	37	BROWN	048243437207

<sup>(1)</sup> Ampacities based on NEC table 400.5 (A).

<sup>(5)</sup> Actual shipping weight may vary.

PACKAGE CODE	A	B	G3
SIZE	25' SPOOL	50' SPOOL	250' SPOOL
18 STRAND	X	X	
16 STRAND			X

# SPT-2 Lamp Cord

25' to 250' Lengths

PRODUCT CODE NUMBER	NO. OF COND.	AWG SIZE	COND. STRANDS	NOMINAL INSULATION THICKNESS		NOMINAL OVERALL DIAMETER		CURRENT AMPS <sup>(1)</sup>	APPROX. NET WEIGHT LBS/M <sup>(2)</sup>	JACKET COLOR	UPC CODE
				INCHES	MM	INCHES	MM				
252-1002A	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	WHITE	048243436569
252-1002G3	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	WHITE	048243437153
252-1002B	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	WHITE	048243436590
252-1001B	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	BLACK	048243436538
252-1001A	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	BLACK	048243436507
252-1001G3	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	BLACK	048243437108
252-1008B	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	BROWN	048243436651
252-1008A	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	BROWN	048243436620
252-1008G3	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	BROWN	048243437054
252-1012B	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	CLEAR	048243436712
252-1012A	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	CLEAR	048243436682
252-1012G3	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	CLEAR	048243437009
252-1015G3	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	SILVER	048243437016
252-1015A	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	SILVER	048243436446
252-1015B	2	18	40/34	0.030	1.14	0.107 x 0.210	3.4x6.8±0.15 3.4 x 6.8	10	22	SILVER	048243436484