

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: BEHR MARQUEE™ INTERIOR SATIN ULTRA PURE WHITE No. 7450

Product Code: 7450 MSDS Manufacturer 7450

Number:

Manufacturer Name: BEHR Process Corporation Address:

3400 W. Segerstrom Avenue Santa Ana, CA 92704 General Phone Number: (714) 545-7101 General Fax Number: (714) 241-1002 Customer Service Phone (800) 854-0133 ext. 2

Number:

For emergencies in the US, call CHEMTREC: 800-424-CHEMTREC:

Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect) MSDS Creation Date: December 03, 2012

MSDS Revision Date: (M)SDS Format:



SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

October 15, 2013

Chemical Name	CAS#	Ingredient Percent
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5 by weight
Titanium dioxide	13463-67-7	10 - 30 by weight
Aluminum hydroxide	21645-51-2	1 - 5 by weight
Nepheline Syenite	37244-96-5	5 - 10 by weight

SECTION 3: HAZARDS IDENTIFICATION

Emergency Overview: Irritant.

Potential Health Effects:

Eye: May cause irritation. Skin: May cause irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting. Chronic Health Effects: Prolonged or repeated contact may cause skin irritation. Signs/Symptoms: Overexposure may cause headaches and dizziness. Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing Conditions: None generally recognized.

SECTION 4: FIRST AID MEASURES

Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists. Eve Contact:

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Skin Contact:

If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention. Inhalation:

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious $\,$ Ingestion:

person.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA),

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Use proper personal protective equipment as listed in section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills $\,$ Spill Cleanup Measures:

immediately observing precautions in the protective equipment section.

SECTION 7: HANDLING and STORAGE

Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Handling:

Storage: Store in a cool, dry, well ventilated area away from sources of heat,

combustible materials, and incompatible substances. Keep container tightly closed when not in use.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid

inhaling vapor or mist.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Use appropriate engineering control such as process enclosures, local

exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the Eye/Face Protection:

European standard EN 166.

Skin Protection Description: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with

eyes, skin or clothing.

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances Respiratory Protection:

where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate

protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an

eyewash facility and a safety shower

EXPOSURE GUIDELINES

Silica, amorphous, precipitated and gel:

TLV-TWA: 10 mg/m3 Guideline ACGIH: OSHA-TWA: 20 mg/m3 Guideline OSHA:

<u>Titanium dioxide</u>:

Guideline ACGIH: TLV-TWA: 10 mg/m3 Guideline OSHA: OSHA-TWA: 15 mg/m3

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid. **Boiling Point:** No Data Melting Point: No Data

Density: 10 - 12 Lbs./gal.

Vapor Density: Greater than 1 (Air = 1).

pH: No Data Molecular Formula: Mixture Molecular Weight: Mixture

Material VOC: 21 gm/l (Includes Water) Coating VOC.: 48 gm/l (Excludes Water) VOC Content:

SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures. Hazardous Polymerization: Not reported.

Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. $\ensuremath{\text{F.}}$ Conditions to Avoid:

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

SECTION 11: TOXICOLOGICAL INFORMATION

Silica, amorphous, precipitated and gel:

RTECS Number: VV7315000

<u>Titanium dioxide</u>:

RTECS Number: XR2275000

Administration onto the skin - Human Standard Draize test.: 300 ug/3D (Intermittent) (RTECS) $\,$ Skin:

IARC: Group 2B: Possibly carcinogenic to humans. Carcinogenicity:

<u>Aluminum hydroxide</u>:

RTECS Number: BD0940000

Nepheline Syenite:

RTECS Number: QP9365000

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the Waste Disposal:

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not Regulated. DOT UN Number: Not Regulated.

SECTION 15: REGULATORY INFORMATION

Silica, amorphous, precipitated and gel:

TSCA Inventory Status: Not listed Canada DSL: Listed

Titanium dioxide:

TSCA Inventory Status: Listed

State Regulations: Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed

Aluminum hydroxide:

TSCA Inventory Status: Listed Canada DSL: Listed

Nepheline Syenite:

TSCA Inventory Status: Not listed Canada DSL: Listed

SECTION 16: ADDITIONAL INFORMATION

MSDS Creation Date: December 03, 2012 MSDS Revision Date: October 15, 2013

MSDS Author: Actio Corporation

Disclaimer:

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.

The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved. Trademark:

 $\label{lem:copyright} \textbf{Copyright} \\ \textcircled{\ontering} \ \ \textbf{1996-2013} \ \ \textbf{Actio} \ \ \textbf{Corporation}. \ \ \textbf{All} \ \ \textbf{Rights} \ \ \textbf{Reserved}.$