

TEXTURED BLACK

TEXTURED BLACK

TEXTURED BLACK



PLAYGROUNDS

PAVEMENT

DRIVEWAYS

PARKING LOTS

BLACKTOP

ASPHALT FILLER & SEALANT



- **FILLS & SEALS CRACKS IN ASPHALT SURFACES**
- **ASPHALT-BASED, LOW SOLVENT FORMULA**
- **EXCELLENT FLEXIBILITY & ADHESION**
- **DURABLE, WEATHERPROOF SEAL**
- **EASY WATER CLEAN UP**
- **EXTERIOR**

WARNING! MAY CAUSE EYE & SKIN IRRITATION.
Read back panel carefully for other cautions.

¡ADVERTENCIA! PUEDE IRRITAR LOS OJOS Y LA PIEL.
Lea atentamente el panel posterior para otras precauciones.

10.1 fl oz (300 mL)

FOR BEST RESULTS: Apply in temperatures above 50°F. Not for continuous underwater use. Do not apply when rain or freezing temps. are forecasted for 24 hours. Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use backer foam rod. Sealant cures fully in approx. 72 hours (depending on temp., humidity & depth of fill). Store away from extreme heat/cold. Keep product from freezing.

INSTRUCTIONS: 1. Surface to be filled should be free of loose, damaged material or other debris/foreign material. Surface should be clean & dry. 2. Cut nozzle at a 45° angle to desired bead size. 3. Puncture inner foil seal. 4. Load into caulk gun. 5. Fill cracks & gaps with sealant. Tool or smooth with putty knife if needed. 6. Clean up excess uncured sealant with a damp sponge before it skins over. Cured sealant must be cut or scraped away. 7. Allow to cure for at least 24 hours before returning area to service, being directly exposed to water or coating with asphalt or tar-based driveway dressing.

COVERAGE: 55 linear ft at 3/16" diameter bead.

Contains: Asphalt, aluminum oxide, iron oxide, and potassium oxide. May cause skin and eye irritation. May cause allergic skin sensitization. Avoid contact with eyes & skin. Do not ingest. Wear rubber gloves & safety glasses with side shields. Use only with adequate ventilation. Avoid breathing vapors. Ensure fresh air entry during application & drying. Close container after each use. Wash thoroughly after handling. **FIRST AID:** SKIN: Immediately remove from skin by wiping with waterless hand cleaner followed by soap & water. EYE: Flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: **DO NOT INDUCE VOMITING.** Get medical attention immediately if complications arise from exposure. **For emergencies,** call poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

NCCC Calif. ARB <1.5 wt/wt% (VOC <5 g/L)



WARRANTY: If product fails to perform when used as directed within one year of date of purchase, call **1-888-DAP-TIPS**, with your sales receipt and product container available, for product replacement or sales price refund. DAP is not liable for incidental or consequential damages.

Contiene: asfalto, óxido aluminico, óxido de hierro y óxido potásico. Puede irritar los ojos y la piel. Podría causar sensibilización alérgica en la piel. Evite el contacto con los ojos y la piel. No lo ingiere. Use guantes y utilice protección para los ojos con protectores laterales. Utilice solamente con ventilación adecuada. Evite inhalar las emanaciones. Proporcionar aire fresco, durante la aplicación y el secado del producto. Cierre el envase después de cada uso. Lávese bien después de manipular el produc. **PRIMEROS AUXILIOS: PIEL:** Retire inmediatamente de la piel utilizando un limpiador sin agua para manos, seguido de agua y jabón. **OJOS:** Enjuague inmediatamente con abundante agua. **INHALACION:** Salir al aire fresco. **INGESTION: NO INDUZCA EL VOMITO.** Busque atención médica de inmediato. Obtenga atención médica inmediatamente si ocurre exposición excesiva. **Para emergencias,** llame al centro de control de envenenamiento al 1-800-222-1222. Refiérase a la SDS para más información. Para una SDS contacte su proveedor o visite dap.com. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ ADVERTENCIA Cáncer y daños al sistema reproductor – www.P65warnings.ca.gov

QUESTIONS/¿PREGUNTAS? Call/Llame al 1-888-DAP-TIPS or visit/o visite dap.com & click on/y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al 1-888-327-8477 o visite dap.com.

DAP Products Inc.
Baltimore, MD
21224

Made in the USA for
DAP Products Inc.
with U.S. and
globally sourced
materials.

dap.com