



The anchor is cold formed and consists of a threaded section with standard coarse bolt threads at one end and a parabolic mandrel at the opposite end for a smoother expansion. It has a 360° one-piece clip that functions as a two-piece clip for more contact, a torque controlled expansion and can be installed into a bottomless hole.

Three head styles are available: Hex Nut, Wire Hanger and Tie Down Hook. Many sizes available in two types of material: Carbon steel and 304 Stainless steel.

WARNING: WEAR SAFETY GOGGLES

COLD FORMED EXPANSION ANCHOR



VIDEO



MOUNTING SPACE



- Anchor size = Hole size
- Fast & easy to install
- Full thread design
- Chamfered head
- Taper shape clip
- Material: High strength carbon steel

INSTALLATION PROCESS

1. Use a carbide bit ANSI B212.15 (-1994) that is the same size as the bolt diameter. Drill hole deeper than bolt embedment (min. 0.5 dia.) Do not use core bits. Maintain accurate hole size.
2. Clean hole using a dust blower or compressed air.
3. Add washer and thread nut 1/8" from the top of bolt. Drive bolt into hole through item to be fastened.
4. To set, tighten nut 3 to 4 full turns or consult chart for guide installation torque.

CERTIFICATIONS & APPROVALS

