

# d-c-fix<sup>®</sup> Outdoor Floor DIY Outdoor Flooring

## d-c-fix<sup>®</sup> Outdoor Floor



d-c-fix® Outdoor Floor is a simple to Do-it-Yourself solution providing aesthetics and outstanding outdoor performance withstanding cold temperatures, extreme UV exposure and precipitation. Ideal for decks, porches, balconies and patios.

#### **Product Overview**

Description	Single-ply printed & embossed vinyl sheet laminated to non-woven fabric	
Application	Outdoor Flooring, Decking and similar outdoor applications	
Processing	Adhesive application using construction adhesive	

#### **Dimensional, Color & Weight Properties**

Total Thickness	0.9 mm base film laminated with 85 grams per square meter of PES non-Woven Backing	
Width	1828 mm	
Roll Size	6' x 12'	
Property	Value	
Property	Value	

### **Physical Properties**

Elongation MD/CD	>80 % MD >90% CD	ASTM D751-B 1" strip, 12 in/min
Breaking Strength	>300 N MD >300 N CD	ASTM D751-B 1" strip, 12 in/min
Low Temperature	Passes -30°C	ASTM D1790
Test Type	Results	test standard

#### **Colorfastness & Surface Durability**

Heat Resistance	No Cracking or Crazing after exposure AATCC Grey Scale 3 or Greater	0.68 W/fil2@340 fiff UV Cycle: 8hrs @ 60°C, 
Accelerated Weathering	No Cracking or Crazing after 3000 hrs, AATC Grey Scale 3 or greater,	ASTM G-154 Sunlamp: UVA340 0.68 W/m2@340 nm

#### **Additional Properties**

Slip Resistance	0.58	EN 13893:2002
Slip Resistance	Classification: R 11	DIN 51130
Slip Resistance (dry)	0.643	ASTM F1678
Phthalate Ester Content	Less than 0.1%	CPSC-CH-C1001-09.4
Heavy Metal Content	Less than 100 ppm for Cd, Hg, Pb and Cr(VI)	EN 71-3, migration of certain elements, category 3

Properties listed do not constitute a warranty or specification. Test values are based on material conditioned and tested in a controlled laboratory using established standards and procedures. Properties vary based on embossed grain, color, multi-ply lamination and other variables.

#### O'Sullivan Films, Inc.

1944 Valley Avenue | Winchester, Virginia 22601 | USA Phone: +1 800 336 9882 | www.continental-industry. com



For more information, available colors and additional collections, scan this code and visit www.dcfixbrand.com.

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2021 ContiTech AG. All rights reserved. For complete information go to: www.continental-industry. com/discl\_en.