Version: V1.3

SDS

SAFETY DATA SHEET

According to 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Prepared For: ShenZhen Better New Energy Technology Co., LTD

1 / F, Building 4, Anjia Industrial Park, Yantian

Village, Fenggang Town, Dongguan City.

Prepared By: Shenzhen LCS Compliance Testing Laboratory Ltd.

101, 201 Building A and 301 Building C, Juji

Industrial Park, Yabianxueziwei, Shajing Street,

Baoan District, Shenzhen, Guangdong, China

Issue Date : 2019.11.22

Report

: LCS191120019ASD

Number

Written by: <u>Seven liu</u> Approved by:

(29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

Version: V1.4

* The SDS is prepared based on the information provided by client. The contents and formats of this SDS are revised as per client's request.

	Section 1- Identifi	cation			
(a) Product identifier					
Product name	Li-ion Polymer Rechargeable Cell				
(b) Other means of ident	tification				
Product description	Model: 18650 2000mAh Nominal Voltage: 3.7V Nominal capacity: 2000mAh Watt-hour: 7.4Wh Weight: 43.0g				
(c) Recommended use of	of the chemical and restrictions on use				
Recommended use	LITHIUM ION BATTERIES				
Uses advised against	No information available.				
(d) Details of the supplie	er of the safety data sheet				
Supplier Name	ShenZhen Better New Energy Technolo	gy Co., LTD			
Supplier Address	1 / F, Building 4, Anjia Industrial Park, Yantian Village, Fenggang Town, Dongguan City.				
Manufacture Company	ShenZhen Better New Energy Technology Co., LTD				
Manufacture Address	1 / F, Building 4, Anjia Industrial Park, Y	antian Village, Fenggang Town, Dongguan City.			
Supplier Phone Number	+86-755-28319672				
(e) Emergency telephon	e number				
+86-755-28319672					
	Section 2- Hazards ide	entification			
1910.1200). This produc	t is an article which is a sealed battery a	Hazard Communication Standard (29 CFR and as such does not require an MSDS per the zards indicated are for a ruptured battery.			
Reproductive toxicity		Category 2			
Acute toxicity-Oral		Category 3			
Skin corrosion/ irritation		Category 1			
Specific target organ toxic	city-repeated exposure	Category 1			
(b) GHS Label elements	, including precautionary statements				
Emergency Overview					

According to 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

Version: V1.4

Signal word Danger

Hazard Statements

Suspected of damaging fertility or the unborn child Toxic if swallowed

Causes severe skin burns and eye damage

Cause damage to organs through prolonged or repeated exposure.



Appearance:	No information available Physica	al State: Solid	Odor: No information available
P101	If medical advice is needed,,have	product containet	or label at hand
P201	Obtain special instructions before	use.	
P202	Do not handle until all safety preca		read and understood.
P260	Do not breathe dust/fume/gas/mis	t/vapours/spray.	
P264	Wash thoroughly after handling.		
P270	dust/fume/gas/mist/vapours/spray		
P280	Wear protective gloves/protective	clothing/eye protec	ction/face protection
	IF exposed or concerned: Get med	dical advice/ attent	ion.
P308+P313	IF SWALLOWED: Immediately cal	II a POISON CENT	ER/doctor/\u2026.
P301+P310	Specific treatment (see on this I	abel).	
P321	Rinse mouth.		
P330	IF SWALLOWED: Rinse mouth. D	o NOT induce vom	niting.
P301+P330+P3	[or shower]	nediately all contan	ninated clothing. Rinse skin with water
P303+P361+P3	Wash contaminated clothing befor	e reuse.	
P363	IF INHALED: Remove person to fr		comfortable for breathing.
P304+P340	Immediately call a POISON		g.
P310	CENTER/doctor/\u2026		
P305+P351+P3 P314	IF IN EYES: Rinse cautiously with present and easy to do. Continue		minutes. Remove contact lenses, if
	Get medical advice/attention if you	ı feel unwell.	
P405	Store locked up.		
P501	Dispose of contents/container to		
i a	'		

(c) Hazards not otherwise classified (HNOC)

Not applicable

(d) Unknown Toxicity

32% of the mixture consists of ingredient(s) of unknown toxicity

According to 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

Version: V1.4

(e) Other information

Very toxic to aquatic life with long lasting effects

(f) Interactions with Other Chemicals

No information available.

Section 3- Composition/information on ingredients

Chemical Name	CAS Number	Weight (%)	Trade Secret
Lithium Cobalt Oxide (CoLiO ₂)	12190-79-3	38.96	*
Copper	7440-50-8	6.63	*
Graphite	7782-42-5	37.58	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	4.56	*
Aluminum foil	7429-90-5	12.27	*

[&]quot;*" The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4- First-aid measures

Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

Section 5- Fire-fighting measures

(a) Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

(b) Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

(c) Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

(d) Hazardous Combustion Products

Carbon oxides.

(e) Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6- Accidental release measures

According to 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

Version: V1.4

(a) Personal precautions, protective equipment and emergency procedures

If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed with sand, earth or other inert substance and contaminated area should be ventilated meantime.

(b) Environment precautions

Do not allow product to reach sewage system or any water source.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers surface or ground water.

(c) Methods and material for containment and cleaning up

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

Section 7- Handling and storage

(a) Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

(b) Conditions for safe storage, including any incompatibilities Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases

Section 8- Exposure controls/personal protection

(a) Control parameters

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite 7782-42-5	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Graphite in presence of Polycyclic aromatic hydrocarbons PAH
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	TWA: 0.02 mg/m³	-	-
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA:2.5mg/m³ F	TWA:2.5mg/m³ F TWA:2.5mg/m³ dust (vacated)TWA:2.5mg/m³	
Copper 7440-50-8	TWA:0.2mg/m³ fume TWA:1mg/m³Cu dust and mist	TWA:0.1mg/m³fume TWA:1mg/m³dust and mist (vacated) TWA:0.1mg/m³Cu	IDLH:100mg/m³dust ,fume and mist TWA:1mg/m³dust and mist

(29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

				REPOR	Г NO.: LCS191120019ASD		
				dust,fume,mist	TWA:0.1mg/m³ fume		
Aluminum foil	TW	A:1mg/m³ re	spirable fraction	TWA:15mg/m³ total dust	TWA:10mg/m³ total dust		
7429-90-5				TWA:5mg/m³respirable fraction	TWA:5mg/m³ respirable dust		
				(vacated)			
				TWA:15mg/m³total dust			
				(vacated) TWA:5mg/m³ respirable fraction(vacated)			
				TWA:5mg/m³ AL Aluminum			
				sts - Threshold Limit Value ble Exposure Limits Immediately Dange	erous to Life or Health		
				Court of Appeals decision in AF ion 15 for national exposure co			
(b) Appropriate	engine	ering contro	ols				
Showers Engineering Measures Evewash							
Engineering Measures Eyewash s Ventilation							
(c) Individual pro	otectio		•	nal protective equipment			
Eye/Face Protection None requi Face protection			red for consumer use. If there is a risk of contact:. Tight sealing safety goggles. Ition shield.				
Skin and body Protection		protective cl					
Respiratory Protection				eded under normal use conditic enced, ventilation and evacuati			
Hygiene Measures Handle in accordance with good industrial hygor smoke when using this product. Take off coreuse. Avoid contact with skin, eyes or clothing protection. Contaminated work clothing should Regular cleaning of equipment, work area and before breaks and immediately after handling remove and wash all contaminated protective available.			duct. Take off contaminated clot eyes or clothing. Wear suitable colothing should not be allowed t, work area and clothing is reco y after handling the product. Fo	hing and wash before e gloves and eye/face out of the workplace. ommended. Wash hands r environmental protection,			
	Se	ection 9-	Physical a	nd chemical proper	ties		
Form			Solid				
Color			Purple				
Odor			Not Available				
рН			Not Available				
Melting point/free	ezing po	oint	Not Available				
Boiling Point and	Boiling	g range	Not Available				

(29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

	REPORT NO LCS 1911200 19ASD
Flash Point	Not Available
Upper/lower flammability or explosive limits	Not Available
Vapor Pressure	Not Available
Vapor Density	Not Available
Relative density	Not Available
Solubility in Water	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Evaporation rate	Not Available
Flammability (soil, gas)	Not Available
Viscosity	Not Available
Sect	ion 10- Stability and reactivity
Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Exposure to air or moisture over prolonged periods. Excessive heat.
Incompatible materials	Acids. Bases. Oxidizing agent.
Hazardous Decomposition Products	Carbon oxides.
Section	n 11 – Toxicological information
Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
Eye contact	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.

(29 CFR 1910.1200)

Specific test data for the substance or mixture is not available. Causes

REPORT NO.: LCS191120019ASD

Ingestion		burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.							
Component Information									
Chemical Name		Oral LD50		Derm	nal LD50	Inhalation LC50			
Graphite 7782-42-5		> 10000 mg/kg (F	Rat)	> 3 g/k	g(Rabbit)	-			
Information on toxicolog	gical effect	s							
Symptoms		Erythema (sk Itching. Rashe		ss). May c	ause redness a	and tearing of the eyes.			
Delayed and immediate	effects as	well as chronic	effects f	rom short	and long-term	exposure			
Sensitization:		May cause sensitization of susceptible persons. May cause sensitization by skin contact.							
Mutagenic Effects:			No information available.						
Carcinogenicity:		The table below indicates whether each agency has listed any ingredient a carcinogen.							
Chemical Name	A	CGIH	I.A	ARC	NTP	OSHA			
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3		A3	Group 2B			Х			
Graphite 7782-42-5		A3	Gro	up 2B		X			
ACGIH (American Conference A3 - Animal Carcinogen IARC (International Agency fo Group 2B - Possibly Carcinoger OSHA (Occupational Safety at X - Present	r Research o l nic to Humans	n Cancer)		nent of Labor)					
Reproductive Toxicity		No information available.							
STOT - single exposure		No information available.							
STOT - repeated exposure		Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).							
Chronic Toxicity			ntains a known or suspected carcinogen. Avoid repeated exposure. solonged exposure may cause chronic effects. May cause adverse liver ects.						
Target Organ Effects						act (GI). Central Vascular system. Systemic			

(29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

Aspiration Ha	nzard	No information available.					
Numerical me	easures of toxicity Pro	duct Information					
_	values are calculated	based on	ATEmix (d	oral):	12,905.00 mg/kg		
chapter 3.1 of	f the GHS document		ATEmix (10,200.00 mg/kg (ATE)		
	Secti	on 12- Ecol	ogical	information			
Ecological To	exicity	Very toxic to aqua	atic life with	n long lasting effects	i.		
Chemical name	Toxicity to Algae	Toxicity to Fish		Toxicity to Microorganisms	Daphnia Magna (Water Flea)		
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L			48h EC50: = 0.03 mg/L		
Graphite 7782-42-5					24h EC50: > 5600 mg/L		
Persistence a	and Degradability	No information ava	ilable.				
Bioaccumula	ation	No information ava	ilable.				
Other adverse	e effects	No information available.					
	Section	on 13- Dispo	sal co	nsiderations			
Waste treatm	ent methods						
Disposal met	hods	regulations (40 C it is mixed with or chemical addition or otherwise alter	FR 261). To therwise are made ed. Consulardous was	This material could be comes in contact we to this material, or lt 40 CFR 261 to dette. Consult the apprending the consult the apprending the consult the consult the consult the consult the apprending the consult the consu	aste according to Federal ecome a hazardous waste if ith a hazardous waste, if if the material is processed termine whether the altered opriate state, regional, or		

(29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

Contaminated Packaging		be in accordance with applicable regional, national and	
	local laws and re	gulations.	
California Hazardous Waste Co This product contains one or mor		sted with the State of California as a hazardous waste.	
Chemical Na	me	California Hazardous Waste	
Lithium Cobalt Oxide 12190-79-3	` '	Toxic	
Copper 7440-50-8		Toxic	
Aluminum fo 7429-90-5	oil	Ignitable powder	
Se	ection 14 – Trai	nsport information	
UN Number -DOT, IMDG, IATA	UN 3480 & UN 3481		
UN Proper shipping name -DOT, IMDG, IATA	Lithium ion Batteries (Including lithium ion polymer batteries) or; Lithium ion Batteries contained in equipments (Including lithium ion polymer batteries) or; Lithium ion Batteries packed with equipment (Including lithium ion polymer batteries)		
Transport information	and has passed in a subsection 38.3. The transportation of Air Transport Associat RUCTION 965, or to SGR 60th Edition for transional Maritime Datation listed in 49 CFR Lithium batteries shippequipment",or "Lithium as "Dangerous Goods"	argeable Cell (Sample Model: 18650 2000mAh) is tested ccordance with UN manual of Tests and Criteria, Part III, lithium cells and batteries is regulated by the International tion (According to Section II/ Section IB of PACKING INST Section II of PACKING INSTRUCTION 966~967 of IATA Deansportation), International Civil Aviation Organization, International Civil Aviatio	
Transport hazard class(es) -DOT, IMDG, IATA	9		
Environmental hazards	Yes(DOT)		
Marine pollutant	Symbol (fish and tree))	
Special precautions for user EMS Number	Warning: Miscellaneo	us dangerous substances and articles	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable		
DOT Remarks:	Special marking with t	the symbol (fish and tree)	
IMDG Limited quantities (LQ) Excepted quantities (EQ)	0 Code: E0 Not permitted as Exce	epted Quantity	

(29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

	S	ectio	on 1	5- R	egula	tory	inforn	nation		30131120013A0D
(a) International I	nventories									
TSCA	Complie	es.								
DSL	All com	ponent	s are l	listed e	ither on	the DSL	or NDS	L.		
(b) US Federal Re	gulations									
SARA 313	Section 313 of Title III of the ARA 313 (SARA). This product containing requirements of the Act and			ct conta	ains à ch	emical o	or chemic	cals which are	subjec	t to the reporting
Chemical Name		CAS No				١	Weight-%	,		313 – Threshold Values %
Lithium Cobalt Oxio (CoLiO ₂)	de	12190-79					15-40			0.1
Copper		744	0-50-8	}			3-7			1.0
Aluminum foil			9-90-5	5			7-13			1.0
SARA 311/312 Haz		ries								
Acute Health Hazar			No							
Chronic Health Haz	ard		No							
Fire Hazard			No							
Sudden release of p	pressure haz	ard	No							
Reactive Hazard			_	No This product contains the following substances which are regulated						
CWA (Clean Water Act)			itants p						regulated 21 and 40 CFR	
Chemical Name CWA - Reportab		-		WA - To Pollutant			A - Priority ollutants	С	WA - Hazardous Substances	
Copper 7440-50-8					Х		X			
CER	CLA		haza	ardous	substan	ice unde	r the Co		Environ	ces regulated as a imental Response
Chemical N	ame	Haz	ardous	s Subst RQs					RQ	
Copper 7440-50-			5	000 lb				5000 lb final RQ 2270 kg final RQ		
(c) US State Regu	ılations									
California Proposi	tion 65				This pr	oduct co	ntains th	e following P	ropositi	on 65 chemicals.
CI	nemical name	e		California Proposition 65						
	hite – 7782-4							Carcinogen		
U.S. State Right-to			ıs		<u> </u>			22.009011		
Chemical Name	New Je			sachus	etts	Pennsyl	vania	Rhode Isl	and	Illinois
Graphite 7782-42-5	Х			Х		X				Х
Lithium Cobalt Oxi (CoLiO ₂) 12190-79-3	de					Х		х		Х
Aluminum 7429-90-5	Х			Х		Х		Х		
Copper 7440-50-8	Х			Х		Х		х		X

According to 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

REPORT NO.: LCS191120019ASD

Version: V1.4

(d) Inter	national Regulation	าร						
Mexico								
National	occupational expos	sure lin	nits					
	Component		Carcin	ogen	Status		Exposure Limits	
7	Graphite 7782-42-5 (15 - 40)						Mexico: TWA=3.5 mg/m ³	
Aluminum 7429-90-5 (7 - 13)							Mexico: TWA= 10 mg/m ³	
Copper 7440-50-8 (3 - 7)					Mexico: TWA= 1 mg/m ³ Mexico: TWA= 0.2 mg/m ³ Mexico: STEL= 2 mg/m ³			
Mexico - O	ccupational Exposure Limi	ts - Carci	inogens			•	•	
Canada								
WHMIS	Hazard Class		Not determined					
		S	ection 16-	Othe	er informat	ion		
NFPA	Health Hazards	1	Flammability	0	Instability	0	Physical and Chemical Hazards	-
HMIS	Health Hazards	2*	Flammability	0	Physical Hazard	0	Personal Protection	X

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

******End of Safety Data Sheet*****